

Flowcooler with air-cooled cooling machine and closed evaporator, for the cooling of circulators connected in series, housing of stainless steel with handle. The refrigerating unit works continuously.

### Technical data according to DIN 12876

Operating temperature range	-30...50 °C	
Safety classification	Class I / NFL	
Cooling power		<b>Order-No.: 3002.0002.99</b>
at 15°C	0,6 kW	
at 0°C	0,47 kW	
at -20°C	0,12 kW	
Refrigeration machine	air-cooled, natural refrigerant	
Refrigerant	R290	
Liquid connection	M16x1 male	
Overall dimensions WxDxH **	280x340x460 mm	
Net weight	30 kg	
Power supply requirement	110V 1~ 50/60Hz	
min. Fuse (1 phase)	10A	
max. Fuse (1 phase)	16A	
min. ambient temperature	5 °C	
max. ambient temperature	40 °C	

from Serial-No.:

1.0/09

Technical details and dimensions are subject to change. No liability is accepted for errors or omissions.

Output data valid for: Room temperature 20° C

in accordance with EN60034-1 the following voltage and frequency tolerances are valid:

Voltage + / - 5% with a simultaneous frequency tolerance of + / - 2%

Example -5% voltage and + 2% frequency -> not allowed!

-5% voltage and - 2% frequency -> allowed

\*\* Please respect space requirements. See operating conditions at [www.huber-online.com](http://www.huber-online.com)