



Nitrile



Lab & Utility

TouchNTuff®

ADVANCED PRODUCT & WORKER PROTECTION

92-605 Nitrile Glove

Proven splash resistance against hazardous chemicals

FEATURES AND BENEFITS:

Outstanding Chemical Resistance

Further testing of the TouchNTuff® gloves by a certified body on an even wider range of chemicals confirms that it resists a greater variety of industrial chemicals for longer periods than any other nitrile disposable gloves.

Excellent puncture resistance

Manufactured from nitrile, TouchNTuff® gloves offers up to four times the puncture resistance of comparable natural rubber latex, and three times the resistance of similar neoprene gloves.

Prevention from Type I Allergy

It contains no natural rubber latex proteins, which prevents Type I allergies for the wearer. Primary skin irritation studies and Insult Patch tests have also shown no evidence of risk from irritation or allergic contact dermatitis.

Easy Donning and Strong Grip

With a unique “Thin Nitrile Technology” formulation, this glove offers easy donning and strong grip in wet or dry conditions. The glove is highly versatile and suitable for many different uses.

Inspected according medical requirements

Inspected to an AQL of 1.5 for pinholes, which matches the standards for medical gloves.



Ansell

TECHNICAL DATA SHEET:

PRODUCT INFORMATION:

	92-605
Material	Nitrile
Color	Green
Glove Design	Ambidextrous, Powder Free, Textured Fingers
Cuff	Beaded Cuff
Audit Standards	ISO 9001
Quality Control	EN420, EN374/1,2,3, ASTM D 6319, FDA 21 CFR 177-2600, Arrete 09/11/04, European Regulation 1935/2004, German Recommendation for Food Commodities.
Packaging	100 gloves per dispensers, 10 dispensers per shipper carton, 1000 gloves per shipper cartons
Storage	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country of Origin	Thailand

PHYSICAL PROPERTIES:

	PROPERTY	TYPICAL VALUES				TESTING METHOD
	SIZE	S 6½-7	M 7½-8	L 8½-9	XL 9½-10	ASTM D3767/EN 420
Length (mm)	92-605	300	300	300	300	
Average Palm Width (mm)	92-605	82	90	99	105	

Freedom from Holes (Inspection level I)	1.5 AQL	ASTM D5151/EN 374-2
Palm Thickness Single Wall	(mm: 0.12) / (mils: 4.7)	ASTM D3767/EN 420

	BEFORE AGING	AFTER AGING	
Ultimate Tensile Strength	> 14 Mpa	> 14 Mpa	ASTM D 412-06a
Elongation at Break (%)	> 500	> 400	ASTM D 412-06a
Force at break (N)	> 6	> 6	EN 455-2

ORDERING INFORMATION:

	SIZE	S 6½-7	M 7½-8	L 8½-9	XL 9½-10
92-605	ORACLE	114096	114097	114098	114099

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

For additional information, call **1-800-800-0444** or visit **www.ansellpro.com**

Ansell

111 Wood Avenue South, Suite 210
Iselin, NJ 08830

* and ™ are registered trademarks owned by Ansell Limited or one of its affiliates.
US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking
© 2014 Ansell limited. All rights reserved.

92-605_PP 062014



EN 374



EN 374



EN 421



Ansell