

Heat Exchanger Unit with circulation pump (industrial plastic material). Housing, atmospheric open expansion tank and heat exchanger. For externally closed applications.

Special Case: Acetone and Polyglycol: The plastic pump is not resistant against acetone and polyglycols (depending on the manufacturer). It is recommended that water is mixed with either glysantine or ethylene glycol for freeze protection. A more resistant plastic is available on request at an additional cost.

Technical data according to DIN 12876

Operating temperature range	(5)...(80) °C
Safety classification	Class I / NFL
Cooling power with delta T 5K ¹	0,28 kW
Cooling power with delta T 10K ¹	0,48 kW
Cooling power with delta T 15K ¹	0,65 kW
Cooling power with delta T 20K ¹	0,8 kW
Pressure pump	
max. delivery	8 l/min
max. delivery pressure	0,2 bar
Pump connection	M16x1 male
max. permissible kin. viscosity	50 mm ² /s
Overall dimensions WxDxH **	280x427x414 mm
Net weight	21 kg
Power supply requirement	208V 2~ 60Hz
Protection class	IP20
max. ambient temperature	40 °C
min. ambient temperature	5 °C



Order-No.: 3011.0013.99

from Serial-No.:

1.0/12

Technical details and dimensions are subject to change. No liability is accepted for errors or omissions.

Output data valid for: the given temperature difference Delta T¹ between environment temperature 20 °C and return temperature.

In accordance with EN60034-1 the following voltage and frequency tolerances are valid:

Voltage + / - 10%, as long as the frequency tolerance does not run in the opposite direction.

Example: -10% voltage and + 3% frequency -> not allowed !

-10% voltage and -3% frequency -> allowed.

** Please respect space requirements. See operating conditions at www.huber-online.com