

Seven2Go™ Conductivity Everywhere You Measure



Simple and reliable, attractively designed and robust. The Seven2Go portables are engineered to provide users with fast quality data, one-handed operation, and durability, making them ideally suited for mobile applications in the laboratory, at-line, or outdoors.

METTLER TOLEDO

Your Mobile Lab, Wherever You Go

Quality Measurement Made Mobile

Routine & Pro meters



Simple Menu – Intuitive Operation

Seven2Go's new intuitive menu guarantees out-of-the-box operation for anyone. Users no longer need to study lengthy operating instructions.




T-Pad – Comfortable, Fast Navigation

Seven2Go's new T-Pad improves the speed with which you move through menus. The smart button arrangement allows for faster navigation that provide you shorter time to actual measurement.



ISM® Ready – Reduced Chances for Error

Upon connection of any InLab ISM (Intelligent Sensor Management) sensor, the instrument automatically recognizes the sensor and stores sensor ID, serial number, and last calibration data.



IP67 – Weatherproof and Robust Design


Thanks to its IP67 protection and drop test resistance, the new Seven2Go portables are able to withstand harsh and demanding environments.

Pro meters only



12 Languages – No more Confusion

The Seven2Go supports 12 languages and offers a user interface that uses complete words and sentences. The lack of cryptic expressions simplify operation and reduces strain on the user.



Sunlight-proof – Always Brilliant Readability

The screen's contrast is enhanced by direct sunlight. This guarantees an excellent readability even under bright and sunny conditions.



StatusLight™ – Easy Readiness Check

Thanks to the new StatusLight you are instantly aware of how the meter is doing. An easy to understand traffic light concept shows if your meter is ready or not.

Specification for Seven2Go



| Measurement Parameters | Specifications | S3 Conductivity | S7 Conductivity |
|---|---|---------------------------------------|--------------------------------|
| Conductivity | Measuring range | 0.01 µS/cm...500 mS/cm | 0.01 µS/cm...1000 mS/cm |
| | Resolution | 0.01...1 | 0.01 |
| | Accuracy | ± 0.5% (electronic) | ± 0.5% (electronic) |
| TDS | Measuring range | 0.01 mg/L...300 g/L | 0.01 mg/L...600g/L |
| | Resolution | 0.01...1 | 0.01...1 |
| | Accuracy | ± 0.5% | ± 0.5% |
| Specific Resistance | Measuring range | 0.00..100.0 MΩcm | 0.00..100.0 MΩcm |
| | Resolution | 0.01...0.1 | 0.01...0.1 |
| | Accuracy | ± 0.5% | ± 0.5% |
| Salinity | Measuring range | 0.00...42 psu | 0.00...42 psu |
| | Resolution | 0.01...0.1 | 0.01...0.1 |
| | Accuracy | ± 0.5% | ± 0.5% |
| Conductivity Ash | Measuring range | 0.00...2022% | 0.00...2022% |
| | Resolution | 0.01, 0.1, 1% (auto) | 0.01, 0.1, 1% (auto) |
| | Accuracy | 0.50% | 0.50% |
| Temperature (°C) | Measuring range | -5...105 | -5...105 |
| | Resolution | 0.1 | 0.1 |
| | Accuracy | ± 0.2 | ± 0.1 |
| | ATC/MTC | Yes | Yes |
| | Choice of reference temp (20/25 °C) | Yes | Yes |
| | Temperature Compensation | Linear | Linear, non-linear, pure water |
| Calibration | Calibration points | 1 | 1 |
| | Predefined conductivity standards | 3 | 3 |
| | User-defined conductivity standards | Yes | Yes |
| | Manual cell constant entry | Yes | Yes |
| General Measurement Specifications | Time-dependent endpoint recording | Yes | Yes |
| | Serial measurements in user-defined time interval | Yes | Yes |
| | Acoustic endpoint signal | No | Yes |
| | Visual endpoint signal | Yes | Yes |
| Data Security/Storage | StatusLigth™ | No | Yes |
| | ISM® | Yes (Light version) | Yes |
| | Time and date | No | Yes |
| | User management (Routine, Expert, Outdoor) | No | Yes |
| | Data storage | 200 | 2000 (GLP conform) |
| | Calibration reminder | No | Yes |
| | Sensor ID, SN; Sample ID; User ID | No | Yes |
| | User-defined alarm limits | No | Yes |
| PIN protection | No | Yes | |
| Connectors | Sensor inputs | LTW 7-pin (IP67) | LTW 7-pin (IP67) |
| | Communication interfaces | No | Micro-USB (USB Device) |
| General | Size/weight instrument | 222 x 70 x 35 mm / 270 g | 222 x 70 x 35 mm / 290 g |
| | Power supply | 4 x 1.5V AA or 1.3V NiMH accumulators | |
| | Operating hours | 250...400 hrs | 200...250 hrs |
| | Display | Segmented LCD display | Graphic LCD display |

Order Information

| Order info | Description | Ideally suited for | Order no. |
|------------------|---|--|-----------|
| S3-Meter | Includes instrument, electrode clip, operating instructions, quick guide, test certificate declaration of conformity and batteries. | | 30207954 |
| S3-Standard kit | As S3-Meter, but also with InLab 738-ISM, bottles for calibration and sachets of conductivity standards 1413 $\mu\text{S}/\text{cm}$ and 12.88 mS/cm . | Aqueous samples with mid- to high conductivity. | 30207955 |
| S3-Field kit | As S3-Standard kit, but including uGo™ carrying case. | As above, but especially for measurements on the go. | 30207956 |
| S3-Cond. Ash kit | As S3-Field kit, but with InLab 725 instead of InLab 738-ISM. | Bioethanol and biofuels. | 30207957 |
| S7-Meter | Includes instrument, LabX direct pH, USB cable, electrode clip, base accessory, operating instructions, quick guide, test certificate, declaration of conformity and batteries. | | 30207961 |
| S7-Standard kit | As S7-Meter but, also with InLab 738-ISM, bottles for calibration and sachets of conductivity standard 1413 $\mu\text{S}/\text{cm}$ and 12.88 mS/cm . | Aqueous samples with mid- to high conductivity. | 30207962 |
| S7-Field kit | As S7-Standard kit, but including uGo™ carrying case. | As above, but especially for measurements on the go. | 30207963 |
| S7-USP/EP kit | As S7-Field kit, but with InLab 742-ISM instead of InLab 738-ISM. | Ultra-pure water and low conductivity samples. | 30207873 |

Accessories for Seven2Go

| | Order no. |
|--|-----------|
| uGo carrying case | 30122300 |
| Seven2Go meter benchtop stabilizing base | 30088880 |
| Seven2Go electrode clip and electrode clip covers (4 pieces) | 30113406 |
| Seven2Go wrist strap (METTLER TOLEDO) | 30088887 |
| Seven2Go micro-USB to standard-A USB cable | 30097888 |
| Seven2Go DC wallplug adapter for USB cable (includes international converters) | 30207980 |

Everything you need for precise and reliable measurements:



► www.mt.com/electrode-guide



► www.mt.com/buffers

www.mt.com/pH

For more information



Mettler-Toledo AG, Analytical

CH-8603 Schwerzenbach, Switzerland
Tel. +41 22 567 53 22
Fax +41 22 567 53 23

Subject to technical changes
© 06/2014 Mettler-Toledo AG, 30208974
Marketing pH Lab / MarCom Analytical

