CLïR 5200 SERIES

TYPE I ULTRAURE POU WATER SYSTEM

HPLC GC/MS TRACE ORGANICS

Designed specifically for trace organics and analytic chemistry applications requiring low organics and bacteria, the CLiR 5200 delivers 2.5 LPM of Type I, 18.2 Megohm water quality on demand. The water is purified using a staged purification process which includes high purity ion exchange resins to remove dissolved minerals, and ultraviolet light for bacteria sterilization and TOC reduction. As the water exits the system, a final filter removes particulates and bacteria to reach Type I specifications.



HIGHLIGHTS

- 2.5 Lpm Of 18 Megohm Type 1 Reagent Water On Demand
- Intuitive, User Friendly Touch-Screen Interface
- Real Time Quality Monitoring With Leak Detection
- Compact Design With Remote Dispense Option
- Quick Change, No Tools Cartridge Design
- Large Capacity, Low Cost Consumables Cartridges
- Genuine Resintech Media

CONFIGURATIONS

- Conditioning Cartridge
- Polishing Cartridge
- UV Oxidation
- 0.2 Micron Filtration

PERFORMANCE SPECIFICATIONS

- Max Pressure of 90 PSIG Max. / 20 PSIG Min.
- Max Temperature of 100°F (30°C)
- Resistivity of 18.2 Megohms
- Bacteria Removal of < 1 CFU / mL
- Particulates at < 0.02 µm filtration

| CONFIGURATION | SYSTEM VOLTAGE | TOTAL ORGANIC CARBONS | PART NUMBER |
|-----------------|----------------|-----------------------|--------------|
| Benchtop | 120V/60Hz | < 5 ppb | CLS-5200-S-1 |
| Benchtop | 220V/50Hz | < 5 ppb | CLS-5200-S-2 |
| Remote Dispense | 120V/60Hz | < 5 ppb | CLS-5200-R-1 |
| Remote Dispense | 220V/50Hz | < 5 ppb | CLS-5100-R-2 |





INSTALLED OPTIONS & ACCESSORIES†

| DESCRIPTION | PART NUMBER |
|------------------------------|-------------|
| Direct Feed Port | CLA-5000-DF |
| Recirculating Dispensing Gun | CLA-5000-DG |
| CLïR Wall Mount Bracket | CLA-5000-WB |

 $^{^{\}scriptscriptstyle \dagger}$ Options must be preordered for factory installation

CARTRIDGES & FILTERS^{††}

| DESCRIPTION | PART NUMBER |
|--|--------------|
| CLïR Dual Conditioning Cartridge (RO Feed) | CLF-5000-C1 |
| CLiR Dual Conditioning Cartridge (SDI / TAP Feed) | CLF-5000-C2 |
| CLïR Polishing Ultrapure Cartridge | CLF-5000-P1 |
| CLïR Polishing Ultrapure Low Organics Cartridge | CLF-5000-P2 |
| 0.2 Micron Capsule Filter - 1/4" MNPT x 1/4" hose barb | CLF-5000-020 |
| 0.2 Micron Endotoxin Removal Capsule Filter - 1/4" MNPT x 1/4" hose barb | CLF-5000-02E |

 $^{^{\}dagger\dagger}$ Cartridges and Filters are not included in a system and are ordered separately

CONSUMABLES

| DESCRIPTION | PART NUMBER |
|---|--------------|
| CLïR Ultrafilter - 3/8" Quick Disconnect Fitting | CLF-5000-005 |
| CLïR UV Bulb 254/185nm TOC Destruct | CLX-5000-016 |
| Sanitization Kit (includes cartridges, test strips, and gloves) | CLX-5000-017 |

