

IX SERIES IWT®/USF® REPLACEMENTS

SERIES OVERVIEW

IX Series cartridges provide ultra high purity water with the highest possible capacities. The white end caps and clear filter tube are constructed of durable polycarbonate. Color changing media gives a visual indication of exhaustion.

IX Series filters are compatible with ARIES FilterWorks, EDC[®], IWT[®] and US Filter[®] single and dual brackets. Cartridge equivalents are available for the Research, Universal, Metex and Absorber filters. Premium resins and carbon ensure the highest quality water and the longest possible life.

FEATURES & BENEFITS

- Polycarbonate Construction
- Crystal Clear Tube
- IWT®, US FILTER® and EDC® Compatible
- Highest Purity
- Highest Capacity
- Color Changing Medias



- IWT[®], US FILTER[®] AND EDC[®] COMPATIBLE
- ULTRA HIGH PURITY
- CRYSTAL CLEAR TUBE

TECHNICAL DATA



Connections: Short tapered nipples

Mat'l of Construction Polycarbonate

Diameter: 3.35 "
Body Length: 18.00"
Overall Length: 19.50"

Volume: 127.17 cu. in. (.074 cu ft.)

Flow: to 1 gpm Max Pressure Drop: 5 psi

Weight: 5.0 pounds (Approx.)

IX Series • IWT® / USF® Replacements

ORDERING GUIDE

MP Series Replacement Cartridges				REPLACEMENT EQUIVALENT IWT® US FILTER® EDC®		
IX-02-4030	High Purity Color Changing Mixed Bed	1290 GRAINS	Research II	3C0800002	HP-100	
IX-02-4040	High Capacity, Color Changing Mixed Bed	1500 GRAINS	Universal II	3C0600002	HC-200	
IX-02-1050	Organics & Chlorine Removal	9600 Gallons Chlorine Removal	Absorber II	3C0200002	CF-300	
IX-02-3002	Metals Removal, Condensate Polishing, Color Changing Cation	3490 GRAINS	Metex II	3C0400002	DC-400	
IX-02-4011	High Purity Low TOC Mixed Bed	1290 GRAINS		Not Available	UP-500	
IX-02-4090	Premium Organic & Chlorine Removal	1850 Gallons Organics Removal				

OTES			

Note: Ordering information subject to change without notice. Please verify all specifications prior to ordering. For more information Call: (856) 768-9600.

MANUFACTURED IN THE USA.

IMPORTANT NOTICE TO USER:

The following is made in lieu of all other warranties expressed or implied. Manufacturer's and Seller's only obligation shall be to issue credit against the purchase or replacement of the equipment proved to be defective in material or workmanship. Neither Manufacturer nor Seller shall be liable for any injury, loss or damage, direct or indirect, special or consequential, arising out of the use of, misuse, or the inability to use such product. The information contained here is based on technical data and tests which we believe to be reliable and is intended for use by persons having technical skill at their discretion and risk. Since conditions of use are outside ResinTech's control, we can assume no liability whatsoever for results obtained or damages incurred through the application of the data presented. This information is not intended as a license to operate under, or a recommendation to infringe upon, any patent of ResinTech's or others covering any material or use. The foregoing may not be altered except by written agreement signed by officers of the Manufacturer.