_P-72
capacity ng glass doors, self-closing, right hinged, not reversible ressor Temperature Controller re operating temperature range: 1°-10°C reperature Display and Alarm Module imulated digital temperature display; .1° Resolution re temperature display in Celsius or Fahrenheit and visual high/low temperature alarms 1 in air and 1 in sample bottle ror alarm ror alarm ror alarm re 1-point Min/Max History ror alarm re 2-point Min/Max History ror alarm re 3-point Min/Max History ror alarm re 4-point Min/Max History ror alarm re 5-point Min/Max History ror alarm ror ontacts re 6-point Min/Max History ror alarm ror alarm re 1-point Min/Max History ror alarm ror alarm re 1-point Min/Max History ror alarm re 1-point Min/Max History ror alarm re 1-point Min/Max History ror alarm ror point Min/Max History ror alarm re 1-point Min/Max History ror alarm re 2-point Min/Max History ror alarm re 3-point Min/Max History ror alarm re 3-point Min/Max History ror alarm ror point Min/Max History ror alarm ror alarm re 1-point Min/Max History ror alarm ror alarm re 1-point Min/Max History ror alarm ror point Min/Max History ror alarm ror point Min/Max History ror alarms ror alarm ror ror alarm ror alarm ror alarm ror resolution ror resolution ror alarm ror resolution ror resolution ror alarm ror resolution ror alarm r
. It is the second of the seco