

NEW
MODELS

Julabo
THE TEMPERATURE CONTROL COMPANY

CORIO™



ENGLISH



CORIO™ – the new laboratory circulators

Advantages at a glance.....4



Refrigerated/Heating Circulators 10

Accessories 16



Heating Circulators 22

Immersion Circulators..... 24

Open Heating Bath Circulators 26

Heating Circulators..... 34

Accessories 36

Technical Specifications 46

The CORIO™ advantages at a glance.



Brilliant.

Bright display with strong illumination can be read easily from a long distance.



Touching permitted.

Maximum safety. The ergonomic plastic handle protects your fingers from hot surfaces.



Switch on. And off you go.

Intelligent operating concept. Ready for operation with just a few quick and easy steps.



Unique.

Specially designed pyramids ensure that the condensed liquid drips directly back into the bath.



Click.

One for all. Control the circulator and the refrigeration unit with only one power switch.



More bath.

Designed for more comfort. Thanks to the recessed cooling coil, the internal bath provides more space.



Everything at the front.

All operating controls and safety functions are accessed easily and comfortably from the front.



JULABO
exclusive

Space saving. Free up space.

Place your CORIO™ right next to an application, another unit, or wall. That saves space. This is made possible positioning vents and connections only on the front and rear sides.



Internal. External.

The pump is controlled via a lever located directly below the display. Easily change between internal and external circulation.



Handle with ease.


Makes day-to-day work easy. Comfortably move your CORIO™ around by using the ergonomic handles (front and rear).






Safety.

CORIO™ CD complies with Class III (FL), CORIO™ C complies with Class I (NFL) according to DIN 12876-1. Both models switch off automatically in case of high temperature or low liquid level alarm.



Modern. Reliable.

Every CORIO™ is equipped with high-grade components like i.e. platinum sensors, proven motor technology, CAN-Bus communication and much more.



Solid.

Minimized energy loss through high-quality insulation.



ATC.

Absolute Temperature Calibration, 1-point calibration.




Mobile.

Extra easy handling. Integrated castors for easy repositioning of refrigerated circulators. (CD-600F, 601F, 900F, 1000F).



Exact.

You can rely on it. PID1 control and 'Active Cooling Control' make the new CORIO™ precise and perfect.




Condensation protection.

Superb design solution. Integrated ventilation directs air over the bath lid and minimizes condensation.



Locked in.

The lockable power plug guarantees safe connection. More process safety.



Stable.

Rubber feet allow for a secured footing of your CORIO™ to prevent damage to your laboratory equipment.



Tidy.

The special drain tap for easy draining of bath fluids without tools.



USB.

Remote control made easy. CORIO™ CD circulators feature a USB connection.



Connection. Easy.

Inclined pump connections (M16x1) facilitate the connection of applications. Each unit includes 2 barbed fittings of 8/12 mm diameter each.



NEW. CORIO™.

Powerful. Robust.

CORIO™ is derived from the word 'Core'. Because the core characteristics of these newly developed laboratory circulators are exact temperature, absolute precision, and a wide working temperature range. In addition CORIO™ is equipped with all the core functions required in your laboratory for the temperature control of a wide variety of applications and samples.

Everything you need. Inside and out.

Precise, robust, and easy to operate units have proven their value in research and industry. That is all you really need. CORIO™ fulfills the highest demands for precision, reliability and handling. And that's not all. CORIO™ offers numerous additional advantages which will facilitate your daily work. An added value which will pay off.

Modern. Ambitious.

CORIO™ accentuates JULABO's ambition to create forward-looking technologies for modern laboratories. Outstanding functionality, ergonomics, easy operation, and a modern design. That is the core. That is CORIO™.

Ergonomic. Elegant.

CORIO™ makes day-to-day laboratory tasks easier. With a user-friendly operation. A bright and clear display. Easy start-up. Exceptional core functions - you will be able to master the new CORIO™ in no time at all.

New. Different.

It is the multitude of innovative details which make CORIO™ products unique. Discover the many advantages for yourself.





CORIO™. The best for your laboratory!

Made in Germany!

CORIO™ is produced according to the highest German quality standards. They utilize reliable and robust core equipment. They feature platinum sensors, proven motor technology, and CAN-Bus communication. Product development consistently applied environmentally friendly materials and technologies.

More comfort in your laboratory!

Switch on. And off you go. With the intelligent operating concept you will be able to set the new CORIO™ quickly and safely. All operating controls and safety functions can be accessed easily from the front. Not only do the new CORIO™ look good, they include integrated handles for superior ergonomics. The elegant, rounded design makes cleaning a breeze.

Safety for users and their processes!

CORIO™ is safe. The circulator and the refrigeration unit are operated via one common switch. The outstanding design of the bath lid and insulation prevent direct contact with hot surfaces. Rubber feet allow for a secured footing. A lockable power plug provides a secure connection which cannot be disconnected by accident. And the best: a stable and reliable performance of the CORIO™ at ambient temperatures of up to +40 °C.

Maximum benefit for your laboratory!

The new drain tap permits easy draining of your CORIO™ without tools – a clever and handy solution. The integrated USB interface of all CORIO™ CD models allows remote control. And only JULABO offers temperature control units with closed side panels. This saves laboratory space as you can place your CORIO™ right next to other units and applications.

Refrigerated Circulators



The Refrigerated / Heating Circulators of the new generation CORIO™ provide more robustness, more reliability, and more advantages. They are ideal for all standard tasks and routine work in your laboratory.



Refrigerated Circulators

CORIO™ CD Series

for working temperatures from -40 °C to +150 °C

Refrigerated / Heating Circulators of the new CORIO™ series distinguish themselves with a great price-to-performance ratio. They are ideal for all standard tasks and routine work in laboratories and industry.

- Models for internal and external applications
- Bright, white, easy to read display
- Very quiet
- Easy change-over from internal to external circulation and vice versa
- External pump connections (M16x1)
- USB interface
- Space-saving cooling coil design provides more usable space in the bath tank
- Bath lid and drain tap included
- Removable ventilation grid
- Refrigeration unit without side vents
- Class III (FL) according to DIN 12876-1

To adapt the CORIO™ Refrigerated / Heating Circulator to your individual application, we offer a comprehensive range of accessories (bath fluid, tubing, adapter, and more).

Applications

Temperature control of samples in a circulator bath or temperature control of an external application. For example: measuring cells, refractometers, polarimeters, photometers, viscometers, fermenters, electrophoresis chambers, chromatography columns, rotary evaporators, rheometers, and more.



Maintenance. Friendly.

The magnetic front grid can be removed easily for user-friendly cleaning and maintenance. Without tools.



CORIO™ CD-200F

Order No.	9 012 701	
Model	CD-200F	
Working temperature range °C	-20 ... +150	
Temperature stability °C	± 0.03	
Heating capacity kW	1	
Cooling capacity kW (Bath fluid: Ethanol)	+20 °C	0 °C
	0.22	0.17
	-10 °C	-20 °C
	0.13	0.06
Pump capacity	l/min	psi
Flow rate / Pressure	16	4.6
Bath opening / Bath depth inch	W x L / D 5.1 x 5.9 / 5.9	
Filling volume liters	3 ... 4	
Dimensions inch	W x L x H 9.1 x 15.4 x 25.6	

CORIO™ CD-201F


Order No.	9 012 702	
Model	CD-201F	
Working temperature range °C	-20 ... +150	
Temperature stability °C	± 0.03	
Heating capacity kW	1	
Cooling capacity kW (Bath fluid: Ethanol)	+20 °C	0 °C
	0.22	0.16
	-10 °C	-20 °C
	0.12	0.06
Pump capacity	l/min	psi
Flow rate / Pressure	16	4.6
Bath opening / Bath depth inch	W x L / D 5.1 x 5.9 / 5.9	
Filling volume liters	3 ... 4	
Dimensions inch	W x L x H 17.3 x 16.1 x 17.3	

CORIO™ CD-300F

Order No.	9 012 703	
Model	CD-300F	
Working temperature range °C	-25 ... +150	
Temperature stability °C	± 0.03	
Heating capacity kW	1	
Cooling capacity kW (Bath fluid: Ethanol)	+20 °C	0 °C
	0.31	0.28
	-10 °C	-20 °C
	0.2	0.11
Pump capacity	l/min	psi
Flow rate / Pressure	16	4.6
Bath opening / Bath depth inch	W x L / D 5.1 x 5.9 / 5.9	
Filling volume liters	3 ... 4	
Dimensions inch	W x L x H 9.4 x 16.5 x 26	


Heat-up time*

Bath fluid: Thermal




Cool-down time

Bath fluid: Ethanol



Pump capacity

Bath fluid: Water



*with 2 kW heater

Refrigerated Circulators



CORIO™ CD-600F

Order No. 9 012 704

Model CD-600F

Working temperature range °C -35 ... +150

Temperature stability °C ± 0.03

Heating capacity kW 1

	+20 °C	0 °C	-10 °C
Cooling capacity kW (Bath fluid: Ethanol)	0.6	0.53	0.35
	-20 °C	-30 °C	-40 °C
	0.22	0.1	-

Pump capacity l/min psi

Flow rate / Pressure 16 4.6

Bath opening / Bath depth inch W x L / D 8.7 x 5.9 / 5.9

Filling volume liters 5 ... 7.5

Dimensions inch W x L x H 13x 18.5 x 27.2



CORIO™ CD-601F



Order No. 9 012 705

Model CD-601F

Working temperature range °C -40 ... +150

Temperature stability °C ± 0.03

Heating capacity kW 1

	+20 °C	0 °C	-10 °C
Cooling capacity kW (Bath fluid: Ethanol)	0.6	0.5	0.35
	-20 °C	-30 °C	-40 °C
	0.2	0.07	0.01

Pump capacity l/min psi

Flow rate / Pressure 16 4.6

Bath opening / Bath depth inch W x L / D 8.7 x 5.9 / 7.9

Filling volume liters 8 ... 10

Dimensions inch W x L x H 14.2 x 18.1 x 29.1

The CORIO™ Principle

Powerful. Robust. CORIO™ features all core functions for the temperature control of a wide variety of applications and samples.

Everything you need. Inside and out. All that is needed for daily routine tasks in laboratories and industry.

Ergonomic. Elegant. CORIO™ incorporates forward-looking technologies with highest demands for precision, reliability, economy and operation.

New. Different. Discover the numerous advantages of the CORIO™ generation.



CORIO™ CD-900F

NEW

Order No. 9 012 706

Model CD-900F

Working temperature range °C -40 ... +150

Temperature stability °C ± 0.03

Heating capacity kW 1

	+20 °C	0 °C	-10 °C
Cooling capacity kW	0.9	0.8	0.55
(Bath fluid: Ethanol)			
	-20 °C	-30 °C	-40 °C
	0.35	0.15	0.02

Pump capacity l/min psi

Flow rate / Pressure 16 4.6

Bath opening / Bath depth inch
10.2 x 13.8 / 7.9

Filling volume liters 21 ... 30

Dimensions inch
15.4 x 24.4 x 29.5



CORIO™ CD-1000F

NEW

Order No. 9 012 707

Model CD-1000F

Working temperature range °C -40 ... +150

Temperature stability °C ± 0.03

Heating capacity kW 1

	+20 °C	0 °C	-10 °C
Cooling capacity kW	1	1	0.73
(Bath fluid: Ethanol)			
	-20 °C	-30 °C	-40 °C
	0.5	0.25	0.1

Pump capacity l/min psi

Flow rate / Pressure 16 4.6

Bath opening / Bath depth inch
8.7 x 5.9 / 5.9

Filling volume liters 5 ... 7.5

Dimensions inch
16.5 x 19.3 x 27.6



CORIO™ CD-1001F

NEW

Order No. 9 012 708

Model CD-1001F

Working temperature range °C -38 ... +100

Temperature stability °C ± 0.03

Heating capacity kW 1.6

	+20 °C	0 °C	-10 °C
Cooling capacity kW	1	0.9	0.63
(Bath fluid: Ethanol)			
	-20 °C	-30 °C	-40 °C
	0.35	0.13	-

Pump capacity l/min psi

Flow rate / Pressure 14 4.6

Bath opening / Bath depth inch
13.8 x 16.1 / 11.8

Filling volume liters 42 ... 56

Dimensions inch
17.7 x 25.2 x 37.4



Saves energy.

CORIO™ comes with various modes for the refrigeration unit: permanently on, permanently off, or on as refrigeration is needed. CORIO™ CD-600F to CORIO™ CD-1001 additionally contain a continuous automatic adjustment of the cooling capacity at the operating point to minimize the power consumption and the heat waste.

Refrigerated Circulators Accessories

JULABO Thermal Bath Fluids


JULABO Thermal bath fluids have been carefully chosen after long-term testing. They are highly suitable for all of your temperature control applications guaranteeing safe and reliable operation.

Choosing the proper bath fluid is critical for high performance temperature control. The viscosity, oxidation and heat transfer characteristics of the Thermal fluids are specifically selected for use with JULABO temperature control instruments.

Advantages

- Wide temperature ranges
- Low viscosity
- High stability
- Good heat conductivity
- Minimum odor
- Low corrosion tendency
- Low toxicity
- Long fluid life

Working temperature range



Makes routine laboratory work easier.

JULABO Thermal bath fluids are delivered in containers with a handy drain tap.



Tidy.

The special drain tap for easy draining of bath fluids without tools.



Thermal EG

Order No. 5 liters 8 891 407

Order No. 10 liters 8 891 406

Working temperature range °C -30 ... +80

Flash point °C not applicable

Fire point °C not applicable

Viscosity, (kinematic at +20 °C) mm²/s 4.25

Density (at +20 °C) g/cm³ 1.08

Pour point °C -70

Boiling point °C +108

Ignition temperature °C +410

Color light yellow



Thermal C5

Order No. 5 liters 8 891 403

Order No. 10 liters 8 891 402

Working temperature range °C -60 ... +110

Flash point °C +135

Fire point °C +443

Viscosity, (kinematic at +20 °C) mm²/s 5

Density (at +20 °C) g/cm³ 0.92

Pour point °C -100

Boiling point °C +205

Ignition temperature °C +443

Color clear



Thermal C10

Order No. 5 liters 8 891 405

Order No. 10 liters 8 891 404

Working temperature range °C -20 ... +160

Flash point °C >+163

Fire point °C +325

Viscosity, (kinematic at +20 °C) mm²/s 10

Density (at +20 °C) g/cm³ 0.93

Pour point °C <-60

Boiling point °C +205

Ignition temperature °C +370

Color clear

JULABO Thermal bath fluids based on silicone ...

... are chemically inert substances which do not affect metals like iron, copper, zinc, aluminum, chrome or nickel. Compared to other fluids, JULABO Thermal fluids have an extraordinarily high dielectric strength. When properly stored, the fluids will last for 12 months and longer as they are not susceptible to climatic influences.

JULABO Thermal bath fluids based on water-glycol ...


... (monoethyleneglycol with anti-corrosion additives) have excellent thermal characteristics and a low viscosity. In addition, they provide anti-freeze protection, i.e. they can be applied at temperatures below the freezing point of water.

More information on JULABO Thermal bath fluids ...

... see 'Thermal Bath Fluids' at www.julabo.com/us.



Refrigerated Circulators Accessories



Hollow balls to reduce heat loss, evaporation, oxygen input, odors, action of light

Order No.	Description	Suitable for
8 970 010	Hollow balls, Polypropylene [®] , 20 mm Ø, 1000 pcs. (up to +100 °C, for water only)	CD



Heat exchangers / Cooling installations

Order No.	Description	Suitable for
9 970 240	Bath cover with built-in heat exchanger	CD-200F, CD-201F, CD-300F
9 970 242	Bath cover with built-in heat exchanger	CD-600F, CD-601F, CD-1000F



CR® tubing (-30 ... +120 °C)

Order No.	Description	Suitable for
8 930 008	1 m, 8 mm inner dia.	CD
8 930 010	1 m, 10 mm inner dia.	CD
8 930 012	1 m, 12 mm inner dia.	CD



Viton® tubing (-35 ... +200 °C)

Order No.	Description	Suitable for
8 930 108	1 m, 8 mm inner dia.	CD
8 930 110	1 m, 10 mm inner dia.	CD
8 930 112	1 m, 12 mm inner dia.	CD



Tubing insulation (-50...+100 °C)

Order No.	Description	Suitable for
8 930 410	1 m, for tubing 8 - 10 mm inner dia.	CR® / Viton® Tubing
8 930 412	1 m, for tubing 12 mm inner dia.	CR® / Viton® Tubing



Tube clamps

Order No.	Description	Suitable for
8 970 480	2 Tube clamps, size 1	CR® / Viton® Tubing 8 mm inner dia.
8 970 481	2 Tube clamps, size 2	CR® / Viton® Tubing 10 - 12 mm inner dia.



Metal tubing flexible, insulated, -50 ... +200 °C

Order No.	Description	Suitable for
8 930 220	0.5 m Metal tubing, 2 fittings M16x1 female	CD
8 930 221	1.0 m Metal tubing, 2 fittings M16x1 female	CD
8 930 222	1.5 m Metal tubing, 2 fittings M16x1 female	CD
8 930 223	3.0 m Metal tubing, 2 fittings M16x1 female	CD



Adapters and connectors

Order No.	Description	Suitable for
8 970 446	2 Barbed fittings for tubing 8 mm inner dia.	CD
8 970 447	2 Barbed fittings for tubing 10 mm inner dia.	CD
8 970 445	2 Barbed fittings for tubing 12 mm inner dia.	CD
8 970 443	1 Adapter M16x1 male to M16x1 male	CD
8 970 490	2 Collar nuts M16x1 female	CD
8 970 442	2 Elbow fittings 90°, M16x1 female/male	CD
8 890 004	2 Adapters M16x1 female to NPT 1/4" male	CD
8 890 005	2 Adapters M16x1 female to NPT 1/4" female	CD
8 890 006	2 Adapters M16x1 female to NPT 3/8" male	CD
8 890 007	2 Adapters M16x1 female to NPT 3/8" female	CD
8 890 008	2 Adapters M16x1 female to NPT 1/2" male	CD
8 890 009	2 Adapters M16x1 female to NPT 1/2" female	CD
8 890 010	2 Adapters M16x1 male to NPT 1/4" female	CD
8 891 008	1 Adapter M16x1 male to BSP 1/2" female	CD
8 891 009	1 Adapter M16x1 male to BSP 3/4" female	CD
8 890 011	2 Adapters M16x1 female to tube 1/4" male	CD
8 890 012	2 Adapters M16x1 female to tube 3/8" male	CD
8 890 013	2 Adapters M16x1 female to tube 1/2" male	CD
8 890 024	2 Adapters M16x1 female to M16x1 female	CD



Shut-off valves for loop circuit

Order No.	Description	Suitable for
8 970 457	Shut-off valve (-30 °C ... +200 °C), M16x1	CD
8 970 456	Shut-off valve (-10 °C ... +100 °C), M16x1	CD




Twin distributing adapters with barbed fittings

Order No.	Description	Suitable for
8 970 470	Twin distributing adapter with barbed fittings	Tubing 8 mm inner dia.
8 970 471	Twin distributing adapter with barbed fittings	Tubing 12 mm inner dia.
8 970 472	Twin distributing adapter with barbed fittings	Tubing 10 mm inner dia.
8 970 473	Twin distributing adapter M16x1 female to 2 x M16x1 male	CD




Refrigerated Circulators Accessories



Test tube racks made of stainless steel, up to +150 °C

Order No.	Description	Suitable for
9 970 320	Test tube rack for 30 tubes 100 x 17 mm dia.	CD-200F, CD-201F, CD-300F
9 970 321	Test tube rack for 42 tubes 75 x 12/13 mm dia.	CD-200F, CD-201F, CD-300F
9 970 322	Test tube rack for 42 tubes 40 x 10/11 mm dia.	CD-200F, CD-201F, CD-300F
9 970 323	Test tube rack for 10 Falcon tubes 50 ml	CD-200F, CD-201F, CD-300F



Immersion-height adjustable platforms

Order No.	Description	Suitable for
9 970 506	Immersion-height adjustable platform	CD-900F



Accessories Beer Forcing Test

Order No.	Description	Suitable for
9 970 247	Transparent bath cover, Plexiglas, temperature range -10 °C ... +80 °C	CD-1001F
9 970 337	Basket for 20 bottles 0.33 l / 0.5 l, stainless steel	CD-1001F



EasyTEMP Software for instrument control, data recording and visualization

Order No.	Description	Suitable for
8 901 102	EasyTEMP Software (free of charge at www.julabo.com)	CD
8 901 105	EasyTEMP Professional Software, incl. USB-Dongle	CD
9 900 110	USB interface cable 2 m, type A-B	CD
9 900 112	USB 2.0 Repeater extension cable, length = 5 m	CD
9 900 114	USB 2.0 Repeater extension cable, length = 10 m	CD



Calibration and manufacturer's certificates

Order No.	Description	Suitable for
8 902 901	1-Point manufacturer's calibration certificate	CD
8 902 903	3-Point manufacturer's calibration certificate	CD
8 902 905	5-Point manufacturer's calibration certificate	CD
8 903 025	Manufacturer's Certificate for JULABO units with up to 1 kW cooling capacity (at +20 °C)	Refrigerated Circulators



IQ/OQ Documentation for Equipment Qualification

Order No.	Description	Suitable for
2 310 110	IQ/OQ Documentation, Category 1	CD



Preventative Maintenance Contract

Order No.	Description	Suitable for
2 350 100	Preventative Maintenance Contract Standard includes the following services: Visual inspection, technical diagnostics, data analysis, BlackBox, testing of tube connections and bath fluid, thorough cleaning of condenser and other components, testing of temperature stability and sensor calibration, testing/measuring of pump and cooling capacity (depending on model) and firmware update (if no hardware adjustment is required)	CD
2 350 110	Preventative Maintenance Contract Premium includes all services listed above as well as spare parts and labor required for installation or replacement	CD



CORIO™ **Heating Circulators** feature professional technology for routine laboratory tasks. The portfolio permits a wide range of applications and includes immersion circulators, open heating bath circulators, and heating circulators.



Heating Circulators



Heating Circulators

CORIO™ C Immersion Circulator

for working temperatures from +20 °C to +100 °C

The CORIO™ C is the basic model of the CORIO™ circulator portfolio. The bath attachment clamp is included in delivery and facilitates mounting of the circulator on any bath tank up to 30 liters.

- Precise temperature control
- For internal standard applications
- For bath tanks with a max. filling volume of 30 liters
- Immersion depth: 7.5 ... 16.5 cm
- Bright, white, easy to read display
- Whisper quiet
- Easy operation
- Class I (NFL) according to DIN 12876-1

To adapt the CORIO™ Immersion Circulator to your individual application we offer a comprehensive range of accessories (racks, bath lids, and more).



Option I

The universal bath attachment clamp permits mounting the CORIO™ Immersion Circulator on rectangular as well as round bath tanks.



Option II

Just a few simple steps and the bath attachment clamp is transformed into a mount for laboratory stands.



Option III

The Immersion Circulator can be attached directly to the rim of an open JULABO bath.



Flexibility.

The jet nozzle permits continuous adjustment of the direction of the pump stream in your bath.



CORIO™ C

Order No.	9 011 000	
Model	C	
Working temperature range °C ¹⁾	+20 ... +100	
Temperature stability °C	± 0.03	
Heating capacity kW	1	
Pump capacity	l/min	psi
Flow rate / Pressure	6	0.14
Dimensions inch	W x L x H	
	5.2 x 6.3 x 14.3	

CORIO™ CD Immersion Circulator

for working temperatures from +20 °C to +150 °C

In addition to the advantages of the CORIO™ C Circulator, the CORIO™ CD Immersion Circulator can be equipped with an optional pump set for temperature control of external applications.

- Precise temperature control
- For internal and external applications (accessories required)
- For bath tanks with a max. filling volume of 50 liters
- Immersion depth: 7.5 ... 16.5 cm
- Bright, white, easy to read display
- Very quiet
- Easy handling
- Pump change-over between internal and external circulation
- USB interface
- Class III (FL) according to DIN 12876-1

To adapt the CORIO™ Immersion Circulator to your individual application we offer a comprehensive range of accessories (racks, bath lids, tubing, adapters, and more).



Optional pump set

With a few simple steps you can install a pump set on the CORIO™ CD Immersion Circulator. In no time at all, your circulator is ready for temperature control of an external application.



Universal.


Universal bath attachment clamp. For straight containers. For round containers. For laboratory stands (in combination with stand attachment).



CORIO™ CD

Order No.	9 012 000	
Model	CD	
Working temperature range °C ¹⁾	+20 ... +150	
Temperature stability °C	± 0.03	
Heating capacity kW	1	
Pump capacity	l/min	psi
Flow rate / Pressure	16	4.6
Dimensions inch	W x L x H	
	5.2 x 6.3 x 14.3	

Pump capacity Bath fluid: Water



Applications (CORIO™ C and CD)

Flexible applications, for example when changing bath tanks. For a large variety of applications in chemistry, pharmaceuticals, medicine, e.g. temperature applications for samples, analytics, or material testing, and more.

¹⁾ For applications near or below ambient temperature: use a cooling coil or JULABO immersion cooler.

Heating Circulators

CORIO™ C Open Heating Bath Circulators

for internal temperature applications with transparent bath tanks
for working temperatures from +20 °C to +100 °C

The Open Heating Bath Circulators of the new CORIO™ series feature durable, high-quality transparent bath tanks.

- For internal applications
- Bright, white, easy to read display
- Whisper quiet

To adapt the CORIO™ Open Heating Bath Circulator to your individual application we offer a comprehensive range of accessories (racks, bath lids, and more).



Clever.

A clean solution. The cleverly integrated drip off design. (B and BT baths)



CORIO™ C-BT5

Order No.	9 011 305	
Model	C-BT5	
Working temperature range °C ¹⁾	+20 ... +100	
Temperature stability °C	± 0.03	
Heating capacity kW	1	
Circulation capacity	l/min	psi
Flow rate / Pressure	6	0.14
Bath opening / Bath depth inch	W x L / D 5.9 x 5.9 / 5.9	
Filling volume liters	3.5 ... 5	
Dimensions inch	W x L x H 9.1 x 15 x 15	





CORIO™ C-BT9

Order No.	9 011 309	
Model	C-BT9	
Working temperature range °C ¹⁾	+20 ... +100	
Temperature stability °C	± 0.03	
Heating capacity kW	1	
Circulation capacity	l/min	psi
Flow rate / Pressure	6	0.14
Bath opening /	W x L / D	
Bath depth inch	9.1 x 5.9 / 5.9	
Filling volume liters	6 ... 9	
Dimensions inch	W x L x H 12.6 x 15 x 15	



CORIO™ C-BT19

Order No.	9 011 319	
Model	C-BT19	
Working temperature range °C ¹⁾	+20 ... +100	
Temperature stability °C	± 0.03	
Heating capacity kW	1	
Circulation capacity	l/min	psi
Flow rate / Pressure	6	0.14
Bath opening /	W x L / D	
Bath depth inch	11.8 x 13.8 / 5.9	
Filling volume liters	14 ... 19	
Dimensions inch	W x L x H 15 x 22.8 x 15	



CORIO™ C-BT27


Order No.	9 011 327	
Model	C-BT27	
Working temperature range °C ¹⁾	+20 ... +100	
Temperature stability °C	± 0.03	
Heating capacity kW	1	
Circulation capacity	l/min	psi
Flow rate / Pressure	6	0.14
Bath opening /	W x L / D	
Bath depth inch	11.8 x 13.8 / 7.9	
Filling volume liters	20 ... 27	
Dimensions inch	W x L x H 15 x 22.8 x 16.9	

Applications

Temperature control of samples, preparation of samples for serology and clinical chemistry, analysis, material testing, and more.

Heat-up time*

Bath fluid: Water



*with 2 kW heater

¹⁾ For applications near or below ambient temperature: use a cooling coil or JULABO immersion cooler.

Heating Circulators

CORIO™ C Open Heating Bath Circulators

for internal temperature applications with stainless steel bath tanks
for working temperatures from +20 °C to +100 °C

The Open Heating Bath Circulators of the new CORIO™ series feature high-quality bath tanks made of stainless steel.

- For internal applications
- Bright, white, easy to read display
- Whisper quiet
- High-quality bath tanks made of stainless steel
- Integrated drain screw (except for B5)

To adapt the CORIO™ Open Heating Bath Circulator to your individual application we offer a comprehensive range of accessories (racks, bath lids, and more).

Applications

Temperature control of samples, preparation of samples for serology and clinical chemistry, analysis, material testing, and more.



CORIO™ C-B5

Order No. 9 011 405

Model C-B5

Working temperature range °C¹⁾ +20 ... +100

Temperature stability °C ± 0.03

Heating capacity kW 1

Circulation capacity	l/min	psi
Flow rate / Pressure	6	0.14

Bath opening / Bath depth inch W x L / D 5.9 x 5.9 / 5.9

Filling volume liters 3.5 ... 5

Dimensions inch W x L x H 9.1 x 15 x 16.1





CORIO™ C-B13

Order No.	9 011 413	
Model	C-B13	
Working temperature range °C ¹⁾	+20 ... +100	
Temperature stability °C	± 0.03	
Heating capacity kW	1	
Circulation capacity	l/min	psi
Flow rate / Pressure	6	0.14
Bath opening / Bath depth inch	W x L / D 11.8 x 7.1 / 5.9	
Filling volume liters	9 ... 13	
Dimensions inch	W x L x H 15 x 15.7 x 16.5	



CORIO™ C-B17

Order No.	9 011 417	
Model	C-B17	
Working temperature range °C ¹⁾	+20 ... +100	
Temperature stability °C	± 0.03	
Heating capacity kW	1	
Circulation capacity	l/min	psi
Flow rate / Pressure	6	0.14
Bath opening / Bath depth inch	W x L / D 11.8 x 7.1 / 7.9	
Filling volume liters	13 ... 17	
Dimensions inch	W x L x H 15 x 15.7 x 18.5	



CORIO™ C-B19

Order No.	9 011 419	
Model	C-B19	
Working temperature range °C ¹⁾	+20 ... +100	
Temperature stability °C	± 0.03	
Heating capacity kW	1	
Circulation capacity	l/min	psi
Flow rate / Pressure	6	0.14
Bath opening / Bath depth inch	W x L / D 11.8 x 13.8 / 5.9	
Filling volume liters	14 ... 19	
Dimensions inch	W x L x H 15 x 22.8 x 16.5	




CORIO™ C-B27

Order No.	9 011 427	
Model	C-B27	
Working temperature range °C ¹⁾	+20 ... +100	
Temperature stability °C	± 0.03	
Heating capacity kW	1	
Circulation capacity	l/min	psi
Flow rate / Pressure	6	0.14
Bath opening / Bath depth inch	W x L / D 11.8 x 13.8 / 7.9	
Filling volume liters	17 ... 27	
Dimensions inch	W x L x H 15 x 22.8 x 18.5	

Heat-up time*

Bath fluid: Water



*with 2 kW heater

¹⁾ For applications near or below ambient temperature: use a cooling coil or JULABO immersion cooler.

Heating Circulators

CORIO™ CD Open Heating Bath Circulators

for internal and external temperature applications with transparent bath tanks for working temperatures from +20 °C to +100 °C


The Open Heating Bath Circulator of the new CORIO™ series feature durable, high-quality transparent bath tanks and pump connections.

- For internal and external applications
- Bright, white, easy to read display
- Very quiet
- Pump change-over between internal and external circulation
- USB connection
- Class III (FL) according to DIN 12876-1

To adapt the CORIO™ Open Heating Bath Circulator to your individual application we offer a comprehensive range of accessories (racks, bath lids, tubing, adapters and more).

Heat-up time*


Bath fluid: Water



*with 2 kW heater

Pump capacity

Bath fluid: Water



Applications

Temperature control of samples, preparation of samples for serology and clinical chemistry, analysis, material testing, and more. External temperature control applications in combination with measuring instruments, measuring cells, photometers, refractometers, polarimeters, and more.



CORIO™ CD-BT5

Order No. 9 012 305

Model CD-BT5

Working temperature range °C¹⁾ +20 ... +100

Temperature stability °C ± 0.03

Heating capacity kW 1

Pump capacity	l/min	psi
Flow rate / Pressure	16	4.6

Bath opening /	W x L / D
Bath depth inch	5.9 x 5.9 / 5.9

Filling volume liters 3.5 ... 5

Dimensions inch W x L x H
9.1 x 15 x 15



CORIO™ CD-BT19

Order No. 9 012 319

Model CD-BT19

Working temperature range °C¹⁾ +20 ... +100

Temperature stability °C ± 0.03

Heating capacity kW 1

Pump capacity	l/min	psi
Flow rate / Pressure	16	4.6

Bath opening /	W x L / D
Bath depth inch	11.8 x 13.8 / 5.9

Filling volume liters 14 ... 19

Dimensions inch W x L x H
15 x 22.8 x 15



CORIO™ CD-BT27

Order No. 9 012 327

Model CD-BT27

Working temperature range °C¹⁾ +20 ... +100

Temperature stability °C ± 0.03

Heating capacity kW 1

Pump capacity	l/min	psi
Flow rate / Pressure	16	4.6


Bath opening /	W x L / D
Bath depth inch	11.8 x 13.8 / 7.9

Filling volume liters 20 ... 27

Dimensions inch W x L x H
15 x 22.8 x 16.9



Bath opening:
W x L / D



Dimensions:
W x L x H



¹⁾ For applications near or below ambient temperature: use a cooling coil or JULABO immersion cooler.

Heating Circulators

CORIO™ CD Open Heating Bath Circulators

for internal and external temperature applications with stainless steel bath tanks for working temperatures from +20 °C to +150 °C

The Open Heating Bath Circulators of the new CORIO™ series feature high-quality bath tanks made of stainless steel and with pump connections.

- For internal and external applications
- Bright, white, easy to read display
- Very quiet
- Pump change-over between internal and external circulation
- USB connection
- High-quality bath tanks made of stainless steel
- Integrated drain screw (except for B5)

To adapt the CORIO™ Open Heating Bath Circulator to your individual application we offer a comprehensive range of accessories (racks, bath lids, tubing, adapters, and more).

Applications

Temperature control of samples, preparation of samples for serology and clinical chemistry, analysis, material testing, and more. External temperature control applications in combination with measuring instruments, measuring cells, photometers, refractometers, polarimeters, and more.



CORIO™ CD-B5

Order No. 9 012 405

Model CD-B5

Working temperature range °C¹⁾ +20 ... +150

Temperature stability °C ± 0.03

Heating capacity kW 1


Pump capacity	l/min	psi
Flow rate / Pressure	16	4.6

Bath opening /	W x L / D
Bath depth inch	5.9 x 5.9 / 5.9


Filling volume liters 3.5 ... 5

Dimensions inch	W x L x H
	9.1 x 15 x 16.1

Pump capacity
Bath fluid: Water



Heat-up time*
Bath fluid: Water



*with 2 kW heater



CORIO™ CD-B13

Order No.	9 012 413	
Model	CD-B13	
Working temperature range °C ¹⁾	+20 ... +150	
Temperature stability °C	± 0.03	
Heating capacity kW	1	
Pump capacity	l/min	psi
Flow rate / Pressure	16	4.6
Bath opening / Bath depth inch	W x L / D 11.8 x 5.9 / 7.1	
Filling volume liters	9 ... 13	
Dimensions inch	W x L x H 15 x 15.7 x 16.5	



CORIO™ CD-B17

Order No.	9 012 417	
Model	CD-B17	
Working temperature range °C ¹⁾	+20 ... +150	
Temperature stability °C	± 0.03	
Heating capacity kW	1	
Pump capacity	l/min	psi
Flow rate / Pressure	16	4.6
Bath opening / Bath depth inch	W x L / D 11.8 x 7.1 / 5.9	
Filling volume liters	13 ... 17	
Dimensions inch	W x L x H 15 x 15.7 x 18.5	



CORIO™ CD-B19

Order No.	9 012 419	
Model	CD-B19	
Working temperature range °C ¹⁾	+20 ... +150	
Temperature stability °C	± 0.03	
Heating capacity kW	1	
Pump capacity	l/min	psi
Flow rate / Pressure	16	4.6
Bath opening / Bath depth inch	W x L / D 11.8 x 13.8 / 7.9	
Filling volume liters	14 ... 19	
Dimensions inch	W x L x H 15 x 22.8 x 16.5	



CORIO™ CD-B27

Order No.	9 012 427	
Model	CD-B27	
Working temperature range °C ¹⁾	+20 ... +150	
Temperature stability °C	± 0.03	
Heating capacity kW	1	
Pump capacity	l/min	psi
Flow rate / Pressure	16	4.6
Bath opening / Bath depth inch	W x L / D 5.9 x 5.9 / 5.9	
Filling volume liters	17 ... 27	
Dimensions inch	W x L x H 15 x 22.8 x 18.5	



CORIO™ CD-B33

Order No.	9 012 433	
Model	CD-B33	
Working temperature range °C ¹⁾	+20 ... +150	
Temperature stability °C	± 0.03	
Heating capacity kW	1	
Pump capacity	l/min	psi
Flow rate / Pressure	16	4.6
Bath opening / Bath depth inch	W x L / D 26 x 5.9 / 12.6	
Filling volume liters	26 ... 39	
Dimensions inch	W x L x H 35.8 x 14.2 x 16.9	



CORIO™ CD-B39

Order No.	9 012 439	
Model	CD-B39	
Working temperature range °C ¹⁾	+20 ... +150	
Temperature stability °C	± 0.03	
Heating capacity kW	1	
Pump capacity	l/min	psi
Flow rate / Pressure	16	4.6
Bath opening / Bath depth inch	W x L / D 13 x 11.8 / 11.8	
Filling volume liters	35 ... 41	
Dimensions inch	W x L x H 21.3 x 13.4 x 22.4	

¹⁾ For applications near or below ambient temperature: use a cooling coil or JULABO immersion cooler.

Heating Circulators

CORIO™ CD Heating Circulators

for internal and external temperature applications with stainless steel baths
for working temperatures from +20 °C to +150 °C

CORIO™ Heating Circulators feature professional technology for demanding applications. These units facilitate internal temperature control in the bath tank or control of externally connected applications.

- For internal and external applications
- Bright, white, easy to read display
- Very quiet
- Pump change-over between internal and external circulation
- USB connection
- High-quality bath tanks made of stainless steel with bath lid and drain tap
- Integrated pump connection M16x1
- Integrated cooling coil for counter-cooling

To adapt the CORIO™ Heating Circulator to your individual application we offer a comprehensive range of accessories (racks, bath lids, tubing, adapters, and more).

Applications

External temperature applications in combination with jacketed reactors, distillation apparatus, mini-plant applications, photometers, refractometers and more, internal temperature applications of samples and small objects.



CORIO™ CD-BC4

Order No. 9 012 504

Model CD-BC4

Working temperature range °C¹⁾ +20 ... +150

Temperature stability °C ± 0.03

Heating capacity kW 1

Pump capacity	l/min	psi
Flow rate / Pressure	16	4.6

Bath opening /	W x L / D
Bath depth inch	5,1 x 5,9 / 5,9

Filling volume liters 3 ... 4.5

Dimensions inch	W x L x H
	9.1 x 16.1 x 16.5



Optional
Bath cover with
built-in heat
exchanger.



CORIO™ CD-BC6

Order No.	9 012 506	
Model	CD-BC6	
Working temperature range °C ¹⁾	+20 ... +150	
Temperature stability °C	± 0.03	
Heating capacity kW	1	
Pump capacity	l/min	psi
Flow rate / Pressure	16	4.6
Bath opening / Bath depth inch	W x L / D 5,1 x 5,9 / 7,9	
Filling volume liters	4.5 ... 6	
Dimensions inch	W x L x H 9.4 x 17.3 x 18.5	



CORIO™ CD-BC12

Order No.	9 012 512	
Model	CD-BC12	
Working temperature range °C ¹⁾	+20 ... +150	
Temperature stability °C	± 0.03	
Heating capacity kW	1	
Pump capacity	l/min	psi
Flow rate / Pressure	16	4.6
Bath opening / Bath depth inch	W x L / D 8.7 x 5.9 / 7.9	
Filling volume liters	8.5 ... 12	
Dimensions inch	W x L x H 13 x 19.3 x 18.5	




CORIO™ CD-BC26

Order No.	9 012 526	
Model	CD-BC26	
Working temperature range °C ¹⁾	+20 ... +150	
Temperature stability °C	± 0.03	
Heating capacity kW	1	
Pump capacity	l/min	psi
Flow rate / Pressure	16	4.6
Bath opening / Bath depth inch	W x L / D 10.2 x 13.8 / 7.9	
Filling volume liters	19 ... 26	
Dimensions inch	W x L x H 15.4 x 24.4 x 18.9	

Heat-up time*


Bath fluid: Thermal



*with 2 kW heater

Pump capacity

Bath fluid: Water



¹⁾ For applications near or below ambient temperature: use a cooling coil or JULABO immersion cooler.

JULABO Thermal Bath Fluids

JULABO Thermal bath fluids have been carefully chosen after long-term testing. They are highly suitable for all of your temperature control applications guaranteeing safe and reliable operation.

Choosing the proper bath fluid is critical for high performance temperature control. The viscosity, oxidation and heat transfer characteristics of the Thermal fluids are specifically selected for use with JULABO CORIO™ CD temperature control instruments.

Advantages


- Wide temperature ranges
- Low viscosity
- High stability
- Good heat conductivity
- Minimum odor
- Low corrosion tendency
- Low toxicity
- Long fluid life



Makes routine laboratory work easier.

JULABO Thermal bath fluids are delivered in containers with a handy drain tap.

Working temperature ranges





Thermal EG

Order No. 5 liters 8 891 407

Order No. 10 liters 8 891 406

Working temperature range °C -30 ... +80

Flash point °C not applicable

Fire point °C not applicable

Viscosity, (kinematic at +20 °C) mm²/s 4.25

Density (at +20 °C) g/cm³ 1.08

Pour point °C -70

Boiling point °C +108

Ignition temperature °C +410

Color light yellow



Thermal C10

Order No. 5 liters 8 891 405

Order No. 10 liters 8 891 404

Working temperature range °C -20 ... +160

Flash point °C >+163

Fire point °C +325

Viscosity, (kinematic at +20 °C) mm²/s 10

Density (at +20 °C) g/cm³ 0.93

Pour point °C <-60

Boiling point °C +205

Ignition temperature °C +370

Color clear



Thermal C20S

Order No. 5 liters 8 891 409

Order No. 10 liters 8 891 408

Working temperature range °C 0 ... +220

Flash point °C +232

Fire point °C +476

Viscosity, (kinematic at +20 °C) mm²/s 20

Density (at +20 °C) g/cm³ 0.97

Pour point °C -60

Boiling point °C +250

Ignition temperature °C +476

Color light brown

JULABO Thermal bath fluids based on silicone ...

... are chemically inert substances which do not affect metals like iron, copper, zinc, aluminum, chrome or nickel. Compared to other fluids, JULABO Thermal fluids have an extraordinarily high dielectric strength. When properly stored, the fluids will last for 12 months and longer as they are not susceptible to climatic influences.

JULABO Thermal bath fluids based on water-glycol ...

... (monoethyleneglycol with anti-corrosion additives) have excellent thermal characteristics and a low viscosity. In addition they provide anti-freeze protection, i.e. they can be applied at temperatures below the freezing point of water.

More information on JULABO Thermal bath fluids ...

... see 'Thermal Bath Fluids' at www.julabo.com/us.







Transparent bath tanks up to +100 °C

Order No.	Description	Inner dimensions inch	Outer dimensions inch	Suitable for
9 901 305	Bath tank BT5	5.9 x 11.8 / 5.9	9.1 x 15 / 6.3	C, CD
9 901 309	Bath tank BT9	9.4 x 11.8 / 5.9	12.6 x 15 / 6.3	C, CD
9 901 319	Bath tank BT19	11.8 x 19.6 / 5.9	15 x 22.8 / 6.3	C, CD
9 901 327	Bath tank BT27	11.8 x 19.6 / 7.9	15 x 22.8 / 8.3	C, CD




Stainless steel bath tanks up to +150 °C, insulated

Order No.	Description	Inner dimensions inch	Outer dimensions inch	Suitable for
9 903 405	Bath tank B5	5.9 x 11.8 / 5.9	9.1 x 15 / 7.9	C, CD
9 903 413	Bath tank B13	11.8 x 12.6 / 5.9	15 x 15.7 / 7.9	C, CD
9 903 417	Bath tank B17	11.8 x 19.6 / 5.9	15 x 15.7 / 9.9	C, CD
9 903 419	Bath tank B19	11.8 x 19.6 / 5.9	15 x 15.7 / 7.9	C, CD
9 903 427	Bath tank B27	11.8 x 19.6 / 7.9	15 x 22.8 / 9.9	C, CD
9 903 433	Bath tank B33	32.6 x 11.8 / 5.9	35.8 x 14.2 / 7.9	C, CD
9 903 439	Bath tank B39	11.8 x 19.6 / 11.8	13.4 x 21.3 / 13.8	C, CD



Bath covers

Order No.	Description	Suitable for
9 970 296	Flat bath cover	B5, BT5
9 970 290	Flat bath cover	B13, B17
9 970 291	Flat bath cover	B19, B27, BT19, BT27
9 970 292	Flat bath cover	B33
9 970 293	Flat bath cover	B39
9 970 253	Lift-up gable bath cover made of stainless steel	B13, B17
9 970 254	Lift-up gable bath cover made of stainless steel	B19, B27, BT19, BT27
9 970 257	Lift-up gable bath cover made of stainless steel	B33




Assembly frames

Order No.	Description	Suitable for
9 970 229	Stainless steel bridge including assembly frame	C-BT5, C-B5
9 970 228	Stainless steel bridge including assembly frame	C-BT19/27, C-B13/17/19/27



Hollow balls to reduce heat loss, evaporation, oxygen input, odors, action of light

Order No.	Description	Suitable for
8 970 010	Hollow balls, Polypropylene [®] , 20 mm Ø, 1000 pcs. (up to +100 °C, for water only)	C, CD



Test tube racks made of stainless steel, up to +150 °C

Order No.	Description	Suitable for
9 970 320	Test tube rack for 30 tubes 100 x 17 mm dia.	B5, BT5
9 970 321	Test tube rack for 42 tubes 75 x 12/13 mm dia.	B5, BT5
9 970 322	Test tube rack for 42 tubes 40 x 10/11 mm dia.	B5, BT5
9 970 323	Test tube rack for 10 Falcon tubes 50 ml	B5, BT5




Test tube racks made of high grade plastic, up to +100 °C

Order No.	Description	Suitable for
9 970 300	Test tube rack for 60 tubes 100 x 16/17 mm dia.	B13, B17, B19, B27, B33, BT19, BT27
9 970 301	Test tube rack for 90 tubes 75 x 12/13 mm dia.	B13, B17, B19, B27, B33, BT19, BT27
9 970 303	Test tube rack for 21 tubes 30 mm dia.	B13, B17, B19, B27, B33, BT19, BT27




Which types of test tube racks are available for your bath and how many can be inserted?

Order No.	BT5	BT9	BT19	BT27	B5	B13	B17	B19	B27	B33	B39
9 970 320	1	-	-	-	1	-	-	-	-	-	-
9 970 321	1	-	-	-	1	-	-	-	-	-	-
9 970 322	1	-	-	-	1	-	-	-	-	-	-
9 970 323	1	-	-	-	1	-	-	-	-	-	-
9 970 300	-	-	3	3	-	1	1	3	3	6	-
9 970 301	-	-	3	3	-	1	1	3	3	6	-
9 970 303	-	-	3	3	-	1	1	3	3	6	-



Immersion-height adjustable platforms

Order No.	Description	Suitable for
9 970 506	Immersion-height adjustable platform	CD-BC26
9 970 503	Immersion-height adjustable platform	B13, B17
9 970 502	Immersion-height adjustable platform	B19, B27




Universal bath attachment clamp

Order No.	Description	Suitable for
9 970 420	Bath attachment clamp for wall thickness up to 30 mm	C, CD



Pump set for external temperature applications

Order No.	Description	Suitable for
9 970 140	Pump set (Pump connectors M16x1)	CD



Stand attachment for laboratory stands

Order No.	Description	Suitable for
9 970 022	Stand attachment with rod 200x12 mm dia.	C, CD



Heat exchangers / Cooling installations

Order No.	Description	Suitable for
9 970 240	Bath cover with built-in heat exchanger	BC4, BC6
9 970 242	Bath cover with built-in heat exchanger	BC12
9 970 100	Assembly cooling coil for counter-cooling with tap water for installation into the existing assembly frame	CD-BT5/19/27, CD-B5/13/17/19/27/33/39
9 970 101	Installation cooling coil for counter-cooling with tap water for mounting on circulator head and for use with the universal bath attachment clamp (without assembly frame)	C, C-BT5/9/19/27, C-B5/13/17/19/27, CD



CR® tubing (-30 ... +120 °C)

Order No.	Description	Suitable for
8 930 008	1 m, 8 mm inner dia.	CD
8 930 010	1 m, 10 mm inner dia.	CD
8 930 012	1 m, 12 mm inner dia.	CD



Viton® tubing (-35 ... +200 °C)

Order No.	Description	Suitable for
8 930 108	1 m, 8 mm inner dia.	CD
8 930 110	1 m, 10 mm inner dia.	CD
8 930 112	1 m, 12 mm inner dia.	CD



Tubing insulation (-50...+100 °C)

Order No.	Description	Suitable for
8 930 410	1 m, for tubing 8 - 10 mm inner dia.	CR® / Viton® Tubing
8 930 412	1 m, for tubing 12 mm inner dia.	CR® / Viton® Tubing



Tube clamps

Order No.	Description	Suitable for
8 970 480	2 Tube clamps, size 1	CR® / Viton® Tubing 8 mm inner dia.
8 970 481	2 Tube clamps, size 2	CR® / Viton® Tubing 10 - 12 mm inner dia.



Metal tubing flexible, insulated, -50 ... +200 °C

Order No.	Description	Suitable for
8 930 220	0.5 m Metal tubing, 2 fittings M16x1 female	CD
8 930 221	1.0 m Metal tubing, 2 fittings M16x1 female	CD
8 930 222	1.5 m Metal tubing, 2 fittings M16x1 female	CD
8 930 223	3.0 m Metal tubing, 2 fittings M16x1 female	CD



Adapters and connectors

Order No.	Description	Suitable for
8 970 446	2 Barbed fittings for tubing 8 mm inner dia.	CD
8 970 447	2 Barbed fittings for tubing 10 mm inner dia.	CD
8 970 445	2 Barbed fittings for tubing 12 mm inner dia.	CD
8 970 443	1 Adapter M16x1 male to M16x1 male	CD
8 970 490	2 Collar nuts M16x1 female	CD
8 970 442	2 Elbow fittings 90°, M16x1 female/male	CD
8 890 004	2 Adapters M16x1 female to NPT 1/4" male	CD
8 890 005	2 Adapters M16x1 female to NPT 1/4" female	CD
8 890 006	2 Adapters M16x1 female to NPT 3/8" male	CD
8 890 007	2 Adapters M16x1 female to NPT 3/8" female	CD
8 890 008	2 Adapters M16x1 female to NPT 1/2" male	CD
8 890 009	2 Adapters M16x1 female to NPT 1/2" female	CD
8 890 010	2 Adapters M16x1 male to NPT 1/4" female	CD
8 891 008	1 Adapter M16x1 male to BSP 1/2" female	CD
8 891 009	1 Adapter M16x1 male to BSP 3/4" female	CD
8 890 011	2 Adapters M16x1 female to tube 1/4" male	CD
8 890 012	2 Adapters M16x1 female to tube 3/8" male	CD
8 890 013	2 Adapters M16x1 female to tube 1/2" male	CD
8 890 024	2 Adapters M16x1 female to M16x1 female	CD



Shut-off valves for loop circuit

Order No.	Description	Suitable for
8 970 457	Shut-off valve (-30 °C ... +200 °C), M16x1	CD
8 970 456	Shut-off valve (-10 °C ... +100 °C), M16x1	CD



Twin distributing adapters with barbed fittings

Order No.	Description	Suitable for
8 970 470	Twin distributing adapter with barbed fittings	Tubing 8 mm inner dia.
8 970 471	Twin distributing adapter with barbed fittings	Tubing 12 mm inner dia.
8 970 472	Twin distributing adapter with barbed fittings	Tubing 10 mm inner dia.
8 970 473	Twin distributing adapter M16x1 female to 2 x M16x1 male	CD



EasyTEMP Software for instrument control, data recording and visualization

Order No.	Description	Suitable for
8 901 102	EasyTEMP Software (free of charge at www.julabo.com)	CD
8 901 105	EasyTEMP Professional Software, incl. USB-Dongle	CD
9 900 110	USB interface cable 2 m, type A-B	CD
9 900 112	USB 2.0 Repeater extension cable, length = 5 m	CD
9 900 114	USB 2.0 Repeater extension cable, length = 10 m	CD



Calibration and manufacturer's certificates

Order No.	Description	Suitable for
8 902 901	1-Point manufacturer's calibration certificate	C, CD
8 902 903	3-Point manufacturer's calibration certificate	C, CD
8 902 905	5-Point manufacturer's calibration certificate	C, CD
8 903 015	Manufacturer's Testing Certificate for JULABO units w/o cooling units	C, CD



IQ/OQ Documentation for Equipment Qualification

Order No.	Description	Suitable for
2 310 110	IQ/OQ Documentation, Category 1	C, CD



Preventative Maintenance Contract

Order No.	Description	Suitable for
2 350 100	Preventative Maintenance Contract Standard includes the following services: Visual inspection, technical diagnostics, data analysis, BlackBox, testing of tube connections and bath fluid, thorough cleaning of condenser and other components, testing of temperature stability and sensor calibration, testing/measuring of pump and cooling capacity (depending on model) and firmware update (if no hardware adjustment is required)	C, CD
2 350 110	Preventative Maintenance Contract Premium includes all services listed above as well as spare parts and labor required for installation or replacement	CD

The **JULABO** advantages at a glance.


JULABO temperature control – high-precision and speed

JULABO products include high-quality temperature control solutions to cover the temperature range from -95 °C to +400 °C.




Refrigerated Circulators

The JULABO refrigerated circulators are suitable for internal and external applications and can be used within the temperature range of -95 °C to +200 °C.



Water Baths and Shaking Water Baths

Water baths and shaking water baths from JULABO can be used for a variety of applications in the temperature range from +20 °C to +99.9 °C



Heating Circulators

Heating circulators are available in various designs including Heating Immersion Circulators, Open Heating Bath Circulators, or Heating Circulators and cover the temperature range from +20 °C to +300 °C.




Additional products

In addition, the JULABO product portfolio has equipment for special applications such as Calibration Baths, Visco Baths, Forcing Test Refrigerated-Heating Circulating Bath, Immersion Coolers, Laboratory Temperature Controllers and Refrigerators for Chemicals.



Highly Dynamic Temperature Control Systems

The highly dynamic temperature control systems from JULABO can be used for demanding temperature applications ranging from -92 °C to +400 °C. The new PRESTO® line offers unique high performance specifications to meet these requirements.




Wireless Communication & Software Solutions

JULABO facilitates the automation of applications. The temperature control units can be comfortably controlled and monitored via PC.



Recirculating Coolers

JULABO recirculating coolers are highly efficient and therefore offer an environmentally friendly and economic alternative to tap water cooling in the range of -25 °C to +130 °C.



Accessories

The extensive range of accessories for all our devices allows the flexible use of JULABO products in research and industry.

Comprehensive service and on-site support

JULABO takes pride in offering customers expert advice for pairing the proper JULABO temperature control solution to their specific application. JULABO service and support options include installation and calibration, equipment qualification documentation and application training. These invaluable services ensure customer confidence in the operation and maintenance of their JULABO unit.

Individual requirements – individual products

The wide range of JULABO offers a solution for almost any application. However, if a specific application needs more than a standard product is able to offer, the JULABO specialists will work out an individual solution with you.



JULABO. Quality.

Highest standards of quality for a long product life.



Green technology.

Deliberately engineered with environmentally friendly materials and technologies.



Satisfied customers.

11 subsidiaries and more than 100 partners worldwide guarantee fast and qualified JULABO support.



100 % Checked.

100 % testing. 100 % quality. Every JULABO product is shipped to customers after successful final inspection.



Quick start.

Individual JULABO consultation and comprehensive manuals at your disposal.



Services 24/7.

Around the clock availability. You can find suitable accessories, data sheets, manuals, case studies, and more at www.julabo.com.

Technical Specifications

CORIO®

Model	Order No.	Working temperature range	Display / display resolution	Temperature control	Temperature stability	Heating capacity	Cooling unit	
		°C			°C			+20
CD-200F	9 012 701	-20 ... +150	LED / 0.1	PID1	± 0.03	1	Air	0.22
CD-201F	9 012 702	-20 ... +150	LED / 0.1	PID1	± 0.03	1	Air	0.22
CD-300F	9 012 703	-25 ... +150	LED / 0.1	PID1	± 0.03	1	Air	0.31
CD-600F	9 012 704	-35 ... +150	LED / 0.1	PID1	± 0.03	1	Air	0.6
CD-601F	9 012 705	-40 ... +150	LED / 0.1	PID1	± 0.03	1	Air	0.6
CD-900F	9 012 706	-40 ... +150	LED / 0.1	PID1	± 0.03	1	Air	0.9
CD-1000F	9 012 707	-40 ... +150	LED / 0.1	PID1	± 0.03	1	Air	1
CD-1001F	9 012 708	-38 ... +100	LED / 0.1	PID1	± 0.03	1	Air	1
C	9 011 000	+20 ... +100	LED / 0.1	PID1	± 0.03	1	-	-
CD	9 012 000	+20 ... +150	LED / 0.1	PID1	± 0.03	1	-	-
C-BT5	9 011 305	+20 ... +100	LED / 0.1	PID1	± 0.03	1	-	-
C-BT9	9 011 309	+20 ... +100	LED / 0.1	PID1	± 0.03	1	-	-
C-BT19	9 011 319	+20 ... +100	LED / 0.1	PID1	± 0.03	1	-	-
C-BT27	9 011 327	+20 ... +100	LED / 0.1	PID1	± 0.03	1	-	-
C-B5	9 011 405	+20 ... +100	LED / 0.1	PID1	± 0.03	1	-	-
C-B13	9 011 413	+20 ... +100	LED / 0.1	PID1	± 0.03	1	-	-
C-B17	9 011 417	+20 ... +100	LED / 0.1	PID1	± 0.03	1	-	-
C-B19	9 011 419	+20 ... +100	LED / 0.1	PID1	± 0.03	1	-	-
C-B27	9 011 427	+20 ... +100	LED / 0.1	PID1	± 0.03	1	-	-
CD-BT5	9 012 305	+20 ... +100	LED / 0.1	PID1	± 0.03	1	-	-
CD-BT19	9 012 319	+20 ... +100	LED / 0.1	PID1	± 0.03	1	-	-
CD-BT27	9 012 327	+20 ... +100	LED / 0.1	PID1	± 0.03	1	-	-
CD-B5	9 012 405	+20 ... +150	LED / 0.1	PID1	± 0.03	1	-	-
CD-B13	9 012 413	+20 ... +150	LED / 0.1	PID1	± 0.03	1	-	-
CD-B17	9 012 417	+20 ... +150	LED / 0.1	PID1	± 0.03	1	-	-
CD-B19	9 012 419	+20 ... +150	LED / 0.1	PID1	± 0.03	1	-	-
CD-B27	9 012 427	+20 ... +150	LED / 0.1	PID1	± 0.03	1	-	-
CD-B33	9 012 433	+20 ... +150	LED / 0.1	PID1	± 0.03	1	-	-
CD-B39	9 012 439	+20 ... +150	LED / 0.1	PID1	± 0.03	1	-	-
CD-BC4	9 012 504	+20 ... +150	LED / 0.1	PID1	± 0.03	1	-	-
CD-BC6	9 012 506	+20 ... +150	LED / 0.1	PID1	± 0.03	1	-	-
CD-BC12	9 012 512	+20 ... +150	LED / 0.1	PID1	± 0.03	1	-	-
CD-BC26	9 012 526	+20 ... +150	LED / 0.1	PID1	± 0.03	1	-	-

Unless otherwise indicated, all data relates to the operation at nominal voltage and frequency and +20 °C ambient temperature. Cooling capacity measured according to DIN 12876-2.

Cooling capacity (kW) at bath temperature in °C (Medium: Ethanol)					Type ☉ Pressure pump ☺ Circulation pump	Pump		Pump connections male	Refrigerant	Filling volume liters
0	-10	-20	-30	-40		Pressure psi	Flow rate l/min			
0.17	0.13	0.06	-	-	☉	4.6	15	M16*1	R134a	3 ... 4
0.16	0.12	0.06	-	-	☉	4.6	15	M16*1	R134a	3 ... 4
0.28	0.2	0.11	-	-	☉	4.6	15	M16*1	R134a	3 ... 4
0.53	0.35	0.22	0.1	-	☉	4.6	15	M16*1	R404a	5 ... 7.5
0.5	0.35	0.2	0.07	0.01	☉	4.6	15	M16*1	R452a	8 ... 10
0.8	0.55	0.35	0.15	0.02	☉	4.6	15	M16*1	R452a	21 ... 30
0.9	0.73	0.5	0.25	0.1	☉	4.6	15	M16*1	R452a	5 ... 7.5
0.9	0.63	0.35	0.13	-	☉	4.6	15	M16*1	R452a	42 ... 56
-	-	-	-	-	☺	0.14	6	-	-	-
-	-	-	-	-	☉	4.6	15	-	-	-
-	-	-	-	-	☺	0.14	6	-	-	3.5 ... 5
-	-	-	-	-	☺	0.14	6	-	-	6 ... 9
-	-	-	-	-	☺	0.14	6	-	-	14 ... 19
-	-	-	-	-	☺	0.14	6	-	-	20 ... 27
-	-	-	-	-	☺	0.14	6	-	-	3.5 ... 5
-	-	-	-	-	☺	0.14	6	-	-	9 ... 13
-	-	-	-	-	☺	0.14	6	-	-	13 ... 17
-	-	-	-	-	☺	0.14	6	-	-	14 ... 19
-	-	-	-	-	☺	0.14	6	-	-	17 ... 27
-	-	-	-	-	☉	4.6	15	M16*1	-	3.5 ... 5
-	-	-	-	-	☉	4.6	15	M16*1	-	14 ... 19
-	-	-	-	-	☉	4.6	15	M16*1	-	20 ... 27
-	-	-	-	-	☉	4.6	15	M16*1	-	3.5 ... 5
-	-	-	-	-	☉	4.6	15	M16*1	-	9 ... 13
-	-	-	-	-	☉	4.6	15	M16*1	-	13 ... 17
-	-	-	-	-	☉	4.6	15	M16*1	-	14 ... 19
-	-	-	-	-	☉	4.6	15	M16*1	-	17 ... 27
-	-	-	-	-	☉	4.6	15	M16*1	-	26 ... 39
-	-	-	-	-	☉	4.6	15	M16*1	-	35 ... 41
-	-	-	-	-	☉	4.6	15	M16*1	-	3 ... 4.5
-	-	-	-	-	☉	4.6	15	M16*1	-	4.5 ... 6
-	-	-	-	-	☉	4.6	15	M16*1	-	8.5 ... 12
-	-	-	-	-	☉	4.6	15	M16*1	-	19 ... 26

Classification acc. to	Power requirement	USB interface	Permissible ambient temperature	Dimensions W x L x H	Weight net	Model
DIN 12876-1	V / Hz / A		°C	inch	lbs	
III (FL)	115/60/12	yes	5 ... 40	9.1 x 15.4 x 25.6	57.3	CD-200F
III (FL)	115/60/12	yes	5 ... 40	17.3 x 16.1 x 17.3	55.1	CD-201F
III (FL)	115/60/12	yes	5 ... 40	9.4 x 16.5 x 26	61.7	CD-300F
III (FL)	115/60/12	yes	5 ... 40	13 x 18.5 x 27.2	79.4	CD-600F
III (FL)	115/60/12	yes	5 ... 40	14.2 x 18.1 x 29.1	84.9	CD-601F
III (FL)	115/60/16	yes	5 ... 40	15.4 x 24.4 x 29.5	114.6	CD-900F
III (FL)	115/60/16	yes	5 ... 40	16.5 x 19.3 x 27.6	113.5	CD-1000F
III (FL)	208/60/14	yes	5 ... 40	17.7 x 25.2 x 37.4	163.1	CD-1001F
I (NFL)	115/60/9	-	5 ... 40	5.2 x 6.3 x 14.3	4.2	C
III (FL)	115/60/10	yes	5 ... 40	5.2 x 6.3 x 14.3	5.7	CD
I (NFL)	115/60/9	-	5 ... 40	9.1 x 15 x 15	10.6	C-BT5
I (NFL)	115/60/9	-	5 ... 40	12.6 x 15 x 15	8.6	C-BT9
I (NFL)	115/60/9	-	5 ... 40	15 x 22.8 x 15	15.4	C-BT19
I (NFL)	115/60/9	-	5 ... 40	15 x 22.8 x 16.9	15.9	C-BT27
I (NFL)	115/60/9	-	5 ... 40	9.1 x 15 x 16.1	16.1	C-B5
I (NFL)	115/60/9	-	5 ... 40	15 x 15.7 x 16.5	18.1	C-B13
I (NFL)	115/60/9	-	5 ... 40	15 x 15.7 x 18.5	20.5	C-B17
I (NFL)	115/60/9	-	5 ... 40	15 x 22.8 x 16.5	23.1	C-B19
I (NFL)	115/60/9	-	5 ... 40	15 x 22.8 x 18.5	28.7	C-B27
III (FL)	115/60/10	yes	5 ... 40	9.1 x 15 x 15	18.1	CD-BT5
III (FL)	115/60/10	yes	5 ... 40	15 x 22.8 x 15	17.6	CD-BT19
III (FL)	115/60/10	yes	5 ... 40	15 x 22.8 x 16.9	17.9	CD-BT27
III (FL)	115/60/10	yes	5 ... 40	9.1 x 15 x 16.1	18.1	CD-B5
III (FL)	115/60/10	yes	5 ... 40	15 x 15.7 x 16.5	20.1	CD-B13
III (FL)	115/60/10	yes	5 ... 40	15 x 15.7 x 18.5	20.5	CD-B17
III (FL)	115/60/10	yes	5 ... 40	15 x 22.8 x 16.5	25.4	CD-B19
III (FL)	115/60/10	yes	5 ... 40	15 x 22.8 x 18.5	28.7	CD-B27
III (FL)	115/60/10	yes	5 ... 40	35.8 x 14.2 x 16.9	46.3	CD-B33
III (FL)	115/60/10	yes	5 ... 40	21.3 x 13.4 x 22.4	39.7	CD-B39
III (FL)	115/60/10	yes	5 ... 40	9.1 x 16.1 x 16.5	19.4	CD-BC4
III (FL)	115/60/10	yes	5 ... 40	9.4 x 17.3 x 18.5	22	CD-BC6
III (FL)	115/60/10	yes	5 ... 40	13 x 19.3 x 18.5	26.9	CD-BC12
III (FL)	115/60/10	yes	5 ... 40	15.4 x 24.4 x 18.9	41.9	CD-BC26

Unless otherwise indicated, all data relates to the operation at nominal voltage and frequency and +20 °C ambient temperature. Cooling capacity measured according to DIN 12876-2.

Voltage Options

CORIO™

Model	Order No.	Available voltage options / Heating capacity kW						
		230 V 50 Hz	208-230 V 60 Hz	208-230 V 50-60 Hz	100-115 V 50-60 Hz	115 V 60 Hz	100 V 50 - 60 Hz	200 V 50 - 60 Hz
CD-200F	9 012 701	2.0	1.6 - 2.0	-	-	1.0	0.8	-
CD-201F	9 012 702	2.0	1.6 - 2.0	-	-	1.0	0.8	-
CD-300F	9 012 703	2.0	1.6 - 2.0	-	-	1.0	0.8	-
CD-600F	9 012 704	2.0	1.6 - 2.0	-	-	1.0	0.8	-
CD-601F	9 012 705	2.0	1.6 - 2.0	-	-	1.0	0.8	-
CD-900F	9 012 706	2.0	1.6 - 2.0	-	-	1.0	-	1.5
CD-1000F	9 012 707	2.0	1.6 - 2.0	-	-	1.0	-	1.5
CD-1001F	9 012 708	2.0	1.6 - 2.0	-	-	-	-	1.5
C	9 011 000	-	-	1.6 - 2.0	0.8 - 1.0	-	-	-
CD	9 012 000	2.0	1.6 - 2.0	-	-	1.0	0.8	-
C-BT5	9 011 305	-	1.6 - 2.0	1.6 - 2.0	0.8 - 1.0	-	-	-
C-BT9	9 011 309	-	-	1.6 - 2.0	0.8 - 1.0	-	-	-
C-BT19	9 011 319	-	1.6 - 2.0	1.6 - 2.0	0.8 - 1.0	-	-	-
C-BT27	9 011 327	-	-	1.6 - 2.0	0.8 - 1.0	-	-	-
C-B5	9 011 405	-	-	1.6 - 2.0	0.8 - 1.0	-	-	-
C-B13	9 011 413	-	-	1.6 - 2.0	0.8 - 1.0	-	-	-
C-B17	9 011 417	-	-	1.6 - 2.0	0.8 - 1.0	-	-	-
C-B19	9 011 419	-	-	1.6 - 2.0	0.8 - 1.0	-	-	-
C-B27	9 011 427	-	-	1.6 - 2.0	0.8 - 1.0	-	-	-
CD-BT5	9 012 305	2.0	1.6 - 2.0	-	-	1.0	0.8	-
CD-BT19	9 012 319	2.0	1.6 - 2.0	-	-	1.0	0.8	-
CD-BT27	9 012 327	2.0	1.6 - 2.0	-	-	1.0	0.8	-
CD-B5	9 012 405	2.0	1.6 - 2.0	-	-	1.0	0.8	-
CD-B13	9 012 413	2.0	1.6 - 2.0	-	-	1.0	0.8	-
CD-B17	9 012 417	2.0	1.6 - 2.0	-	-	1.0	0.8	-
CD-B19	9 012 419	2.0	1.6 - 2.0	-	-	1.0	0.8	-
CD-B27	9 012 427	2.0	1.6 - 2.0	-	-	1.0	0.8	-
CD-B33	9 012 433	2.0	1.6 - 2.0	-	-	1.0	0.8	-
CD-B39	9 012 439	2.0	1.6 - 2.0	-	-	1.0	0.8	-
CD-BC4	9 012 504	2.0	1.6 - 2.0	-	-	1.0	0.8	-
CD-BC6	9 012 506	2.0	1.6 - 2.0	-	-	1.0	0.8	-
CD-BC12	9 012 512	2.0	1.6 - 2.0	-	-	1.0	0.8	-
CD-BC26	9 012 526	2.0	1.6 - 2.0	-	-	1.0	0.8	-

Unless otherwise indicated, all data relates to the operation at nominal voltage and frequency and +20 °C ambient temperature. Cooling capacity measured according to DIN 12876-2.



NORTH AMERICA

JULABO USA Inc.

884 Marcon Boulevard
Allentown, PA 18109
United States of America

Tel. +1 610 231 0250
Fax +1 610 231 0260
Tollfree +1 800 458 5226

info@julabo.us
www.julabo.com

GERMANY Headquarters

JULABO GmbH
www.julabo.com

ITALY

JULABO Italia Srl.
www.julaboitalia.it

UK

JULABO UK, Ltd.
www.julabo.com

FRANCE

JULABO France SAS
www.julabo.com

NETHERLANDS

JULABO Nederland B.V.
www.julabo.com

JAPAN

JULABO Japan Co., Ltd.
www.julabo-japan.co.jp

KOREA

JULABO Korea Co., Ltd.
www.julabo-korea.co.kr

CHINA

JULABO Technology (Beijing) Co., Ltd.
www.julabo.com.cn

LATIN AMERICA

JULABO Latin America
www.julabo-latinamerica.com

SINGAPORE

JULABO Singapore Pte., Ltd.
www.julabo.com

INDIA

JULABO India
www.julabo.com

**Plus more than
100 partner distributors
worldwide**