



Thomas
Scientific

go green
with

Enviro-Safe[®]

The only thermometers and packaging certified
environmentally safe!

- EnviroKleen[™] certified for environmental safety by ChemTel, Inc.
- Non-toxic, non-hazardous, biodegradable green **Enviro-Safe**[®] liquid.
- Lead-free glass and recyclable packaging.
- Accuracy **traceable** to NIST and DKD - statement of accuracy included.
- Individually **serialized** meeting SOP's and Reportability requirements. (excludes pocket and 200mm lengths)
- **Made in the USA** by H-B, an ISO 9001:2000 company with ISO Guide 17025:2005 laboratory accreditation through A2LA.
- RoHS compliant.

Why Specify **Enviro-Safe**[®]?

- **Enviro-Safe**[®] replaces mercury thermometers banned (or partially banned) in more than a dozen US states and many European countries.
- **Enviro-Safe**[®] is the ONLY 100% Environmentally safe thermometer on the planet. Liquid is biodegradable and will clean up with soap and water. The glass is lead free and non-toxic.
- **Enviro-Safe**[®] meets government, education, and industry mandates to purchase "Green" products.
- **Enviro-Safe**[®] can be used wherever spirit (hazardous) or mercury (hazardous) thermometers are being used
- **Enviro-Safe**[®] qualifies for H-B's Mercury Exchange Program. Call 800-4-TEST-LAB for details.
- **Enviro-Safe**[®] has lock out specifications. No other thermometer company can meet or exceed these specifications.
- Manufactured in the USA by a US company, in business since 1903. Meets government requirements for made in the USA product.



www.thomassci.com

green

is not just another

thermometer liquid color...



Enviro-Safe[®] Laboratory Thermometers

Range	Division	Accuracy	Immersion	Item No.
200mm (8") Length				
-10 to 110°C	1°	1°	50mm (2")	9317C01
-10 to 110°C	1°	1°	Total	9317C03
-10 to 150°C	1°	1°; 1.5° above 105°	50mm (2")	9317C05
-10 to 150°C	1°	1°; 1.5° above 105°	Total	9317C07
20 to 230°F	2°	2°	50mm (2")	9317C09
20 to 230°F	2°	2°	Total	9317C11
20 to 300°F	2°	2°	50mm (2")	9317C13
20 to 300°F	2°	2°	Total	9313C15
305mm (12") Length				
-20 to 110°C	1°	1°	76mm (3")	9313A27
-20 to 110°C	1°	1°	Total	9313C17
-20 to 150°C	1°	1°; 1.5° above 105°	76mm (3")	9313C19
-20 to 150°C	1°	1°; 1.5° above 105°	Total	9313C21
0 to 230°F	2°	2°	76mm (3")	9313C23
0 to 230°F	2°	2°	Total	9313C39
0 to 300°F	2°	2°; 3° above 221°	76mm (3")	9313C27
0 to 300°F	2°	2°; 3° above 221°	Total	9313C29
355mm (14") Length				
-10 to 260°C	1°	1°; 1.5° above 105°; 2° above 200°	76mm (3")	9313A25
-10 to 225°C	1°	1°; 1.5° above 105°; 2° above 200°	Total	9313C31
20 to 500°F	2°	2°; 3° above 221°; 4° above 392°	76mm (3")	9313C33
20 to 440°F	2°	2°; 3° above 221°; 4° above 392°	Total	9313C35
405mm (16") Length				
-1 to 51°C	0.1°	±1° full scale	76mm (3")	9313C37
420mm (16½") Length				
-1 to 61°C	0.1°	±1° full scale	76mm (3")	9313C39
460mm (18") Length				
-1 to 51°C	0.1°	±1° full scale	76mm (3")	9313C41

Enviro-Safe[®] Pocket Thermometers

Range	Division	Accuracy	Length	Closed Metal Case	Window Metal Case	Closed Plastic Case	Window Plastic Case	Aluminum Duplex Case	Window Nickel-Plated Brass Case
-10 to 110°C	1°	1°	160mm (6¼")	9317B01	9317B09	9317B17	9317B25	9317B33	9317B41
-5 to 50°C	0.5°	0.5°	160mm (6¼")	9317B03	9317B11	-	9317B27	9317B35	9317B43
0 to 220°F	2°	2°	160mm (6¼")	9317B05	9317B13	9317B21	9317B29	9317B37	9317B45
20 to 120°F	1°	1°	160mm (6¼")	9317B07	9317B15	9317B12	9317B31	9317B39	9317B47

