# HyFlex® 11-800

# The ideal general purpose glove



### **Product information**

Australia: Level 3, 678 Victoria Street, Richmond, Victoria 3121 Telephone: 1800 337 041 Facsimile: 1800 803 578

China: Room 1012-1013, Yunsun Tower, No. 2025 Zhongshan West Road, Shanghai, China 200 235

Telephone: +86 21 5103 6377 Facsimile: +86 21 5407 1107

Malaysia: Lot 16, Persiaran Perusahaaan Section 23, Shah Alam 40000 Telephone: +60 3 5541 9797 Facsimile: +60 3 5549 4397

Japan: 2nd Floor, Ochanomizu Wing Building, 15-13 Hongo 2-chrome, Bunkyo-ku, Tokyo 113 0033

Telephone: +81 3 5805 3781 Facsimile: +81 3 5800 6171

#### **Primary industries**

Automotive and transportation
Metal fabrication
Machinery and equipment
Oil, gas and chemical
Building and construction
Recycling
Mining

Email: protection@ap.ansell.comWebsite: www.ansell.com.au

www.ansellasiapacific.com



The world leader in hand protection

## HyFlex® 11-800

Multi-purpose		Light Mech		anical protection				
Style no	Туре	Liner material	Coating material	Cuff style	Colour	Sizes	Length mm	Packaging
11-800	Palm coated	Nylon	Foam nitrile	Elasticised knitwrist	Grey coating on a white liner	6, 7, 8, 9, 10, 11	200 – 265	12 pairs in a bag 12 bags in a carton




• Ansell's best-selling HyFlex 11-800 glove is the original nitrile foam glove.

- A highly versatile solution for precision assembly and general handling, it provides the perfect balance between comfort, dexterity and protection.
- Advanced knitting technology allows increased stretch and flexibility in high-stress areas: the hand operates more freely, improving comfort and reducing hand fatigue.

Featured technology

**KVSD** 



- Automotive and transportation Metal fabrication
- Machinery and equipment
- Oil, gas and chemical
- Building and construction
- · Recycling
- Mining

Note: Not a chemical resistant glove.

#### Ideal applications

- Warehouse work
- Assembly of white goods
- Light assembly tasks
- General handling



3131 FN388

Risk Category II

Testing compliant to AS/NZS 2161 Anti-static according to EN1149

