

MB92

High Performance Moisture Analysis with Advanced Features

Display

4.3" Capacitive touchscreen display

Communication

RS232, USB Host, USB Device (cables not included)

Construction

Carbon fiber heating source, enhanced durability, metal pan support, metal pan handler, in-use cover

Design Features

Upgraded load cell, 8 shut-off criteria including custom settings, 4 heating profiles, 40C to 200C heating range

Operation

Power cord (included)



Robust and durable with the new carbon heating technology and an upgraded full color capacitive touchscreen.

Multiple drying profiles, shut off criteria and methods offer great flexibility in method creation. Enhanced password protection ensures greater data security and integrity.

A full glass panel and tool-free heating chamber assembly makes cleaning and maintenance easy. Perfect for both the laboratory and the production floor.

Model	Capacity	Moisture Readability	Pan Size	Item Number	List Price (USD)
MB92	90 g	1 mg / 0.01%	3.5 in (90 mm)	30971930	4,900

Accessories	Item Number	
Pan Handler, MB32, MB62, MB92	30954234	97
In-Use-Cover, MB92	30954269	55
Temp. calibration kit MB Series	11113857	778
Scoop	30284477	68
SF40A Impact Printer	30064203	1,303
Interface Kit, RS232-USB	30304101	191
Interface Kit, RS232-Ethernet	30304102	191

Accessories	Item Number	
Cage, Sample, MB Series	80252477	139
Reusable Pan, Set (3), 7mm	80252478	116
Reusable Pan, Set (3), 14mm	80252479	120
Cable RS232 IBM 9P Male-to-Female	80500525	254
Anti-Theft Device Lab Balance	80850043	305
Aluminum Pan (80)	80850086	87
Glass Fiber Pads (200)	80850087	137



MB62

Designed for Durability and Flexible Performance for a Variety of Applications

Display

5" LCD with dot matrix second line display

Communication

RS232, USB Device (cables not included)

Construction

Carbon fiber heating source, enhanced durability, metal pan support, metal pan handler, in-use cover

Design Features

Upgraded load cell, knob control, 7 shut-off criteria, 4 heating profiles, 40C to 200C heating range

Operation

Power cord (included)



Designed with durability and simplicity in mind, the wide 5-inch LCD display, knob control, and new carbon fiber heating technology guarantee a longer service life and reliable results.

Flexible method and sample management with 4 drying profiles, 7 shut off criteria and library storage for up to 20 methods and 100 results with sample ID for easy recall.

Always understand the status of your test with the status indication curve and multi-color status light.

Model	Capacity	Moisture Readability	Pan Size	Item Number	List Price (USD)
MB62	90 g	1 mg / 0.01%	3.5 in (90 mm)	30971929	4,200

Accessories	Item Number	Accessories	Item Number	Item Number
Pan Handler, MB32, MB62, MB92	30954234	Cage, Sample, MB Series	80252477	139
In-Use-Cover, MB32, MB62	30954235	Reusable Pan, Set (3), 7mm	80252478	116
Temp. calibration kit MB Series	11113857	Reusable Pan, Set (3), 14mm	80252479	120
Scoop	30284477	Cable RS232 IBM 9P Male-to-Female	80500525	254
SF40A Impact Printer	30064203	Anti-Theft Device Lab Balance	80850043	305
Interface Kit, RS232-USB	30304101	Aluminum Pan (80)	80850086	87
Interface Kit, RS232-Ethernet	30304102	Glass Fiber Pads (200)	80850087	137



MB32

Perfect for Routine Moisture Testing

Display

LCD with dot matrix second line display

Communication

RS232, USB Device (cables not included)

Construction

Carbon fiber heating source, enhanced durability, metal pan support, metal pan handler, in-use cover

Design Features

Upgraded load cell, knob control, 5 shut-off criteria, 2 heating profiles, 40C to 180C heating range

Operation

Power cord (included)



An LCD with second line display, navigation knob, and intuitive operation makes for convenient and easy routine moisture testing.

The new carbon fiber heating technology and upgraded loadcell shortens analysis time, saves power, and produces accurate and repeatable results.

Robust, slim design with a strong housing ensures MB32's durability even in harsh environments.

Model	Capacity	Moisture Readability	Pan Size	Item Number	List Price (USD)
MB32	90 g	1 mg / 0.01%	3.5 in (90 mm)	30971928	3,300

Accessories	Item Number	Accessories	Item Number	Item Number	Item Number
Pan Handler, MB32, MB62, MB92	30954234	Cage, Sample, MB Series	80252477	97	139
In-Use-Cover, MB32, MB62	30954235	Reusable Pan, Set (3), 7mm	80252478	55	116
Temp. calibration kit MB Series	11113857	Reusable Pan, Set (3), 14mm	80252479	778	120
Scoop	30284477	Cable RS232 IBM 9P Male-to-Female	80500525	68	254
SF40A Impact Printer	30064203	Anti-Theft Device Lab Balance	80850043	1,303	305
Interface Kit, RS232-USB	30304101	Aluminum Pan (80)	80850086	191	87
Interface Kit, RS232-Ethernet	30304102	Glass Fiber Pads (200)	80850087	191	137

