Description: Nor-Lake Scientific Manual Defrost Hydrocarbon Laboratory & Medical Freezer 20 Cu. Ft. Capacity One solid swing door, right hinged Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts 2 probes; 1 in air and 1 in glycol bottle Adjustable operating temperature range: -15°C – -25°C Six fixed shelves Keyed door lock Magnetic door gasket for positive seal Leveling legs Probe access port (3/8") Powder coat exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R290), foam insulation and packaging	Product Name:	NSPF201WWW/0MHC
Medical Freezer 20 Cu. Ft. Capacity One solid swing door, right hinged Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts 2 probes; 1 in air and 1 in glycol bottle Adjustable operating temperature range: -15°C – -25°C Six fixed shelves Keyed door lock Magnetic door gasket for positive seal Leveling legs Probe access port (3/8") Powder coat exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R290), foam insulation and packaging		
compressor parts warranty Exterior dimensions: 30 ¾ "W x 28 ½" D x 74 5/8"H Note: This unit must have 4" clearance on sides and back for adequate ventilation Manual defrost 115V, 60 Hz, 1.96 Amps, ½ HP UL/C-UL listed	Description:	Medical Freezer 20 Cu. Ft. Capacity One solid swing door, right hinged Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts 2 probes; 1 in air and 1 in glycol bottle Adjustable operating temperature range: -15°C25°C Six fixed shelves Keyed door lock Magnetic door gasket for positive seal Leveling legs Probe access port (3/8") Powder coat exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R290), foam insulation and packaging Two year parts and labor warranty, plus additional three year compressor parts warranty Exterior dimensions: 30 ¾ "W x 28 ½" D x 74 5/8"H Note: This unit must have 4" clearance on sides and back for adequate ventilation Manual defrost 115V, 60 Hz, 1.96 Amps, ½ HP UL/C-UL listed
·		UL/C-UL listed