



DASH APEX 6 SET & LOCK STAT CENTRIFUGE

Thomas No. 20A00K610

Discover a better way to spin STAT with labForce's DASH Apex 6 STAT centrifuges. Minimize lab error, reduce turnaround time, and streamline training with the DASH Apex's simple controls and powerful performance.

Easy to Monitor

Prevent forgotten samples and reduce TAT with LED lid lighting (patent pending). Bright lights indicate when the centrifuge is ready to load (off), running (on), or done (flashing). Lights continue flashing until the lid is opened.

Easy to Use

The simple two-button interface makes it easy to select a preset or program your custom validated STAT cycles. Use all three presets, or set and lock to a single cycle for maximum repeatability. Spin 75-100 mm (3-10 mL) tubes with the same rotor and universal tube holders.

Eliminate Wait Time

Further shorten TAT by using a centrifuge array in accessioning to eliminate queuing. The array takes advantage of the DASH Apex 6's compact size to allow samples to be spun as soon as they arrive.

Safe and Durable

Enjoy years of worry-free operation with the DASH Apex 6's brushless motor and rugged, reinforced carbon fiber components. Enhance lab safety with imbalance protection and a clear, shatterproof lid, which locks until the centrifuge has stopped completely.

A Great Value


Each centrifuge comes ready to run with a horizontal rotor, universal tube holders, and 2-year warranty included in the affordable price.




2-Stage Horizontal Rotor

Our patented swing-out horizontal rotor design incorporates a unique test tube holder that produces the ideal horizontally separated samples.

Loading Angle



Rotation Angle



Tubes

6 75-100 mm 3-10 mL

Applications

STAT Chemistry, Coag, PPP

Centrifugation

Horizontal 4,000 xg Max RCF 5,300 Max RPM

Included

Rotor, Tube Holders

Warranty

2 years
Rotor: lifetime warranty
Extended warranty available

DASH APEX 6



Free 30-Day Evaluation (U.S. Only)

Part Numbers		
Centrifuge	Thomas No. 20A00K610	
Replacement 75-100 mm Tube Holder/Bucket	03-1-0007-0046	
Adapters, 0.5 to 1 mL	7713068 (1 qty)	
Adapters, 1.5 to 2 mL	7713065 (1 qty)	
1 yr Warranty Extension	03-0-0007-0003	
2 yr Warranty Extension	03-0-0007-0004	
3 yr Warranty Extension	03-0-0007-0005	
* Custom Settings	00-100-101	

^{*} Add this part number to your centrifuge order to have your custom validated cycles pre-programmed at the factory

Factory Settings				
	RPM	Time	G-Force	
1st Setting/Cycle	5,300	3	4,000	
2nd Setting/Cycle	5,300	5	4,000	
3rd Setting/Cycle	3,800	7	2,000	

Specifications	
Sound level	61 dBA
Dimensions (W x D x H)	11 x 13.5 x 8 in
	28 x 34 x 20 cm
Weight	12 lbs (5.4 kg)
Power	95 to 253 VAC - 50/60 Hz













Disclaimer: Pricing and offers subject to change without notice.



ThomasScicom

General Lab 833.544.7447

Production 833.750.1234







