


## Lab products

The **heart** of every lab

Up to **75%** off



Save on **meters, stirrers, mixers, rockers, buffers and much more**

The benchtop equipment you rely on every day is often the key to the speed and efficiency of your workflows. For a limited-time, find big savings on the small devices that keep your lab functioning and help drive your research forward.

- Thermo Scientific™ Cimatec+™ Stirring Hotplates Series
- Thermo Scientific™ Basic Vortex Mixers
- Thermo Scientific™ Tube Revolver Rotators
- Thermo Scientific™ Digital Dry Baths/Block Heaters
- Thermo Scientific™ Digital Tube Rockers
- Thermo Scientific™ Precision™ General Purpose Baths
- Thermo Scientific™ Orion™ Lab Star and Versa Star Pro™ Benchtop pH Meters
- Thermo Scientific™ Orion Star™ Portable Multiparameter Meters
- Thermo Scientific™ Orion™ All-in-One pH Buffer Kits
- Thermo Scientific™ Orion™ ROSS Ultra™ Glass Triode™ pH/ATC Combination Electrodes
- Thermo Scientific™ Orion™ ROSS™ Sure-Flow™ pH Electrodes
- Thermo Scientific™ Barnstead™ GenPure™ Pro, MicroPure™ and Smart2Pure™ Pro Water Purification Systems
- Thermo Scientific™ Heratherm™ General Protocol Microbiological Incubators

## Save on benchtop equipment at the core of your productivity

Order using the catalog numbers below to take advantage of your special pricing today.

### Ordering information

#### Cimarec+ Stirring Hotplates Series

Plate surface	Speed	Electrical req.	Thomas No.	Cat. No.
4.25 x 4.25 in. (10.8 x 10.8 cm)	50–1,500 rpm	100/120 V, 50/60 Hz	<b>1187P02-PROMO</b>	SP88854100PM
7.25 x 7.25 in. (18.4 x 18.4 cm)	50–1,500 rpm	100/120 V, 50/60 Hz	<b>1187P04-PROMO</b>	SP88857100PM
10.25 x 10.25 in. (26 x 26 cm)	50–1,500 rpm	100/120 V, 50/60 Hz	<b>1187P10-PROMO</b>	SP88850100PM

#### Thermo Scientific Basic Vortex Mixer

Orbit	Speed	Voltage	Thomas No.	Cat. No.
4 mm	200–3,000 rpm	100/240 V	<b>25A00A237-PROMO</b>	88882011PM

#### Thermo Scientific Tube Revolver Rotator

Speed	Temp. range	Holds	Electrical req.	Thomas No.	Cat. No.
10–40 rpm	2–60°C	Combination of 4 paddles of: <ul style="list-style-type: none"><li>• 7 x 10 to 15 mL</li><li>• 7 x 5 to 7 mL</li><li>• 15 x 1.5 to 2 mL</li><li>• 21 x 0.5 to 0.8 mL tubes</li></ul> 1 paddle of: <ul style="list-style-type: none"><li>• 6 x 50 mL tubes</li></ul>	100/240 V, 50/60 Hz	<b>1199A86-PROMO</b>	88881001PM

#### Thermo Scientific Digital Dry Baths/Block Heaters

Time	Temp. range	Voltage	Quantity	Thomas No.	Cat. No.
≤20 min.	30–130°C	100/120 V	2*	<b>1188Y71-PROMO</b>	88870002PM
≤25 min.	30–130°C	100/120 V	4*	<b>1188Y72-PROMO</b>	88870003PM

\*Order separately

#### Thermo Scientific Digital Tube Rocker

Speed range	Speed control	Tube diameter	Electrical req.	Thomas No.	Cat. No.
2–40 rpm	±1 rpm	30 mm	100/240 V, 50/60 Hz	<b>25A00A238-PROMO</b>	88882017PM

#### Thermo Scientific Precision General Purpose Baths

Capacity	Electrical req.	Thomas No.	Cat. No.
2 L	120/230 V, 50/60 Hz	<b>1184L86-PROMO</b>	TSGP02PMSH
5 L		<b>1184L88-PROMO</b>	TSGP05PMSH
10 L		<b>1184L89-PROMO</b>	TSGP10PMSH
20 L		<b>1184L90-PROMO</b>	TSGP20PMSH



### Benchtop pH and multiparameter meters

Description	Measures	Includes	Thomas No.	Cat. No.
Thermo Scientific Orion Lab Star PH111 Bench pH Meter	pH, mV, ORP, temp.	<ul style="list-style-type: none"> <li>Thermo Scientific™ Orion™ Triode™ 3-in-1 pH/ATC Probe</li> <li>Thermo Scientific Orion All-in-One pH Buffer Kit</li> <li>Storage and cleaning solution, 60 mL</li> <li>Kit meter with electrode stand, PC cable and universal power adapter</li> </ul>	<b>22A00F839-PROMO</b>	LSTAR1115PM
Thermo Scientific Orion Versa Star Pro Benchtop pH Meter	pH, mV, ORP, temp.	<ul style="list-style-type: none"> <li>Versa Star Pro Meter with pH module</li> <li>ROSS Ultra Glass-Body pH/ATC Electrode</li> <li>Thermo Scientific™ Orion™ Automatic Stirrer Probe and Paddle</li> <li>Orion All-in-One pH Buffer Kit</li> <li>Electrode stand, 100–240 V universal power adapter and computer cable</li> </ul>	<b>1218X72-PROMO</b>	VSTAR12PM
Thermo Scientific Orion Star A329 pH/ISE/Conductivity/Dissolved Oxygen Portable Multiparameter Meter	pH, ion concentration, conductivity, dissolved oxygen, temp	<ul style="list-style-type: none"> <li>Star A329 pH/ISE/Conductivity/RDO/DO Meter with batteries</li> <li>Thermo Scientific Orion ROSS Ultra Low Maintenance pH/ATC Triode Combination Electrode</li> <li>Thermo Scientific™ Orion™ DuraProbe™ 4-Cell Conductivity Probe</li> <li>Thermo Scientific™ Orion™ RDO™ Dissolved Oxygen Probe</li> </ul>	<b>1218X69-PROMO</b>	STARA3295PM

### Orion All-in-One pH Buffer Kit

Description	Includes	Thomas No.	Cat. No.
4 x 475 mL, 1 x 60 mL	<ul style="list-style-type: none"> <li>475 mL bottle each of pH 4.01, 7.00 and 10.01 buffers</li> <li>475 mL bottle of Thermo Scientific™ Orion™ ROSS™ pH Electrode Storage Solution</li> <li>60 mL bottle of pH electrode cleaning solution</li> <li>12 mm diameter electrode storage bottle</li> </ul>	<b>1197F21-PROMO</b>	810199PM

### Electrodes

Description	Diameter	pH range	Operating temp.	Thomas No.	Cat. No.
Thermo Scientific Orion ROSS Ultra Glass Triode pH/ATC Combination Electrode	12 mm	0–14	0–100°C	<b>1222U09-PROMO</b>	8302BNUMDPM
Thermo Scientific Orion ROSS Sure-Flow pH Electrode, BNC Connector	16 mm			<b>1234Y72-PROMO</b>	8172BNWPPM

## Water purification systems

Description	Operating pressure	Electrical req.	Thomas No.	Cat. No.
Thermo Scientific Barnstead GenPure Pro	2–6 bar	90/240 V, 50/60 Hz	<b>1204P03-PROMO</b>	50131948PR
Thermo Scientific Barnstead MicroPure	0.1–6 bar	100/240 V, 50/60 Hz	<b>1209T48-PROMO</b>	50132370PROMO
Thermo Scientific Barnstead Smart2Pure Pro	1– 6 bar	100/240 V, 50/60 Hz	<b>1147K95-PROMO</b>	50157873PRVC

## Heratherm General Protocol Microbiological Incubators

Capacity	Electrical req.	Thomas No.	Cat. No.
2.6 cu. ft. (75 L)	120 V, 60 Hz	<b>1218W90-PROMO</b>	51028063PM
4 cu. ft. (117 L)	120 V, 60 Hz	<b>1218W91-PROMO</b>	51028064PM



 833.544.7447

 customerservice@thomassci.com

 thomassci.com



 Contact a Thomas Scientific sales representative to learn more about this offer.

Discounts taken off list price.

This offer is valid January 1, 2025 to June 30, 2025.

US customers acknowledge that this offer may include a discount or other price reduction that must be properly and accurately accounted for and reported by customer in accordance with all federal and state laws, including without limitation the federal anti-kickback law (42 U.S.C. § 1320a-7b(b)(3)(A)) and regulations thereunder (42 C.F.R. §1001.952(h)).

Canada customers acknowledge that this offer may include a discount or other price reduction that must be properly and accurately accounted for and reported by customer as applicable.

**For Laboratory Use. It is the customer's responsibility to ensure that the performance of the product is suitable for customers' specific use or application.**

© 2024 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific and its subsidiaries unless otherwise specified. STUDIO-24-198-3422

**thermo** scientific