| Product Name: | NSWDR472WWG/0 |
|---------------|--|
| | |
| Description: | NSWDR472WWG/0 White Diamond Series Laboratory and Medical Refrigerator 47 Cu. Ft. Capacity Two sliding glass doors, self-closing (energy efficient, double pane vacuum insulated) Microprocessor temperature controller Touch Screen Digital Temperature Display with user friendly interface Alarm Module with battery back-up to support temperature monitoring and alarms Password-protected control panel C°/F° switchable .1° Resolution Adjustable operating temperature: 1°C to 10°C Active temperature scale bar display Resettable 1-point min/max history |
| | Digital 24-hour temperature chart Temperature data logging USB port for data transfer and software updates Real-time operational display clock 4-20mA output Adjustable alarm volume Audible and visual high/low temperature alarms 2 probes; 1 in air and 1 in sample bottle Sensor error alarm Power failure alarm Door ajar alarm Low battery alarm |
| | Alarm validation (audible, visual, and remote alarm) Alarm mute with ring back Remote alarm contacts Customizable alarm time delay settings Ten adjustable shelves (adjustable in ½" increments) Forced draft air circulation Keyed door lock Magnetic door gasket for positive seal Integrated door handles Swivel casters (3 ½") LED interior lights are safety shielded and switch controlled Probe access port (3/8") |
| | White powder-coated steel exterior and interior Hydrocarbon, natural refrigerant (R290) Easily cleaned smooth interior Three year parts and labor warranty, plus an additional two year compressor parts warranty Exterior dimensions: 54 1/8" W x 32 1/2" D x 82 1/2" H with casters; 78 ¼" H without casters Cycle defrost 115V, 60 Hz, 4.5 Amps. 1/4 HP ETL listed Energy Star certified Shipping weight: 508 lbs. |