

MX Analytical Balances

Fast and Accurate



Fast and Accurate Weighing

The high-resolution load cell delivers accurate and reliable results and offers readability as low as 0.01 mg. With the SmartPan, the balance stabilizes quickly, even in turbulent environments, enabling fast and efficient weighing.



GxP Compliance Support

Automatic data logging and user management options help you to comply with GxP guidelines. Transfer data to a printer or computer for complete and error-free documentation.




Innovative Engineering

Clever features provide an ergonomic, stress-free weighing experience, especially for long or repetitive tasks: The StatusLight provides instant confirmation of the balance status, the backlit draft shield offers high visibility, and the ErgoDoors make weighing convenient.



Sustainable Design

High-quality materials and robust construction ensure a long balance lifetime, providing an overall low cost of ownership. Designed with sustainability in mind, including a power-saving mode, MX balances are efficient and economical in operation.



Smart Features

For Advanced Requirements

The superior load cell, quality assurance functions, and multiple connectivity options combine to satisfy higher demands for accuracy, compliance, and efficiency. Easily integrated into your existing laboratory infrastructure, these balances have a multitude of smart features to make your weighing processes fast, convenient, and efficient.

Define your own routine testing schedule on the balance according to your internal quality requirements and process tolerances. Your balance will remind you when tests are due to be sure your results remain accurate in the intervals between calibrations.

METTLER TOLEDO

Technical Specifications



	MODEL Thomas No.	MX105 24A00B886	MX105DU 24A00B888	MX205DU 24A00B892
Limit values				
Capacity		120 g	120 g	220 g
Readability		0.01 mg	0.1 mg	0.1 mg
Capacity of fine range		–	42 g	82 g
Readability in fine range		–	0.01 mg	0.01 mg
Repeatability (at 5% load)		0.02 mg	0.02 mg	0.02 mg
Linearity deviation		0.1 mg	0.2 mg	0.2 mg
Sensitivity offset (at nominal load) ▲		0.4 mg	0.4 mg	0.8 mg
Typical values				
Repeatability (at 5% load)		0.0125 mg	0.0125 mg	0.0125 mg
Linearity deviation		0.06 mg	0.06 mg	0.06 mg
Sensitivity offset (at nominal load) ▲		0.25 mg	0.25 mg	0.5 mg
Minimum weight (USP, tolerance = 0.10%) ▼		25 mg	25 mg	25 mg
Minimum weight (tolerance = 1%) ▼		2.5 mg	2.5 mg	2.5 mg
Settling time		2 s	2 s	2 s
Dimensions and other specifications				
Balance dimensions (W × D × H)		222 × 379 × 353 mm	222 × 379 × 353 mm	222 × 379 × 353 mm
Weighing pan diameter		80 mm	80 mm	80 mm

▲ after adjustment with internal weight

▼ determined at 5% load, k = 2

All models are available as approved versions.



	MODEL Thomas No.	MX104 24A00B884	MX204 24A00B890	MX304 24A00B894
Limit values				
Capacity		120 g	220 g	320 g
Readability		0.1 mg	0.1 mg	0.1 mg
Repeatability (at 5% load)		0.1 mg	0.1 mg	0.1 mg
Linearity deviation		0.2 mg	0.2 mg	0.3 mg
Sensitivity offset (at nominal load) ▲		0.5 mg	0.8 mg	1 mg
Typical values				
Repeatability (at 5% load)		0.05 mg	0.05 mg	0.05 mg
Linearity deviation		0.06 mg	0.06 mg	0.06 mg
Sensitivity offset (at nominal load) ▲		0.3 mg	0.5 mg	0.6 mg
Minimum weight (USP, tolerance = 0.10%) ▼		100 mg	100 mg	100 mg
Minimum weight (tolerance = 1%) ▼		10 mg	10 mg	10 mg
Settling time		2 s	2 s	2 s
Dimensions and other specifications				
Balance dimensions (W × D × H)		222 × 379 × 353 mm	222 × 379 × 353 mm	222 × 379 × 353 mm
Weighing pan diameter		90 mm	90 mm	90 mm

▲ after adjustment with internal weight

▼ determined at 5% load, k = 2

All models are available as approved versions.

Features

Performance

- MonoBloc weighing cell
- FACT automatic internal adjustment

Efficient Operation

- 7" touchscreen
- 10 built-in applications
- Statistical data analysis
- Ergonomic door operation
- Backlit draft shield

Quality Assurance

- OIML/NTEP approved
- User management
- Leveling assistant
- Configurable sample and task IDs
- Activity log
- StatusLight
- Configurable routine tests
- Time server synchronisation

Data Management

- 3 interfaces: USB-A, USB-C, Ethernet
- Bluetooth option
- Advanced reporting

- Autopublish function
- Drop-to-cursor
- MT-SICS
- EasyDirect Balance software

Sustainable Value

- Full metal housing
- IP41 (0.1 mg models)
- Overload protection
- Power-saving mode
- Easy-to-clean QuickLock draft shield

Power Consumption

Instrument Steady State	Approx. Power Consumption (W)*
Operational Mode	2.2
Standby Mode	2.1
Power Saving Mode	0.5

*Test results conducted by METTLER TOLEDO under ideal conditions.

Operational Mode = Default balance settings



Applications

- Weighing
- Piece Counting
- Density Determination
- Backweighing
- Differential Weighing
- Formulation
- Check Weighing
- Totating
- Dynamic Weighing
- Statistics



Accessories

Enhance performance, improve ergonomics, and handle your data efficiently with our wide range of accessories, including EasyDirect Balance data management software, printers, weights, density kit, and Bluetooth adapter.

For further information on accessories, please visit our web page.

► www.mt.com/lab-accessories



Professional Service

With a professional installation, your balance is expertly set up to deliver accurate results from day one.

To learn more about our service offerings, scan the QR code or visit our website:

▶ www.mt.com/professional-service



customerservice@thomasci.com



833.544.7447



thomasci.com

