

Immersion Cooler with air-cooled refrigerating unit. Electronic temperature control and digital display. Stainless steel housing with handle (front) and rollers (back), condensing probe of stainless steel and flexible cooling connection line in special single-tube construction, protective hose with smooth surface. The refrigeration unit works continuously. The temperature control actuates a solenoid valve in the cooling circuit. The temperature sensor is connected to the device with cable and plug.

MPC-Controller:

Modern and easy to use microprocessor controller with a large temperature display.

Limited to essential functions only:

- \* Large temperature display
- \* LED indicators for pump, cooling and heating
- \* Simple operation using only 3 keys

### Technical data according to DIN 12876

Operating temperature range	-100...40 °C	
Temperature stability at -10°C	0,5 K	
Temperature adjustment	digital	<b>Order-No.: 3005.0063.99</b>
Sensor external connection	Pt100	
Cooling power		
at 0°C	0,16 kW	
at -20°C	0,15 kW	
at -30°C	0,14 kW	
at -50°C	0,13 kW	
at -60°C	0,12 kW	
at -80°C	0,12 kW	
at -90°C	0,07 kW	
at -100°C	0,01 kW	
Safety classification	Class I / NFL	
Refrigeration machine	air-cooled, natural refrigerant	
Refrigerant	R1270	
Refrigerant quantity	0,114 kg	
Refrigerant 2nd stage	R1150	
Refrigerant quantity 2nd stage	0,056 kg	
Nominal diameter probe	48 mm	
Length of probe	155 mm	
Length flexible connection	1150 mm	
Overall dimensions WxDxH **	295x500x570 mm	
Net weight	61 kg	
Power supply requirement	115V 1~ 60Hz	
min. Fuse (1 phase)	10A	
min. ambient temperature	5 °C	
max. ambient temperature	40 °C	

from Serial-No.:

1.0/13

Technical details and dimensions are subject to change. No liability is accepted for errors or omissions.

Accessories and periphery: Pt100 sensor (Part.No. 6138)\*.

\* standard equipment

Output data valid for: Room temperature 20° C

in accordance with EN60034-1 the following voltage and frequency tolerances are valid:

Voltage + / - 5% with a simultaneous frequency tolerance of + / - 2%

Example -5% voltage and + 2% frequency -> not allowed!

-5% voltage and - 2% frequency -> allowed

\*\* Please respect space requirements. See operating conditions at [www.huber-online.com](http://www.huber-online.com)