

### APPLICATIONS

Food grade sanitizer used in the dairy, food and beverage processing industry for CIP pipeline cleaning, fruit and vegetable washing, and sanitizing. Appropriate for organic production sanitizing as approved by the NOP. It is also used in the treatment of cooling water, oilfield process water and wastewater. Additional uses are for slime and biofouling control in the pulp & paper industry, agricultural irrigation, dispersed pigments and coatings industries.

### PROPERTIES

**BioSide™ HS 15%** has a high oxidation potential and is very reactive. It exhibits excellent bactericidal and fungicidal activity against a wide range of microorganisms in cold or warm water. Product is stable for a minimum of 1 year under normal conditions. It ultimately degrades to oxygen, water, and acetic acid (vinegar).

### CHEMICAL COMPOSITION

**BioSide™ HS 15%** is an equilibrium mixture of peracetic acid, hydrogen peroxide, acetic acid, proprietary ingredients, and water.

Peracetic acid (% wt.)	14.8-15.7
H <sub>2</sub> O <sub>2</sub> (% wt.)	21.5-22.5
Acetic acid (% wt.)	15.8-16.6

### PHYSICAL PROPERTIES

Density 20°C (68°F), (g/ml)	1.135 (9.47 lbs/gal)
Vapor Pressure 20°C (68°F), (mbar)	27
pH 10% solution, 20°C (68 °F)	<1
Flash Point (DIN 51584)	> 98° C (207° F)
Freezing Point <	< -29° C (-20° F)

### APPEARANCE

Clear, colorless liquid (pungent vinegar-like odor)

### STORAGE

The **BioSide™ HS 15%** container must be stored in an upright position. The storage area should be well ventilated and **shaded from sunlight** as well as protected from sources of radiant heat. Contamination of the product, especially heavy metal ions and alkali, must be avoided.

### SHELF LIFE

At least 1 year without notable losses of active oxygen if stored properly.

### PACKAGING

5 gal (45 lb), 53 gal (500 lb), 300 gal (2841 lb)  
Available in HDPE plastic pails, drums and totes.

### TRANSPORT (DOT)

UN3109, Organic peroxide type F, liquid (<=25% peracetic acid with <=26% hydrogen peroxide), 5.2 (8)

All information and statements contained herein are believed to be accurate at the time of publication, but Enviro Tech Chemical Services, Inc. makes no warranty with respect thereto, including but not limited to any results to be obtained or the infringement of any proprietary rights. Use or application of such information or statements is at user's sole discretion, without any liability on the part of Enviro Tech. Nothing herein shall be construed as a license of or recommendation for use which infringes upon any proprietary rights. Use of this product shall be the sole responsibility of user, and Enviro Tech shall not be liable in any way for said use, other than reimbursement for the actual cost of product.