

93-243 400 mm / 16 inch Extended Cuff Disposable Nitrile Gloves



Extra Long Cuff for Superior Forearm and Product Protection

- Designed with elbow-length cuff (400 mm/16 inches) provide additional protection to the upper arm and extra security against cross contamination
- Made with soft nitrile formulation for comfortable fit and feel while improved cuff design helps prevent gloves from rolling down
- Textured fingers and palm ensure a secure grip in a variety of applications
- Nitrile formulation offers greater puncture resistance and chemical resistance than natural rubber latex
- Gloves are packed in polybags to help protect product integrity

Industries

- Automotive
- Chemical (Basic, Specialty & Petrochemical)
- Electronics (Class 1000 & higher)
- Food Processing
- Life Sciences (Pharmaceutical, Biopharmaceutical & Medical Devices
- Recycling & Waste Disposal

Applications

- Analytical testing
- Handling compression press and tablet manufacturing
- Industrial cleaning
- Intricate parts handling
- Lab work, blending, compounding, filling
- Maintenance and equipment clean up





93-243 400 mm / 16 inch Extended Cuff Disposable Nitrile Gloves

TECHNICAL DATA SHEET:

PRODUCT INFORMATION:

	93-243
Material	Nitrile
Color	Blue
Glove Design	Ambidextrous, Powder-Free, Textured grip
Cuff	Beaded Cuff
Manufacturing/QMS Audit Standards	ISO 9001
Regulatory/Standards Compliance	COMPLIANT WITH ASTM D 3577, TYPE II
Packaging	100 gloves per polybag, 10 polybags in a shipper box
Storage	Keep out of direct sunlight; store in a cool and dry place.
Country of Origin	Malaysia

PHYSICAL PROPERTIES:

	TYPICAL VALUES					TESTING METHOD	
	5.5 - 6 XS	6.5 - 7 S	7.5 - 8 M	8.5 - 9 L	9.5 - 10 XL	10.5 - 11 XXL	
Length (mm/inches)	400/16	400/16	400/16	400/16	400/16	400/16	ASTM D3767/EN 420
Average Palm Width (mm)	76	86	96	108	120	132	

Freedom from Holes (Inspection level I)	1.5 /	ASTM D6319-10/ ASTM D5151-06/EN 374-2		
Palm Thickness Single Wall	(mm : 0.12)	ASTM D3767/EN 420		
	BEFORE AGING	AFTER AGING		
Ultimate Tensile Strength (MPa)	> 14	> 14	ASTM D6319-10	
Elongation at Break (%)	> 500	> 400	ASTM D6319-10	
Force at break (N)	6	6	EN 455-2	

ORDERING INFORMATION:

SIZE		5.5 - 6 6.5 - 7		7.5 - 8	8.5 - 9	9.5 - 10	10.5 - 11
		XS S		M	L	XL	XXL
93-243	REORDER NO.	93243060	93243070	93243080	93243090	93243100	93243110

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application

For additional information visit us at www.ansell.com, or call us at

Ansell 111 Wood Avenue South, Suite 210 Iselin, NJ 08830 **1-800-800-0444** Ansell-Canada 105 Lauder Street Cowansville, QC J2K 2K8 1-800-363-8340

* and ™ are trademarks owned by Ansell Limited or one of its affiliates. © 2016 All Rights Reserved. 2016.1855.v1

Performance Standards



Regulatory Compliance



