Corning[®] LSE[™] Shaking Incubators

CORNING



Corning LSE 49L and 71L Shaking Incubators (49L shown)



Corning LSE Benchtop Shaking Incubator

Corning LSE Shaking Incubators are the ideal solution to meet your small batch incubator needs. Whether performing bacterial research, microbiology, insect studies, yeast cultures, egg incubation, or any number of other applications, the shaking incubators from Corning provide a safe and convenient format for incubating your precious samples. Each model features an integrated orbital shaker designed into a compact footprint maximizing laboratory space. Additionally, a wide range of platform accessories are available to accommodate Corning glass and plastics consumables.

Features

- Outstanding temperature uniformity
- Large viewing area for undisturbed monitoring of samples
- Broad temperature range
- Multiple shelving options
- Precision control shaking mechanism



Corning® LSE™ Benchtop Shaking Incubator

Truly a benchtop style, the lid on the Corning benchtop shaking incubator has a low pivot point which provides a space-saving size sure to fit on the lab bench and under shelves. Each unit includes a software package, which provides the option of saving data to an external computer or monitoring rpm and temperature throughout runs. The maximum capacity is 4 x 1L flasks.

Specifications

Temperature Range	Ambient +5°C to +70°C
Operation Temperature Range	4°C to 65°C
Shaker Speed	20 to 300 rpm
Shaker Timer	1 minute to 99 hours or continuous
Shaker Orbit	19 mm
Temperature Increments	0.1°C
Temperature Accuracy	±0.5°C
Temperature Uniformity	±0.5°C
Speed Increments	1 rpm
Platform Dimensions	11.8 x 11.8 in. (30 x 30 cm)
Dimensions (W x D x H)	14.6 x 20.9 x 15.7 in. (37 x 53 x 40 cm)
Weight	43 lbs (19.5 kg)
Height Lid Open	21.7 in. (55 cm)
Communication Port	USB for temperature and rpm monitor with included Windows® compatible software
Electrical	120V/230V, 50/60 Hz



Corning LSE 49L Shaking Incubator

This cabinet-style incubator has a compact footprint and can also be stacked to maximize space efficiency. The built in orbital shaker accepts a large assortment of platforms and clamps that can accommodate flasks, Petri dishes, and test tube racks. The maximum capacity is 4 x 1L flasks.

Specifications

49L/1.7 cu. ft.
Ambient +5° to 80°C in 0.1°C increments/digital
±0.25°C/±0.1°C
20 to 400 rpm (maximum 300 rpm when stacked)
0 to 99 minutes or continuous
19 mm
4 x 1L, 5 x 500 mL, 9 x 250 mL, 16 x 125 mL
Interior: Mirrored stainless steel Exterior: Cold rolled steel
13.5 x 14.75 x 15 in. (34.3 x 37.5 x 38.1 cm)
23 x 19.25 x 22.25 in. (42.5 x 55 x 58 cm)
83 lbs (37.7 kg)
120V/230V, 50/60 Hz



This high performance shaking incubator has a full size glass door and internal light that allows easy viewing of samples without disturbing the chamber contents. Mechanical convection provides a safe, stable temperature environment and fast chamber temperature recovery after opening the door. The maximum capacity is $4 \times 2L/6 \times 1L$ flasks.



Chamber Volume	71L/2.5 cu. ft.
Temperature Range/Display	Ambient +5° to 80°C
Temperature Uniformity/Accuracy	±0.2°C at 37°C
Temperature Display	0.1°C
Shaker Speed	20 to 300 rpm
Shaker Orbit	19 mm
Shaker Timer	0 to 99 minutes or continuous
Dimensions (W x D x H)	Chamber: 17.4 x 15.6 x 16 in. (44.2 x 39.6 x 40.6 cm) Exterior: 22.6 x 21.4 x 25 in. (57.4 x 54.4 x 63.5 cm)
Weight	140 lbs (63.6 kg)
Electrical	120V/230V, 50/60 Hz


Ordering Information

Corning	SE Benchtop Shaking Incubator	
Cat. No.	Description	Qty/Cs
6790	LSE Benchtop shaking incubator with platform, 120V	1
6791	LSE Benchtop shaking incubator with platform, 230V (EU plug)	1
480144	Universal platform, 30 x 30 cm	1
480145	Petri dish shelf	1
480146	Sticky mat, 150 x 150 x 30 mm	1
480147	Microtiter hotel, holds maximum 4 microplates	1
480148	Combination tube holder, 6 x 15/50 mL tubes	1
480149	Plastic clamp, 125 mL	1
480150	Plastic clamp, 250 mL	1
480151	Plastic clamp, 500 mL	1
480152	Plastic clamp, 1000 mL	1
Corning	LSE 49L Shaking Incubator	
6750	LSE Shaking incubator, 49 Liters, 120V	1
6752	LSE Shaking incubator, 49 Liters, 230V (EU and UK plug)	1
480153	Flask clamp platform, pre-drilled	1
480154	Flat platform with nonslip rubber mat (300 x 300 mm)	1
480155	Double flat platform with non-slip rubber mat (300 x 300 mm)	1
480156	Universal spring-loaded clamp platform for Cat. Nos. 6750 and 6752 only	1
480157	Shelf, full, for Cat. Nos. 6750 and 6752	1
480158	Stacking adapter for Cat. Nos. 6750 and 6752	1
Corning		
6753	LSE 71L Shaking Incubator LSE Shaking incubator, 71L, 120V	1
6754	LSE Shaking incubator, 71L, 120V LSE Shaking incubator, 71L, 230V (EU and UK plug)	1
480159	Shaking platform pre-drilled for flask clamps	1
480159	Flat shaker platform with non-slip rubber mat (390 x 330 mm)	1
480161	Platform with 4 x 2L flask clamps	1
	<u>'</u>	1
480162	Platform with 6 x 1L flask clamps	1
480163 480164	Platform with 8 x 500 mL flask clamps	1
480165	Platform with 12 x 250 mL flask clamps Platform with 20 x 125 mL flask clamps	1
	ı	1
480166	Platform with 30 x 50 mL flask clamps	
480168	Rack holder for 15 mL test tubes Rack holder for 50 mL test tubes	1
480169 480170	Shelf, full, for Cat. Nos. 6753 and 6754	1 1
		т
•	or 49L and 71L Shaking Incubators	
480110	Clamp for 25 mL flask	1
480111	Clamp for 50 mL flask	1
480112	Clamp for 125 mL flask	1
480113	Clamp for 250 mL flask	1
480114	Clamp for 500 mL flask	1
480115	Clamp for 1,000 mL flask	1
480167	Clamp for 2,000 mL flask (for use with 71L only)	1



Complementary Products Insect media for the following cell lines: Sf9, Sf21, DS2, Tn-368* Cat. No.





*Custom formulations available upon request. Please contact your local Corning Account Manager.



Cat. No.	Description	Qty/Cs
4980-500	PYREX 500 mL narrow mouth Erlenmeyer flasks with heavy duty rim	36
4980-1L	PYREX 1L narrow mouth Erlenmeyer flasks with heavy duty rim	24
431143	Corning 125 mL polycarbonate Erlenmeyer flask with vent cap	50
431144	Corning 250 mL polycarbonate Erlenmeyer flask with vent cap	50
431147	Corning 1L polycarbonate Erlenmeyer flask with vent cap	25
431255	Corning 2L polycarbonate Erlenmeyer flask with vent cap	6



Gosselin™ Petri Dish

Cat. No.	Description	Qty/Pk	Qty/Cs
BP94S-01	Round Petri dish, 100 x 15 mm, stackable, sterile	25	500

For more specific information on claims, visit the Certificates page at www.corning.com/lifesciences.

Warranty/Disclaimer: Unless otherwise specified, all products are for research use only. Not intended for use in diagnostic or therapeutic procedures. Corning Life Sciences makes no claims regarding the performance of these products for clinical or diagnostic applications.

For additional product or technical information, visit www.corning.com/lifesciences or call 800.492.1110. Outside the United States, call +1.978.442.2200 or contact your local Corning sales office.

Corning Incorporated Life Sciences 836 North St. Building 300, Suite 3401 Tewksbury, MA 01876 t 800.492.1110 t 978.442.2200

f 978.442.2476

www.corning.com/lifesciences

Worldwide Japan EUROPE t 81 3-3586 1996 **Support Offices** France f 81 3-3586 1291 t 0800 916 882 ASIA/PACIFIC f 0800 918 636 t 82 2-796-9500 Australia/New Zealand Germany f 82 2-796-9300 t 61 427286832 t 0800 101 1153 Singapore f 0800 101 2427 China t 86 21 3338 4338 t 65 6572-9740 The Netherlands f 86 21 3338 4300 f 65 6861-2913 t 31 20 655 79 28 Taiwan f 31 20 659 76 73 India t 886 2-2716-0338 t 91 124 4604000 United Kingdom f 886 2-2516-7500 f 91 124 4604099 t 0800 376 8660 f 0800 279 1117

t 31 (0) 20 659 60 51 f 31 (0) 20 659 76 73 LATIN AMERICA grupoLA@corning.com Brasil t (55-11) 3089-7400 f (55-11) 3167-0700 Mexico t (52-81) 8158-8400

f (52-81) 8313-8589

All Other European Countries





