1 C	Premier Glass Door Chromatography Refrigerator 16 Cu. Ft. capacity One swing glass door, self-closing, right hinged, not reversible Microprocessor Temperature Controller
1 C	16 Cu. Ft. capacity One swing glass door, self-closing, right hinged, not reversible Microprocessor Temperature Controller
ADSAASPRR2AATFKOTMHLSPAVHHT PEwoC1E	Adjustable operating temperature range: 1°-10°C Digital Temperature Display and Alarm Module Sample simulated digital temperature display; .1° Resolution Adjustable temperature display in Celsius or Fahrenheit Audible and visual high/low temperature alarms Sensor error alarm Power failure alarm Resettable 1-point Min/Max History Remote alarm contacts 2 probes; 1 in air and 1 in sample bottle Alarm validation (audible, visual, and remote alarm) Alarm mute with ring back Three adjustable shelves (adjustable in ½" increments) Forced draft air circulation Keyed door lock One GFCI protected duplex electrical outlet Two 2" access ports with spring-loaded, self-closing gasketed metal covers Magnetic door gasket for positive seal Heavy duty door handle LED interior lights are safety shielded and switch controlled Swivel Casters (3 ½") Probe access port (3/4") Advanced hydrocarbon detector White powder-coated steel interior and exterior High density urethane foam cabinet insulation Hydrocarbon, natural refrigerant (R290) Two year parts and labor warranty, plus an additional three compressor parts warranty Exterior dimensions: 26 1/2" W* x 29 3/4" D x 79" H with casters; 75 ½" H without casters. *Width w/access ports closed; 34 1/2" width w/access ports open Cycle defrost 115V, 60 Hz, 3 Amps, 1/5 HP ETL listed Shipping weight: 283 lbs. Note: This unit requires two (2) outlets
E	