

Save time by using the stopper bowl cover instead of wrapping with sheets of material and autoclave tape. When used in conjunction with a secondary Tyvek® Bag, it creates an effective wrapping system. After the outer bag is removed, this stopper bowl cover should remain in place, providing protection from microbial and particulate contamination while the remaining set-up activities are performed.

TYPICAL APPLICATION & CHARACTERISTICS:

- Steam sterilization indicator
- Lint-free
- Autoclavable at 121°C 125°C
- Hydrophobic
- Resists tearing and punctures
- Manufactured and packaged in ISO certified Cleanroom
- Conveniently packaged: 1 per heat-sealed labeled poly bag
- Certificates of Conformance sent with shipment
- Made in USA



TYVEK® STOPPER BOWL COVERS



MATERIAL SPECIFICATIONS:

PROPERTY	UNITS	TEST METHOD	TYPICAL VALUES 1422A TYVEK®
Basis Weight	g/m2	EN ISO 536	41
Total Thickness	μ	EN 20534	130
Air Permeability	S	ISO 5636-5	20
Water Vapor Permeability	G/M2/24 HR	ASTM 398	1700
Hydrostatic Head	cm H20	ISO 811	120
Trapezoidal Tear MD/CD	N	ISO 9073-4	26.1/30.6
Linting Propensity	Rating	BS 6909 (Shirley Method 21)	Pass Rating: Excellent
Burst Resistance	kPa	ISO 2960 (50 cm2)	108
Puncture Resistance	N	EN 863	10.8
Melting Point	C°		135

KEYSTONE PART NUMBER	SIZE CHART	
BWLT2A20	Fits 11" to 16" Diameter	
BWLT2A24	Fits 12" to 20" Diameter	
BWLT2A26	Fits 14" to 22" Diameter	
BWLT2A30	Fits 20" to 26" Diameter	
BWLT2A36	Fits 26" to 30" Diameter	
BWLT2A42	Fits 28" to 35" Diameter	
BWLT2A46	Fits 30" to 38" Diameter	
BWLT2A48	Fits 30" to 40" Diameter	
BWLT2A54	Fits 35" to 45" Diameter	
BWLT2A60	Fits 40" to 50" Diameter	
BWLT2A72	Fits 50" to 60" Diameter	

