

Product Name:	ABT-HC-CP-69
Description:	<p>Premier Glass Door Chromatography Refrigerator  69 Cu. Ft. capacity  Three sliding glass doors, self-closing (energy efficient, double pane vacuum insulated)  Microprocessor Temperature Controller  Adjustable operating temperature range: 1°-10°C  Digital Temperature Display and Alarm Module  Sample simulated digital temperature display; .1° Resolution  Adjustable temperature display in Celsius or Fahrenheit  Audible and visual high/low temperature alarms  2 probes; 1 in air and 1 in sample bottle  Sensor error alarm; Power failure alarm  Resettable 1-point Min/Max History  Remote alarm contacts  Alarm validation (audible, visual, and remote alarm)  Alarm mute with ring back  Twelve adjustable shelves (adjustable in ½" increments)  Forced draft air circulation  Keyed door lock  One GFCI protected duplex electrical outlet  Two 2" access ports with spring-loaded, self-closing gasketed metal covers  Magnetic door gasket for positive seal  Integrated door handles  LED interior lights are safety shielded and switch controlled  Swivel casters (3 ½")  Probe access port (3/4")  Advanced hydrocarbon detector  White powder-coated steel exterior and interior  High density urethane foam cabinet insulation  Hydrocarbon, natural refrigerant (R290)  Two year parts and labor warranty, plus an additional three year compressor parts warranty  Exterior dimensions: 82 1/2" W* x 33 1/4" D x 78 1/4" H without casters; 81 3/4" H with casters. *Width w/access ports closed; 90 1/2" width w/access ports open  Cycle defrost  115V, 60 Hz, 7.5 Amps, 1/2 HP  ETL listed  Shipping weight: 738 lbs. Note: This unit requires two (2) outlets</p>