


One Click® Water Determination Simple and Secure



One Click® User Interface

The large color touchscreen features the simple-to-understand and fast-to-operate One Click user interface. All users have their own homescreen with dedicated shortcut buttons to directly start specific routine tasks.




Solvent Manager

Users are protected against contact with chemicals using the Solvent Manager liquid handling device. It is fully controlled by the titrator and offers solvent exchange with only One Click without additional user interaction.



Intelligent Burettes

The titrant is automatically recognized, when the burette is installed on the titrator. Important data such as concentration or lifetime is saved on the RFID chip and directly transferred to the titrator, where it is stored and can be monitored. Using the wrong or an expired titrant is therefore impossible.



PC software LabX® Titration

Full control over the titrator, secure database archiving, networking, efficient result management with control charts and individual search filters or rapid and clear method development are only some aspects of the powerful LabX titration PC software.



V20S Compact Volumetric KF Titrator

The routine Karl Fischer titrator combines fast and precise water content determination with easy operation. Samples from any industry with water content between 100 ppm and 100% are analyzed in single measurements or sample series with statistics.

- Color touchscreen with One Click user interface
- User interface in English, German, French, Spanish, Italian, Chinese, Russian, Polish, Korean and Portuguese
- Intelligent burettes with RFID chip saving all relevant titrant data
- Connectivity to LabX Titration PC software via USB or direct Ethernet (TCP/IP)
- Common USB printers or the USB-P25 compact printer for secure and GLP-compliant paper recording

Functionality Overview		V20S
Application	Solid, liquid and gaseous samples	•
	Resources and method database	•
	KF titrants	100
	KF standards	50
One Click® Titration	User specific Home Screen with Shortcuts	•
	Shortcuts per user	12
	Solvent Control	-
Hot Plug & Play	Solvent Manager	•
	Burette recognition with titrant, concentration and monitoring data	•
	External Dosing Unit for addition of auxiliary reagents	-
	USB printer DIN-A4/US letter / USB-P25 compact printer	•
	USB memory stick / USB barcode reader	•
Security	LevelSens	-
	LogStraight Fingerprint Reader	-
Automation	Stromboli oven sample changer	-
User Management	Expert – Routine	-
	Preprogrammed METTLER TOLEDO methods	-
	KF standard methods	4
	Max. number of user methods	5
	External extraction/dissolution dedicated method type	-
	Number of method function	12
	Number of samples per series	120
	Autostart: automatic start after sample addition	•
	Drift stop for endpoint recognition (absolute and relative, tmax, delay)	•
	Max. number of calculations/results per method	3
	User defined calculations	-
	Statistics of up to 120 samples including result limits check, outlier test	•
	Extra statistical functions as max. srel and multiple determinations	-
	Recalculation of results	•
	Data in Online Screen: time, water count, potential, stirrer speed, volume, drift	•
Data in measured value table: time, water count, potential, volume, drift	•	
Curves in Online Screen and printout: E-V, E-t, V-t, drift-t, water count-t	•	
Task list	Number of tasks queued	-
Online Help	Context sensitive parameter explanation	•
Data Export	USB, Ethernet, PDF	•
Languages	User interface and printouts in English, German, French, Spanish, Italian, Chinese, Russian, Polish, Korean, Portuguese	•
PC software	LabX® Titration Express and Server	•
Homogenizer	TTL	-
	Ethernet (TCP/IP)	1
	COM (serial balance connection)	1
	USB host (printer, memory stick, barcode reader, hub)	2
	USB client (PC)	1
Communication	Integrated Magnetic Stirrer	1
	Pump / Stirrer	1

- exclusive V30S functionality

Technical Specifications

Polarized sensor input	Measurement range	-2000...+2000 mV
	Resolution / Limits of error	0.1 mV / 2 mV
	Polarization current range	0...24 µA
	Polarization current resolution / Limits of error	0.1 µA / 1 µA
Burette drive	Drive resolution	20 000 steps
	Burette resolution (for 5 mL burette)	0.25 µL
	Limits of error	0.3% of the respective volume
	Resolver	32 pulses / mm stroke
	Resolver resolution	0.0625% of burette volume
	Filling time and discharge time	20 s at 100% filling rate
Environment	Ambient temperature	+5...+40 °C
	Atmospheric humidity	max. 80% at 31 °C
Titration dimensions	Width x depth x height / Weight	210 x 333 x 320 mm / 4.2 kg
	Glass beaker	150 mL
Control and display	Touchscreen	VGA 5.7" color TFT, 640 x 480 pixel
Application (depends on the environment and handling)	Drift measurement	Online, < 5 µg/min
	Measurement range	100 ppm...100%
	Repeatability	0.3% at >10 mg H ₂ O



Mettler-Toledo GmbH, Analytical
 CH-8603 Schwerzenbach, Switzerland
 Tel. +41 44 806 77 11
 Fax +41 44 806 72 40

Subject to technical changes
 © 03/2016 Mettler-Toledo GmbH
 Printed in Switzerland 30265532A
 Marketing Titration / Global MarCom Switzerland, 1688 PH

www.mt.com/titration

For more information

One Click is a Registered Trademark of METTLER TOLEDO in Switzerland, the European Union, Russia and Singapore.
 LabX is a Registered Trademark of METTLER TOLEDO in Switzerland, USA, China, Germany and a further 13 countries.