

## Grade 121

## Characteristics:

Binder-free microfiber glass

Physical Property	Standard Units		Metric Units	
Basis Weight	lbs/1389ft <sup>2</sup>	41.0	gsm	143.9
Basis Weight	oz/yd²	4.25		
Thickness	mils	26.0	mm	0.6604
Rapidity			mls/min	48.0
Frazier Permeability	cfm/ft²	2.3	L/m²/sec	18.4
Tensile Strength MDT Dry	lb/in	4.5	N/m	788
Tensile Strength CDT	lb/in		N/m	
Retention	micron	1.0		
Wet Burst	in	18.0	cm	45.7

Micron ratings are based on an Ahlstrom test method where 98% of a particulate size is removed during gravitational filtration. Micron rating values vary between industries and manufacturers depending on the test procedure.

## Contact office:

Ahlstrom Filtration LLC Mount Holly Springs 122 West Butler Street Mt Holly Springs, PA 17065 T: +1 717 486 3438 F: +1 717 486 6413

## www.ahlstrom.com

DISCLAIMER: The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed, including without limitation any warranty of merchantability and fitness for use. All users of the material are responsible for assuring that it is suitable for their needs, environment and end use. All data is subject to change as Ahlstrom deems appropriate. Refer to www.ahlstrom.com for contact information.