

# MICROBIOLOGY QC PRODUCTS

For reliable test results that ensure effective product quality monitoring

**Pall Laboratory** high-performance membranes, filter funnels, manifolds, pumps, accessories and **environmental filters & shakers** are designed for simple operation, ease-of-analysis, and reduced contamination risk to produce reliable test results.

Sentino Dispensers, Pumps & Filter Funnels

Single-Use Filter Funnels

Reusable Filter Funnels

Filter Funnel Membranes

Laboratory Manifold

Ampoule Broths, Petri Dishes, Accessories





# HIGHLIGHTS

Experience our innovation

**We've expanded our MicroFunnel™ ST and Plus filter funnel offerings:** New larger volume, membrane and ST dual-layer packaging choices of the MicroFunnel Plus filter funnels are now available. Specifically designed for water testing with an integrated sample cup and filter funnel all-in-one.


MicroFunnel ST Filter Funnel Information Sheet >

MicroFunnel Filter Funnel Catalog >

Pharmaceutical Applications >



## NEW RESOURCES



BROCHURE

### PALL LABORATORY MANIFOLD

All you need to know about how Pall's manifold optimizes testing without sacrificing cleanliness. Includes new product selector to help choose the correct adapter and filter funnel.

Download >



WEBINAR

### CUT THE COST OF CONTAMINATION

Cross-contamination during testing can result in false positives requiring costly retests and delaying your products from reaching the market. This webinar will cover topics to help labs prevent contamination while also saving money.

Watch Now >



APPLICATION NOTE

### REDUCING RSI AND IMPROVING ERGONOMICS IN MICROBIOLOGICAL QUALITY CONTROL PROCEDURES

Performing the same motion over and over, such as in QC testing, can result in repetitive stress injury (RSI). Read about how Pall products are designed for ergonomic use.

Download >



# PRODUCT CATALOG

Meet our high-performance  
Microbiology QC product line:



**Single-Use Filter  
Funnels**

Learn More >



**Sentino® Dispensers,  
Pumps & Filter Funnels**

Learn More >



**Laboratory Manifold**

Learn More >



**Reusable Filter  
Funnels**

Learn More >



**Filter Funnel  
Membranes**

Learn More >



**Ampoule Broths, Petri  
Dishes, Accessories**

Learn More >



**Environmental Water  
Filters & Shakers**

Learn More >



**Download Full  
Product Lists and  
Specifications**



# MICROFUNNEL™ AND MICROCHECK® FILTER FUNNELS

Single-use filter funnels for  
a range of microbiology  
applications



Full Product List  
and Specifications

### Superior Design

Easy squeeze removal of funnel top reduces risk of repetitive stress injury (RSI). Details such as volume graduations molded on the outside of the funnel to reduce sample loss and potential false negative results.

### Single Use

Individually bagged and gamma irradiated means no need for cleaning and sterilizing prior to use, with no chance for cross contamination.

### GLP Compliance

Each lot QC tested and certified, with certificates available on-line. Individually labeled packaging eases documentation needs and +/-2% accuracy at the maximum volumes enables compliance with applicable requirements.

### Available with Polycarbonate Membrane

Flat, smooth surface provides easy elution of organisms or particulate for further analysis.



### MicroFunnel Plus Filter Funnels

Options include Supor® membrane compatible with hot water loops up to 90° C and sample cup holder for safe operation. Combines standard MicroFunnel filter funnel features with a filter funnel and sample cup in a semi-closed system to reduce contamination during in-line sampling and transport.

### MicroFunnel ST Filter Funnels

ST second packaging layer requires only one wipe down to transfer multiple filter funnels when processed in cleanrooms or hoods. The overpack layer reduces gross particulate contamination that can come from cardboard.

### MicroCheck Filter Funnels

Disposable Microcheck filter funnel is specifically designed for beverage microbial analysis, including integrated petri dish. Easy-to-use filter funnel is ideal for ingredient or final product testing for microbial contamination prior to release.

## PRODUCT CATALOG

- ▶ **Single-Use Filter Funnels**
- Sentino® Dispensers/Pumps**
- Laboratory Manifold**
- Reusable Filter Funnels**
- Filter Funnel Membranes**
- Ampoule Broths/Petri Dishes/Accessories**
- Environmental Filters/Shakers**

## APPLICATIONS

### General Microbial Testing

For aqueous fluids used in pharmaceutical production and water system monitoring. Check for a variety of contaminants such as total coliforms or *pseudomonas*.

### Bioburden Testing

Prior to sterilization for confirmation that microbial load is not above expected and validated quantities.

### Sterility Testing

To confirm sterility where no more than 1 sample in 1 million contain microbial activity.

# MICROFUNNEL™ AND MICROCHECK® FILTER FUNNELS

Ordering information and specifications



CLOSE

- 1
- 2
- 3
- 4
- 5
- 6
- 7

## 100 ML STANDARD, INCLUDING OVERPACK OPTIONS (ST)

ORDERING INFORMATION			DIMENSIONS AND WEIGHT*			OTHER SPECIFICATIONS					
Thomas #	Description	Pkg	Height	Diameter	Outlet	Capacity	Pore Size	Color	Effective Filtration Area	Max Sample Collection Temp	Cleaning and Sterilization
20A00U094	0.45 µm GN-6 white gridded membrane, individually bagged, gamma irradiated	50/pkg	With cover: 7.6 cm (3.0 in) Without cover: 7.3 cm (2.9 in)	With cover: 6.1 cm (2.4 in) Without cover: 5.7 cm (2.3 in)	Fits MicroFunnel adapters	100 mL	0.45 µm	Membrane: white with black grid Funnel: translucent colorless	13.46 cm <sup>2</sup>	N/A	Gamma irradiated at validated dose of 15 - 30 kGy
20A00U095	0.45 µm GN-6 white gridded membrane, bulk, gamma irradiated	50/pkg	With cover: 7.6 cm (3.0 in) Without cover: 7.3 cm (2.9 in)	With cover: 6.1 cm (2.4 in) Without cover: 5.7 cm (2.3 in)	Fits MicroFunnel adapters	100 mL	0.45 µm	Membrane: white with black grid Funnel: translucent colorless	13.46 cm <sup>2</sup>	N/A	Gamma irradiated at validated dose of 15 - 30 kGy
20A00U097	0.45 µm GN-6 white gridded membrane, individually bagged, gamma irradiated	200/pkg	With cover: 7.6 cm (3.0 in) Without cover: 7.3 cm (2.9 in)	With cover: 6.1 cm (2.4 in) Without cover: 5.7 cm (2.3 in)	Fits MicroFunnel adapters	100 mL	0.45 µm	Membrane: white with black grid Funnel: translucent colorless	13.46 cm <sup>2</sup>	N/A	Gamma irradiated at validated dose of 15 - 30 kGy
20A00U104	0.45 µm GN-6 white gridded membrane, individually bagged with ST overpack, gamma irradiated	40/pkg*	With cover: 7.6 cm (3.0 in) Without cover: 7.3 cm (2.9 in)	With cover: 6.1 cm (2.4 in) Without cover: 5.7 cm (2.3 in)	Fits MicroFunnel adapters	100 mL	0.45 µm	Membrane: white with black grid Funnel: translucent colorless	13.46 cm <sup>2</sup>	N/A	Gamma irradiated at validated dose of 15 - 30 kGy
20A00U096	0.2 µm Supor white gridded membrane, individually bagged, gamma irradiated	50/pkg	With cover: 7.6 cm (3.0 in) Without cover: 7.3 cm (2.9 in)	With cover: 6.1 cm (2.4 in) Without cover: 5.7 cm (2.3 in)	Fits MicroFunnel adapters	100 mL	0.2 µm	Membrane: white with black grid Funnel: translucent colorless	13.46 cm <sup>2</sup>	N/A	Gamma irradiated at validated dose of 15 - 30 kGy
20A00U115	0.45 µm Supor white gridded membrane, individually bagged, gamma irradiated	50/pkg	With cover: 7.6 cm (3.0 in) Without cover: 7.3 cm (2.9 in)	With cover: 6.1 cm (2.4 in) Without cover: 5.7 cm (2.3 in)	Fits MicroFunnel adapters	100 mL	0.45 µm	Membrane: white with black grid Funnel: translucent colorless	13.46 cm <sup>2</sup>	N/A	Gamma irradiated at validated dose of 15 - 30 kGy
20A00U099	0.2 µm Supor white ungridded membrane, individually bagged, gamma irradiated	50/pkg	With cover: 7.6 cm (3.0 in.) Without cover: 7.3 cm (2.9 in)	With cover: 6.1 cm (2.4 in) Without cover: 5.7 cm (2.3 in)	Fits MicroFunnel adapters	100 mL	0.2 µm	Membrane: white Funnel: translucent colorless	13.46 cm <sup>2</sup>	N/A	Gamma irradiated at validated dose of 15 - 30 kGy
21A00A839	0.2 µm Supor white gridded membrane, individually bagged with ST overpack, gamma irradiated	40/pkg*	With cover: 7.6 cm (3.0 in.) Without cover: 7.3 cm (2.9 in)	With cover: 6.1 cm (2.4 in) Without cover: 5.7 cm (2.3 in)	Fits MicroFunnel adapters	100 mL	0.2 µm	Membrane: white with black grid Funnel: translucent colorless	13.46 cm <sup>2</sup>	N/A	Gamma irradiated at validated dose of 15 - 30 kGy
20A00U092	0.45 µm Supor white ungridded membrane, individually bagged with ST overpack, gamma irradiated	40/pkg*	With cover: 7.6 cm (3.0 in) Without cover: 7.3 cm (2.9 in)	With cover: 6.1 cm (2.4 in) Without cover: 5.7 cm (2.3 in)	Fits MicroFunnel adapters	100 mL	0.45 µm	Membrane: white Funnel: translucent colorless	13.46 cm <sup>2</sup>	N/A	Gamma irradiated at validated dose of 15 - 30 kGy
20A00U098	0.45 µm MetriceI black gridded membrane, individually bagged, gamma irradiated	50/pkg	With cover: 7.6 cm (3.0 in) Without cover: 7.3 cm (2.9 in)	With cover: 6.1 cm (2.4 in) Without cover: 5.7 cm (2.3 in)	Fits MicroFunnel adapters	100 mL	0.45 µm	Membrane: black with white grid Funnel: translucent colorless	13.46 cm <sup>2</sup>	N/A	Gamma irradiated at validated dose of 15 - 30 kGy

\*100 mL funnels (40 units total per box): 10 individually bagged funnels within an overpack bag, 4 overpack bags per box.

# MICROFUNNEL™ AND MICROCHECK® FILTER FUNNELS

Ordering information and specifications



CLOSE

- 1
- 2
- 3
- 4
- 5
- 6
- 7

## 100 ML WITH LID KIT

ORDERING INFORMATION			DIMENSIONS AND WEIGHT*			OTHER SPECIFICATIONS					
Thomas #	Description	Pkg	Height	Diameter	Outlet	Capacity	Pore Size	Color	Effecive Filtration Area	Max Sample Collection Temp	Cleaning and Sterilization
20A00U103	0.45 µm GN-6 white gridded membrane, individually bagged, gamma irradiated	50/pkg	With lid kit: 8.1 cm (3.2 in) Without lid kit: 7.6 cm (3.0 in)	With lid kit: 6.4 cm (2.5 in) Without lid kit: 6.1 cm (2.4 in)	Fits MicroFunnel adapters	100 mL	0.45 µm	Membrane: white with black grid Funnel: translucent colorless	13.46 cm <sup>2</sup>	N/A	Gamma irradiated at validated dose of 15 - 30 kGy

\*100 mL funnels (40 units total per box): 10 individually bagged funnels within an overpack bag, 4 overpack bags per box.

# MICROFUNNEL™ AND MICROCHECK® FILTER FUNNELS

Ordering information and specifications



CLOSE

- 1
- 2
- 3
- 4
- 5
- 6
- 7

## 100 ML PLUS, INCLUDING ASCEPTIC PORT OPTION (AP)

ORDERING INFORMATION			DIMENSIONS AND WEIGHT*			OTHER SPECIFICATIONS					
Thomas #	Description	Pkg	Height	Diameter	Outlet	Capacity	Pore Size	Color	Effective Filtration Area	Max Sample Collection Temp	Cleaning and Sterilization
20A00U100	0.45 µm GN-6 white gridded membrane, individually bagged, gamma irradiated	50/pkg	With cover: 7.6 cm (3.0 in) Without cover: 7.3 cm (2.9 in)	With cover: 6.1 cm (2.4 in) Without cover: 5.7 cm (2.3 in)	Fits MicroFunnel adapters	100 mL	0.45 µm	Membrane: white with black grid Funnel: translucent colorless	13.46 cm <sup>2</sup>	74 °C (165 °F)	Gamma irradiated at validated dose of 15 - 30 kGy
COMING SOON 4856	0.45 µm GN-6 white gridded membrane, bulk, gamma irradiated	50/pkg	With cover: 8.7 cm (3.4 in) Without cover: 7.3 cm (2.9 in)	With cover: 6.1 cm (2.4 in) Without cover: 5.7 cm (2.3 in)	Fits MicroFunnel adapters	300 mL	0.45 µm	Membrane: white with black grid Funnel: translucent colorless	13.46 cm <sup>2</sup>	74 °C (165 °F)	Gamma irradiated at validated dose of 15 - 30 kGy
20A00U102	0.2 µm Supor white gridded membrane, individually bagged, gamma irradiated	50/pkg	With cover: 7.6 cm (3.0 in) Without cover: 7.3 cm (2.9 in)	With cover: 6.1 cm (2.4 in) Without cover: 5.7 cm (2.3 in)	Fits MicroFunnel adapters	100 mL	0.2 µm	Membrane: white with black grid Funnel: translucent colorless	13.46 cm <sup>2</sup>	90 °C (194 °F)	Gamma irradiated at validated dose of 15 - 30 kGy
20A00U111	0.45 µm Supor white gridded membrane, individually bagged, gamma irradiated	50/pkg	With cover: 7.6 cm (3.0 in) Without cover: 7.3 cm (2.9 in)	With cover: 6.1 cm (2.4 in) Without cover: 5.7 cm (2.3 in)	Fits MicroFunnel adapters	100 mL	0.45 µm	Membrane: white with black grid Funnel: translucent colorless	13.46 cm <sup>2</sup>	90 °C (194 °F)	Gamma irradiated at validated dose of 15 - 30 kGy
20A00U118	0.45 µm Supor white gridded membrane, individually bagged with ST overpack, gamma irradiated	40/pkg*	With cover: 7.6 cm (3.0 in) Without cover: 7.3 cm (2.9 in)	With cover: 6.1 cm (2.4 in) Without cover: 5.7 cm (2.3 in)	Fits MicroFunnel adapters	100 mL	0.45 µm	Membrane: white with black grid Funnel: translucent colorless	13.46 cm <sup>2</sup>	90 °C (194 °F)	Gamma irradiated at validated dose of 15 - 30 kGy
20A00U101	0.45 µm Metrical black gridded membrane, individually bagged, gamma irradiated	50/pkg	With cover: 7.6 cm (3.0 in) Without cover: 7.3 cm (2.9 in)	With cover: 6.1 cm (2.4 in) Without cover: 5.7 cm (2.3 in)	Fits MicroFunnel adapters	100 mL	0.45 µm	Membrane: black with white grid Funnel: translucent colorless	13.46 cm <sup>2</sup>	N/A	Gamma irradiated at validated dose of 15 - 30 kGy
COMING SOON 4843	0.2 µm Supor white gridded membrane, individually bagged, gamma irradiated, with aseptic port	50/pkg	With cover: 8.7 cm (3.4 in) Without cover: 7.3 cm (2.9 in)	With cover: 6.1 cm (2.4 in) Without cover: 5.7 cm (2.3 in)	Fits MicroFunnel adapters	100 mL	0.2 µm	Membrane: white with black grid Funnel: translucent colorless	13.46 cm <sup>2</sup>	90 °C (194 °F)	Gamma irradiated at validated dose of 15 - 30 kGy
20A00U114	0.45 µm Supor white gridded membrane, individually bagged, gamma irradiated, with aseptic port	50/pkg	With cover: 8.7 cm (3.4 in) Without cover: 7.3 cm (2.9 in)	With cover: 6.1 cm (2.4 in) Without cover: 5.7 cm (2.3 in)	Fits MicroFunnel adapters	100 mL	0.45 µm	Membrane: white with black grid Funnel: translucent colorless	13.46 cm <sup>2</sup>	90 °C (194 °F)	Gamma irradiated at validated dose of 15 - 30 kGy

\*100 mL funnels (40 units total per box): 10 individually bagged funnels within an overpack bag, 4 overpack bags per box.



# MICROFUNNEL™ AND MICROCHECK® FILTER FUNNELS

Ordering information and specifications



CLOSE

- 1
- 2
- 3
- 4
- 5
- 6
- 7

## 100 ML MICROCHECK WITH LID KIT

ORDERING INFORMATION			DIMENSIONS AND WEIGHT*			OTHER SPECIFICATIONS					
Thomas #	Description	Pkg	Height	Diameter	Outlet	Capacity	Pore Size	Color	Effecive Filtration Area	Max Sample Collection Temp	Cleaning and Sterilization
21A00A830	0.45 µm GN-6 white gridded membrane, bulk packed, gamma irradiated	50/pkg	With lid kit: 8.1 cm (3.2 in) Without lid kit: 7.6 cm (3.0 in)	With lid kit: 6.4 cm (2.5 in) Without lid kit: 6.1 cm (2.4 in)	Fits MicroFunnel adapters	100 mL	0.45 µm	Membrane: white with black grid Funnel: translucent blue	13.46 cm <sup>2</sup>	N/A	Gamma irradiated at validated dose of 15 - 30 kGy
21A00A831	0.8 µm GN-6 white gridded membrane, bulk packed, gamma irradiated	50/pkg	With lid kit: 8.1 cm (3.2 in) Without lid kit: 7.6 cm (3.0 in)	With lid kit: 6.4 cm (2.5 in) Without lid kit: 6.1 cm (2.4 in)	Fits MicroFunnel adapters	100 mL	0.8 µm	Membrane: white with black grid Funnel: translucent blue	13.46 cm <sup>2</sup>	N/A	Gamma irradiated at validated dose of 15 - 30 kGy
21A00A832	0.45 µm Metrical black gridded membrane, bulk packed, gamma irradiated	50/pkg	With lid kit: 8.1 cm (3.2 in) Without lid kit: 7.6 cm (3.0 in)	With lid kit: 6.4 cm (2.5 in) Without lid kit: 6.1 cm (2.4 in)	Fits MicroFunnel adapters	100 mL	0.45 µm	Membrane: black with white grid Funnel: translucent blue	13.46 cm <sup>2</sup>	N/A	Gamma irradiated at validated dose of 15 - 30 kGy
21A00A833	0.8 µm Metrical black gridded membrane, bulk packed, gamma irradiated	50/pkg	With lid kit: 8.1 cm (3.2 in) Without lid kit: 7.6 cm (3.0 in)	With lid kit: 6.4 cm (2.5 in) Without lid kit: 6.1 cm (2.4 in)	Fits MicroFunnel adapters	100 mL	0.8 µm	Membrane: black with white grid Funnel: translucent blue	13.46 cm <sup>2</sup>	N/A	Gamma irradiated at validated dose of 15 - 30 kGy

## 100 mL Polycarbonate

Ordering Information			Dimensions and Weight*			Other Specifications					
Thomas #	Description	Pkg	Height	Diameter	Outlet	Capacity	Pore Size	Color	Effecive Filtration Area	Max Sample Collection Temp	Cleaning and Sterilization
20A00U119	0.4 µm polycarbonate white ungridded membrane, individually bagged, gamma irradiated	50/pkg	With cover: 7.6 cm (3.0 in) Without cover: 7.3 cm (2.9 in)	With cover: 6.1 cm (2.4 in) Without cover: 5.7 cm (2.3 in)	Fits MicroFunnel adapters	100 mL	0.4 µm	Membrane: white Funnel: translucent colorless	13.46 cm <sup>2</sup>	N/A	Gamma irradiated at validated dose of 15 - 30 kGy

\*100 mL funnels (40 units total per box): 10 individually bagged funnels within an overpack bag, 4 overpack bags per box.



# MICROFUNNEL™ AND MICROCHECK® FILTER FUNNELS

Ordering information and specifications



CLOSE

- 1
- 2
- 3
- 4
- 5
- 6
- 7

## 300 ML STANDARD, INCLUDING OVERPACK OPTIONS (ST)

ORDERING INFORMATION			DIMENSIONS AND WEIGHT*			OTHER SPECIFICATIONS					
Thomas #	Description	Pkg	Height	Diameter	Outlet	Capacity	Pore Size	Color	Effective Filtration Area	Max Sample Collection Temp	Cleaning and Sterilization
20A00U107	0.45 µm GN-6 white gridded membrane, individually bagged, gamma irradiated	20/pkg	With cover: 9.1 cm (3.6 in) Without cover: 8.9 cm (3.5 in)	With cover: 8.8 cm (3.5 in) Without cover: 8.4 cm (3.4 in)	Fits MicroFunnel adapters	300 mL	0.45 µm	Membrane: white with black grid Funnel: translucent colorless	13.46 cm <sup>2</sup>	74 °C (165 °F)	Gamma irradiated at validated dose of 15 - 30 kGy
20A00U105	0.45 µm GN-6 white gridded membrane, individually bagged with ST overpack, gamma irradiated	20/pkg*	With cover: 9.1 cm (3.6 in) Without cover: 8.9 cm (3.5 in)	With cover: 8.8 cm (3.5 in) Without cover: 8.4 cm (3.4 in)	Fits MicroFunnel adapters	300 mL	0.45 µm	Membrane: white with black grid Funnel: translucent colorless	13.46 cm <sup>2</sup>	74 °C (165 °F)	Gamma irradiated at validated dose of 15 - 30 kGy
20A00U109	0.2 µm Supor white gridded membrane, individually bagged, gamma irradiated	20/pkg	With cover: 9.1 cm (3.6 in) Without cover: 8.9 cm (3.5 in)	With cover: 8.8 cm (3.5 in) Without cover: 8.4 cm (3.4 in)	Fits MicroFunnel adapters	300 mL	0.2 µm	Membrane: white with black grid Funnel: translucent colorless	13.46 cm <sup>2</sup>	100 °C (212 °F)	Gamma irradiated at validated dose of 15 - 30 kGy
20A00U116	0.2 µm Supor white gridded membrane, individually bagged with ST overpack, gamma irradiated	20/pkg*	With cover: 9.1 cm (3.6 in) Without cover: 8.9 cm (3.5 in)	With cover: 8.8 cm (3.5 in) Without cover: 8.4 cm (3.4 in)	Fits MicroFunnel adapters	300 mL	0.2 µm	Membrane: white with black grid Funnel: translucent colorless	13.46 cm <sup>2</sup>	100 °C (212 °F)	Gamma irradiated at validated dose of 15 - 30 kGy
20A00U112	0.45 µm Supor white ungridded membrane, individually bagged, gamma irradiated	20/pkg	With cover: 9.1 cm (3.6 in) Without cover: 8.9 cm (3.5 in)	With cover: 8.8 cm (3.5 in) Without cover: 8.4 cm (3.4 in)	Fits MicroFunnel adapters	300 mL	0.45 µm	Membrane: white with black grid Funnel: translucent colorless	13.46 cm <sup>2</sup>	100 °C (212 °F)	Gamma irradiated at validated dose of 15 - 30 kGy
20A00U093	0.45 µm Supor white ungridded membrane, individually bagged with ST overpack, gamma irradiated	20/pkg*	With cover: 9.1 cm (3.6 in) Without cover: 8.9 cm (3.5 in)	With cover: 8.8 cm (3.5 in) Without cover: 8.4 cm (3.4 in)	Fits MicroFunnel adapters	300 mL	0.45 µm	Membrane: white Funnel: translucent colorless	13.46 cm <sup>2</sup>	100 °C (212 °F)	Gamma irradiated at validated dose of 15 - 30 kGy
20A00U108	0.45 µm MetriceL black gridded membrane, individually bagged, gamma irradiated	20/pkg	With cover: 9.1 cm (3.6 in) Without cover: 8.9 cm (3.5 in)	With cover: 8.8 cm (3.5 in) Without cover: 8.4 cm (3.4 in)	Fits MicroFunnel adapters	301 mL	0.45 µm	Membrane: black with white grid Funnel: translucent colorless	13.46 cm <sup>2</sup>	N/A	Gamma irradiated at validated dose of 15 - 30 kGy
20A00U110	0.8 µm MetriceL black gridded membrane, individually bagged, gamma irradiated	20/pkg	With cover: 9.1 cm (3.6 in) Without cover: 8.9 cm (3.5 in)	With cover: 8.8 cm (3.5 in) Without cover: 8.4 cm (3.4 in)	Fits MicroFunnel adapters	300 mL	0.8 µm	Membrane: black with white grid Funnel: translucent colorless	13.46 cm <sup>2</sup>	N/A	Gamma irradiated at validated dose of 15 - 30 kGy

\* 300 mL funnels (20 units total per box): 5 individually bagged funnels within an overpack bag, 4 overpack bags per box.

# MICROFUNNEL™ AND MICROCHECK® FILTER FUNNELS

Ordering information and specifications



CLOSE

- 1
- 2
- 3
- 4
- 5
- 6
- 7

## 300 ML PLUS, INCLUDING ASCEPTIC PORT OPTIONS (AP) AND OVERPACK OPTIONS (ST)

ORDERING INFORMATION			DIMENSIONS AND WEIGHT*			OTHER SPECIFICATIONS					
Thomas #	Description	Pkg	Height	Diameter	Outlet	Capacity	Pore Size	Color	Effective Filtration Area	Max Sample Collection Temp	Cleaning and Sterilization
20A00U113	0.45 µm GN-6 white gridded membrane, individually bagged, gamma irradiated	20/pkg	With cover: 8.9 cm (3.5 in) Without cover: 8.6 cm (3.4 in)	With cover: 8.7 cm (3.4 in) Without cover: 8.3 cm (3.4 in)	Fits MicroFunnel adapters	300 mL	0.45 µm	Membrane: white with black grid Funnel: translucent colorless	13.46 cm <sup>2</sup>	74 °C (165 °F)	Gamma irradiated at validated dose of 15 - 30 kGy
COMING SOON 4813	0.2 µm Supor white gridded membrane, individually bagged, gamma irradiated	20/pkg	With cover: 8.9 cm (3.5 in) Without cover: 8.6 cm (3.4 in)	With cover: 8.7 cm (3.4 in) Without cover: 8.3 cm (3.4 in)	Fits MicroFunnel adapters	300 mL	0.2 µm	Membrane: white with black grid Funnel: translucent colorless	13.46 cm <sup>2</sup>	90 °C (194 °F)	Gamma irradiated at validated dose of 15 - 30 kGy
20A00U117	0.2 µm Supor white gridded membrane, individually bagged with ST overpack, gamma irradiated	20/pkg*	With cover: 8.9 cm (3.5 in) Without cover: 8.6 cm (3.4 in)	With cover: 8.7 cm (3.4 in) Without cover: 8.3 cm (3.4 in)	Fits MicroFunnel adapters	300 mL	0.2 µm	Membrane: white with black grid Funnel: translucent colorless	13.46 cm <sup>2</sup>	90 °C (194 °F)	Gamma irradiated at validated dose of 15 - 30 kGy
20A00U106	0.45 µm Supor white gridded membrane, individually bagged, gamma irradiated	20/pkg	With cover: 8.9 cm (3.5 in) Without cover: 8.6 cm (3.4 in)	With cover: 8.7 cm (3.4 in) Without cover: 8.3 cm (3.4 in)	Fits MicroFunnel adapters	300 mL	0.45 µm	Membrane: white with black grid Funnel: translucent colorless	13.46 cm <sup>2</sup>	90 °C (194 °F)	Gamma irradiated at validated dose of 15 - 30 kGy
21A00C063	0.45 µm Supor white gridded membrane, individually bagged with ST overpack, gamma irradiated	20/pkg*	With cover: 8.9 cm (3.5 in) Without cover: 8.6 cm (3.4 in)	With cover: 8.7 cm (3.4 in) Without cover: 8.3 cm (3.4 in)	Fits MicroFunnel adapters	300 mL	0.45 µm	Membrane: white with black grid Funnel: translucent colorless	13.46 cm <sup>2</sup>	90 °C (194 °F)	Gamma irradiated at validated dose of 15 - 30 kGy
COMING SOON 4855	0.45 µm Supor white gridded membrane, individually bagged, gamma irradiated with aseptic port	20/pkg	With cover: 9.8 cm (3.8 in) Without cover: 8.6 cm (3.4 in)	With cover: 8.7 cm (3.4 in) Without cover: 8.3 cm (3.4 in)	Fits MicroFunnel adapters	300 mL	0.45 µm	Membrane: white with black grid Funnel: translucent colorless	13.46 cm <sup>2</sup>	90 °C (194 °F)	Gamma irradiated at validated dose of 15 - 30 kGy

## 300 mL Polycarbonate

Ordering Information			Dimensions and Weight*			Other Specifications					
Thomas #	Description	Pkg	Height	Diameter	Outlet	Capacity	Pore Size	Color	Effective Filtration Area	Max Sample Collection Temp	Cleaning and Sterilization
20A00U120	0.4 µm polycarbonate white ungridded membrane, individually bagged, gamma irradiated	20/pkg	With cover: 9.1 cm (3.6 in) Without cover: 8.9 cm (3.5 in)	With cover: 8.8 cm (3.5 in) Without cover: 8.5 cm (3.4 in)	Fits MicroFunnel adapters	300 mL	0.4 µm	Membrane: white Funnel: translucent colorless	13.46 cm <sup>2</sup>	N/A	Gamma irradiated at validated dose of 15 - 30 kGy

\* 300 mL funnels (20 units total per box): 5 individually bagged funnels within an overpack bag, 4 overpack bags per box.



# MICROFUNNEL™ AND MICROCHECK® FILTER FUNNELS

Ordering information and specifications



CLOSE

- 1
- 2
- 3
- 4
- 5
- 6
- 7

## ACCESSORIES

ORDERING INFORMATION			DIMENSIONS AND WEIGHT*			OTHER SPECIFICATIONS					
Thomas #	Description	Pkg	Height	Diameter	Outlet	Capacity	Pore Size	Color	Effective Filtration Area	Max Sample Collection Temp	Cleaning and Sterilization
21A00A836	MicroFunnel Plus 100 mL filter funnel holder for hot water applications	1/pkg	N/A	N/A	N/A	100 mL	N/A	Black	N/A	N/A	N/A
21A00A837	MicroFunnel Plus 300 mL filter funnel holder for hot water applications	1/pkg	N/A	N/A	N/A	300 mL	N/A	Black	N/A	N/A	N/A
21A00A826	MicroFunnel filter funnel #8 stopper adapter	3/pkg	N/A	N/A	N/A	N/A	N/A	Black	N/A	N/A	Withstands multiple autoclavings* at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min
21A00A838	MicroFunnel Plus filter funnel AP sample tubing, individually bagged, gamma irradiated	50/pkg	N/A	N/A	N/A	N/A	N/A	Translucent colorless	N/A	N/A	Gamma irradiated at validated dose of 15 - 30 kGy
21A00A840	Culture-in-Place lid kit for 100 mL MicroFunnel filter funnels (lid, base plug), gamma irradiated	20/pkg	N/A	N/A	N/A	100 mL	N/A	Transparent colorless	N/A	N/A	Gamma irradiated at validated dose of 15 - 30 kGy
21A00C064	MicroFunnel filter funnel #8 stopper adapter, Gamma Irradiated	60/pkg (20 sets of 3 in overpack)	N/A	N/A	N/A	N/A	N/A	Blue	N/A	N/A	Gamma irradiated at validated dose of 15 - 30 kGy

\* 100 mL funnels (40 units total per box): 10 individually bagged funnels within an overpack bag, 4 overpack bags per box.

\*\* Actual number of autoclave cycles will depend upon application and use

# SENTINO® DISPENSERS, PUMPS AND FILTER FUNNELS

Maximize workspace and  
minimize contamination risk



Full Product List  
and Specifications

## PRODUCT CATALOG

Single-Use Filter Funnels

▶ Sentino® Dispensers/Pumps

Laboratory Manifold

Reusable Filter Funnels

Filter Funnel Membranes

Ampoule Broths/Petri Dishes/  
Accessories

Environmental Filters/Shakers

The Sentino system's compact, portable design frees valuable bench top space and its disposable fluid path and optional single-use filter funnels limit biofilm build up and contamination.

### Process Simplicity

The Sentino pump eliminates the need for separate manifold, pump, and excess tubing. Small, portable equipment is easy to bring to in-field sampling locations and designed to work together seamlessly.

### Single-Use Options

Our disposable Sentino pump fluid path, combined with the gamma-irradiated Sentino Filter Funnel option, virtually eliminates the risk of cross contamination from test equipment.

### Filter Funnel Flexibility

Available fluid path adapters include options compatible with Pall's Sentino filter funnels, all magnetic filter funnels, and MicroFunnel™ filter funnels, giving the freedom to use the appropriate validated methods.



### Sentino Pump and Dispenser

Compact footprints and portable design with battery operation option frees valuable bench space. Peristaltic pump action sends filtrate to waste collection, while our dispenser guide plates reduce jarring and neatly wind packaging onto spools for easy disposal.



### Sentino Membranes

200-pack membrane packaging requires less frequent loading, and includes two extra membranes for dispenser set-up. Visual indicator alerts when membrane is running low.



### Sentino Filter Funnels

Unique magnetic funnel design enables efficient membrane removal, and no-leak magnetic seals allow one-handed operation. Available disposable, gamma-irradiated filter funnel options offer single-use convenience.

## APPLICATIONS

### Limited Bench Space

Whether working under a hood or with limited space, the small footprints and low profile of Sentino products make them ideal for laboratories working with laminar flow hoods or minimal bench areas.

### In-Field Options

Some applications such as environmental water testing may require in-field or other remote sample processing. With its battery operation design and easy portability, the Sentino pump and dispenser are ideally designed for this specialized need.

### Last-Minute Testing

It can be frustrating to find a contaminated sample late in the day after your manifold has been cleaned, packaged, and sterilized for the next day's use. It's single-sample design, and disposable fluid path and filter funnel options, make the Sentino pump the perfect choice to run any last-minute samples, saving the time to re-clean and re-sterilize your manifold.





# SENTINO® DISPENSERS, PUMPS AND FILTER FUNNELS

Ordering information and specifications



CLOSE

- 1
- 2
- 3

## DISPENSER AND MEMBRANES

ORDERING INFORMATION			DIMENSIONS AND WEIGHT					OTHER SPECIFICATIONS		
Thomas #	Description	Pkg	Height	DIAMETER / WIDTH / OD	Length	Weight	Outlet	OPERATION TEMP RANGE	POWER	CLEANING AND STERILIZATION
21A00A728	Sentino Z-pack membrane dispenser	1/pkg	20.0 cm (7.9 in)	12.0 cm (4.7 in)	22.0 cm (7.9 in)	0.9 kg (2.0 lbs)	N/A	15-30 °C (59-86 °F)	24 V DC, 1.6 Amp, 100-240 V AC47-63 Hz 12 V NIMH battery IEC 320 3-pin socket input 2.5 mm barrel jack output IEC 320 connector and NEMA 5-15P grounded plug, IEC 320 connector and European CEE 7/7 plug, IEC 320 connector and UK BS1363 plug	Consult user instructions
21A00A730	0.45 µm 47 mm GN-6 white gridded membrane, z-pack, gamma irradiated	1000/pkg (5 boxes of 200)	N/A	47 mm	N/A	N/A	N/A	74 °C 165 °F	N/A	Gamma irradiated at validated dose of 15 - 30 kGy
21A00A731	0.2 µm 47 mm Supor white gridded membrane, z-pack, gamma irradiated	1000/pkg (5 boxes of 200)	N/A	47 mm	N/A	N/A	N/A	100 °C (212 °F)	N/A	Gamma irradiated at validated dose of 15 - 30 kGy
21A00A732	0.45 µm 47 mm MetriceI black gridded membrane, z-pack, gamma irradiated	1000/pkg (5 boxes of 200)	N/A	47 mm	N/A	N/A	N/A	N/A	N/A	Gamma irradiated at validated dose of 15 - 30 kGy
21A00A733	0.8 µm 47 mm MetriceI black gridded membrane, z-pack, gamma irradiated	1000/pkg (5 boxes of 200)	N/A	47 mm	N/A	N/A	N/A	N/A	N/A	Gamma irradiated at validated dose of 15 - 30 kGy



# SENTINO® DISPENSERS, PUMPS AND FILTER FUNNELS

Ordering information and specifications



CLOSE

- 1
- 2
- 3

## PUMP FILTER FUNNELS

ORDERING INFORMATION			DIMENSIONS AND WEIGHT					OTHER SPECIFICATIONS		
Thomas #	Description	Pkg	Height	Diameter / Width / OD	Length	Weight	Outlet	OPERATION TEMP RANGE	Power	Cleaning and Sterilization
21A00A725	Sentino 100 mL polypropylene filter funnel, gamma irradiated	100/pkg	5.3 cm (2.1 in)	8.1 cm (3.2 in); Supports 47 mm filter	N/A	N/A	fits 4872	N/A	N/A	Gamma irradiated at validated dose of 15 - 30 kGy
21A00A726	Sentino 250 mL polypropylene filter funnel, gamma irradiated	80/pkg	9.6 cm (3.8 in)	8.1 cm (3.2 in); Supports 47 mm filter	N/A	N/A	fits 4872	N/A	N/A	Gamma irradiated at validated dose of 15 - 30 kGy
21A00A718	Sentino 150 mL polyphenylsulfone magnetic filter funnel	1/pkg	11.8 cm (4.6 in)	7.6 cm (3.0 in); Supports 47 mm filter	N/A	N/A	fits 4283	N/A	N/A	Withstands multiple autoclavings* at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min
21A00A719	Sentino 300 mL polyphenylsulfone magnetic filter funnel	1/pkg	16.8 cm (6.6 in)	7.6 cm (3.0 in); Supports 47 mm filter	N/A	N/A	fits 4283	N/A	N/A	Withstands multiple autoclavings* at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min
21A00A720	Sentino 500 mL polyphenylsulfone magnetic filter funnel	1/pkg	16.6 cm (6.5 in)	8.9 cm (3.5 in); Supports 47 mm filter	N/A	N/A	fits 4283	N/A	N/A	Withstands multiple autoclavings* at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min
21A00A721	Sentino polyphenylsulfone magnetic funnel replacement base, with support screen	1/pkg	N/A	Supports 47 mm filter	N/A	N/A	fits 4283	N/A	N/A	Withstands multiple autoclavings* at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min

\* Actual number of autoclave cycles will depend upon application and use

# LABORATORY MANIFOLD

Filtration flexibility crafted  
in stainless steel



**Full Product List  
and Specifications**

## PRODUCT CATALOG

Single-Use Filter Funnels

Sentino® Dispensers/Pumps

▶ Laboratory Manifold

Reusable Filter Funnels

Filter Funnel Membranes

Ampoule Broths/Petri Dishes/  
Accessories

Environmental Filters/Shakers

### Control Contamination

Designed in stainless steel with few pieces to disassemble and reassemble for easy cleaning, no o-rings in the fluid path for a lowered contamination risk and a lowered hose outlet means no back-burping that can require expensive and time-consuming retesting.

### Flexibility in Stainless Steel

Easy right- or left-handed set up with interchangeable end cap and hose barb ensure you are never reaching over the top of a funnel to turn valves on and off. Available adapters for MicroFunnel filter funnels and Sentino filter funnels, plus standard and elongated tulips for use with #8 stoppers.

### Double Capacity

Our coupler enables combining two 3-place manifolds for 6-place capacity that can still fit in a standard lab autoclave.



### Pall Laboratory Manifold

Unique design limits a lot of headaches typical of other manifolds such as places for contamination to hide, difficult cleaning and incompatibility with autoclaving, resulting in a worry-free option for processing up to 6 samples at one time.




Download the Brochure >



### Funnel Adapters

Four adapters to meet any application need including use with standard magnetic funnels, Sentino filter funnels, or any MicroFunnel™ filter funnel.



### Accessories

Add our coupler for increased capacity, combining two manifolds into one. Available replacement valves, hose barbs in two sizes, and end caps for those lost pieces save money by replacing only what you need.

## APPLICATIONS

### Bioburden or Sterility Testing in Pharmaceuticals

Determine number of viable  
microorganisms to assure product safety

### Spoilage Detection in Food and Beverages

Detect spoilage microorganisms to keep contaminated  
food and beverage products from reaching the market

### Drinking Water Testing

Monitor potable water for compliance with  
standards using Membrane Filtration Technique



# LABORATORY MANIFOLD

Ordering information and specifications



CLOSE

## MANIFOLD

ORDERING INFORMATION			DIMENSIONS AND WEIGHT				OTHER SPECIFICATIONS
Thomas #	Description	Pkg	Length	Width	Height	Weight	CLEANING AND STERILIZATION
20A00U122	3 Place Manifold including 3 valves, 1 end cap, 1 hose barb cap	1 set/pkg	3-place: 437.1 mm (17.2 in) 6-place: 846.0 mm (33.3 in)	152.4 mm (6.0 in)	99 mm (3.9 in)	3-place: 1.7 kg (3.76 lb) 6-place: 3.5 kg (7.72 lb)	Withstands multiple autoclavings* at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min
20A00U123	Microfunnel filter funnel adapter	3/pkg	N/A	53 mm (2.1 in)	35 mm (1.4 in)	213 g (0.5 lb)	Withstands multiple autoclavings* at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min
20A00U124	Sentino funnel adapter	3/pkg	N/A	60 mm (2.4 in)	29 mm (1.1 in)	172 g (0.4 lb)	Withstands multiple autoclavings* at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min
20A00U125	Standard adapter	3/pkg	N/A	44 mm (1.7 in)	45 mm (1.8 in)	116 g (0.3 lb)	Withstands multiple autoclavings* at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min
20A00U128	Elongated standard adapter	3/pkg	N/A	44 mm (1.7 in)	87 mm (3.4 in)	168 g (0.4 lb)	Withstands multiple autoclavings* at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min
20A00U126	Coupling device	1/pkg	34 mm (1.3 in)	31 mm (1.2 in)	N/A	70 g (0.2 lb)	Withstands multiple autoclavings* at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min

\* Actual number of autoclave cycles will depend upon application and use

# LABORATORY MANIFOLD

Ordering information and specifications



CLOSE

## MANIFOLD ACCESSORIES AND REPLACEMENT PARTS

ORDERING INFORMATION			DIMENSIONS AND WEIGHT				OTHER SPECIFICATIONS
Thomas #	Description	Pkg	Length	Width	Height	Weight	CLEANING AND STERILIZATION
20A00U121	Spare O-ring kit	1 set/pkg	N/A	N/A	N/A	N/A	N/A
20A00U127	Manifold valves	1/pkg	N/A	N/A	N/A	N/A	Withstands multiple autoclavings* at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min
<div>COMING SOON</div> 4887	5/16" ID-comparable hose barb end cap	1/pkg	N/A	N/A	N/A	N/A	Withstands multiple autoclavings* at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min
<div>COMING SOON</div> 4967	3/8" ID-compatible hose barb end cap	1/pkg	N/A	N/A	N/A	N/A	Withstands multiple autoclavings* at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min
<div>COMING SOON</div> 4899	Standard end cap	1/pkg	N/A	N/A	N/A	N/A	Withstands multiple autoclavings* at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min

\*Tubing must be vacuum rated

\*\*Actual number of autoclave cycles will depend upon application and use



# REUSABLE FILTER FUNNELS

High-performance magnetic and stainless steel filter funnels for the ultimate application flexibility



**Full Product List and Specifications**

## PRODUCT CATALOG

Single-Use Filter Funnels

Sentino® Dispensers/Pumps

Laboratory Manifold

▶ Reusable Filter Funnels

Filter Funnel Membranes

Ampoule Broths/Petri Dishes/Accessories

Environmental Filters/Shakers

### Easy-to-Use Options

All funnels are designed for easy membrane access and no clips, twisting or other extra parts are needed to secure the funnels to the base. Wide range of funnel materials for any application.

### Economical Choice

Clean and sterilize over and over using disposable membranes, saving money and providing a more eco-friendly option.

### Accurate Sample Measurement

Graduated at 50 mL increments for high visibility with +/-2% accuracy at maximum volume.



### Magnetic Filter Funnels

Unique magnetic seal allows one-handed removal of funnel top to access membrane. Polyphenyl-sulfone construction adds durability and safety. Forceps access point for easy filter retrieval.



### Stainless Steel Filter Funnels

Designed for vacuum filtration to collect biological or particulate matter from liquids. Superior chemical resistance for harsh applications. Funnel's weight seals filter to base.



### Sentino Magnetic Filter Funnels

All the same great features as our standard magnetic funnel designed to fit on our Sentino pump with a shorter stem. Sentino 47 mm magnetic filter funnel option available.

## APPLICATIONS

### Waste Reduction and Cost Savings

Re-usable funnels prevent excess waste, while also providing an economical option over single-use alternatives.

### Water and Effluent Testing

Use our standard or Sentino magnetic filter funnel and the Membrane Filter Technique to test drinking water, surface and plant water or municipal effluent.

### Harsh Chemicals

Our stainless steel filter funnels are designed for applications requiring superior chemical resistance. Works with standard manifold systems or vacuum flasks.

# REUSABLE FILTER FUNNELS

Ordering information and specifications



CLOSE

- 1
- 2
- 3

## MAGNETIC FUNNELS

ORDERING INFORMATION			DIMENSIONS AND WEIGHT			OTHER SPECIFICATIONS		
Thomas #	Description	Pkg	Height	Diameter	Outlet		Effective Filtration Area	Cleaning and Sterilization
21A00A705	150 mL polyphenylsulfone for 47 mm membranes	1/pkg	17.8 cm (7.0 in)	7.6 cm (3.0 in); accepts 47 mm filters	fits standard #8 stopper	150 mL	9.6 cm <sup>2</sup>	Withstands multiple autoclavings* at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min; UV sterilizable
21A00A700	300 mL polyphenylsulfone for 47 mm membranes, with lid	1/pkg	22.9 cm (9.0 in)	7.6 cm (3.0 in); accepts 47 mm filters	fits standard #8 stopper	300 mL	9.6 cm <sup>2</sup>	Withstands multiple autoclavings* at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min; UV sterilizable
21A00A701	300 mL polyphenylsulfone for 47 mm membranes	1/pkg	22.9 cm (9.0 in)	7.6 cm (3.0 in); accepts 47 mm filters	fits standard #8 stopper	300 mL	9.6 cm <sup>2</sup>	Withstands multiple autoclavings* at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min; UV sterilizable
21A00A699	500 mL polyphenylsulfone for 47 mm membranes	1/pkg	22.9 cm (9.0 in)	8.9 cm (3.5 in); accepts 47 mm filters	fits standard #8 stopper	500 mL	13.1 cm <sup>2</sup>	Withstands multiple autoclavings* at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min; UV sterilizable

\* Actual number of autoclave cycles will depend upon application and use



# REUSABLE FILTER FUNNELS

Ordering information and specifications



CLOSE

- 1
- 2
- 3

## STAINLESS STEEL FUNNELS

### ORDERING INFORMATION

Thomas #	Description	Pkg
21A00A695	100 mL 304 stainless steel for 47 mm membranes	1/pkg
21A00A697	1 L 304 stainless steel for 47 mm membranes	1/pkg

### DIMENSIONS AND WEIGHT

Height	Diameter	Outlet
16.3 cm (6.4 in)	6.6 cm (2.6 in); accepts 47 and 50 mm filters	fits standard #8 stopper
22.2 cm (8.7 in)	15.2 cm (6.0 in); ; accepts 47 mm filters	fits standard #2 stopper

### OTHER SPECIFICATIONS

	Effective Filtration Area	Cleaning and Sterilization
100 mL, calibrated to 50 mL	9.6 cm²	Withstands multiple autoclavings* at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min; UV sterilizable
1 L	9.6 cm²	Withstands multiple autoclavings* at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min; UV sterilizable

## Other Funnels

### Ordering Information

Thomas #	Description	Pkg
21A00A673	50 mL polysulfone for 25 mm membranes	1/pkg
21A00A672	200 mL polysulfone for 25 mm membranes	1/pkg

### Dimensions and Weight

Height	Diameter	Outlet
15.8 cm (6.2 in)	7.1 cm (2.8 in); accepts 25 mm filters	fits standard #2 stopper
20.1 cm (7.9 in)	7.1 cm (2.8 in); accepts 25 mm filters	fits standard #2 stopper

### Other Specifications

Capacity	Effective Filtration Area	Cleaning and Sterilization
50 mL	N/A	Withstands multiple autoclavings* at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min
200 mL	N/A	Withstands multiple autoclavings* at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min

\* Actual number of autoclave cycles will depend upon application and use

# REUSABLE FILTER FUNNELS

Ordering information and specifications



CLOSE

- 1
- 2
- 3

## ACCESSORIES

ORDERING INFORMATION			DIMENSIONS AND WEIGHT			OTHER SPECIFICATIONS		
Thomas #	Description	Pkg	Height	Diameter	Outlet		Effective Filtration Area	Cleaning and Sterilization
21A00B113	No. 8 rubber stopper	1/pkg	N/A	N/A	N/A	N/A	N/A	Withstands multiple autoclavings* at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min
21A00A704	300 mL magnetic funnel lid kit	1/pkg	N/A	N/A	N/A	300 mL	N/A	Withstands multiple autoclavings* at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min
21A00A706	150 mL polyphenylsulfone magnetic funnel replacement housing	1/pkg	N/A	N/A	N/A	150 mL	N/A	Withstands multiple autoclavings* at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min
21A00A702	300 mL polyphenylsulfone magnetic funnel replacement housing	1/pkg	N/A	N/A	N/A	300 mL	N/A	Withstands multiple autoclavings* at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min
21A00A716	500 mL polyphenylsulfone magnetic funnel replacement housing	1/pkg	N/A	N/A	N/A	500 mL	N/A	Withstands multiple autoclavings* at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min
21A00A703	150/300 mL polyphenylsulfone magnetic funnel replacement base, without support screen	1/pkg	N/A	N/A	N/A	N/A	N/A	Withstands multiple autoclavings* at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min
21A00B117	Polyphenylsulfone magnetic funnel replacement support screen	1/pkg	N/A	N/A	N/A	N/A	N/A	Withstands multiple autoclavings* at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min
21A00A698	304 stainless steel magnetic funnel replacement support screen	1/pkg	N/A	N/A	N/A	N/A	N/A	Withstands multiple autoclavings* at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min
COMING SOON 4231	304 stainless steel replacement 47 mm compatible base, without support screen	1/pkg	N/A	N/A	N/A	N/A	N/A	Withstands multiple autoclavings* at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min
21A00B112	304 stainless steel replacement 47 mm compatible support screen	1/pkg	N/A	N/A	N/A	N/A	N/A	Withstands multiple autoclavings* at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min

\* Actual number of autoclave cycles will depend upon application and use



# FILTER FUNNEL MEMBRANES

Certified membranes for high-performance microbiological analysis



Full Product List and Specifications

## PRODUCT CATALOG

- Single-Use Filter Funnels
- Sentino® Dispensers/Pumps
- Laboratory Manifold
- Reusable Filter Funnels
- ▶ Filter Funnel Membranes
- Ampoule Broths/Petri Dishes/Accessories
- Environmental Filters/Shakers

### Flexibility of Choice

From high-performance Supor® membrane with its exceptional flow and retention rates to GN-6 mixed cellulose esters to meet most regulatory application needs, including a variety of package sizes with sterile S-packs and non-sterile options.

### Ensure Accurate Analysis

Unique dot grid pattern provides guidance for bacterial colony quantification without growth inhibition or enhancement. No expensive and time consuming recounts or retests needed.

### Certified for Use

Each lot is QC tested to assure reliable results, with certificates available online.



### GN-6 Membrane

Certified 0.45 µm membrane is designed for microbiological analysis with the MF Technique. Mixed cellulose esters provide maximum organism recovery that meets regulatory guidelines.



### Metricel® Black PES Membrane

Membrane's dark background provides excellent contrast for counting light-colored or opaque colonies. Sharp contrast between membrane and white grid lines ensures accuracy while viewing and counting.



### Supor® PES Membrane

Highly retentive, certified membrane for isolation and enumeration of organisms. Superior flow rates reduce filtration time and assure high throughput. Low protein binding and chemical compatibility permit use in any application. 0.2 µm and 0.45 µm options enable filtration of smaller organisms.

## APPLICATIONS

### Pharmaceutical, Water, Food & Beverage

Widely-accepted mixed cellulose esters, like our GN-6, are ideal for microbiological analysis in pharmaceutical, food and beverage, and other regulatory guidelines. Certified for microbiological analysis of potable, waste, process, and natural waters using MF Technique. Ideal for isolation and enumeration of total and fecal coliforms, *E. coli*, *Fecal Streptococcus*, and fungi.

### Colonies Light in Color

Our Metricel Black PES membrane is designed for sterile filtration and clarification applications such as isolation and enumeration of yeast and mold colonies, plus spoilage organism monitoring and identification in food and beverage QC labs.

### High Performance Required

Superior flow rate and retention performance makes Supor membranes ideal where traditional cellulose ester membranes fail with a 0.2 µm pore size. Certified for microbiological examination of water and wastewater. Ideal for labs requiring enumeration of organisms stunted in size from exposure to harsh conditions. Easily isolates *Pseudomonas* species, especially stressed organisms.

# FILTER FUNNEL MEMBRANES

Ordering information and specifications



CLOSE

- 1
- 2
- 3

## GN-6

ORDERING INFORMATION			DIMENSIONS AND WEIGHT		OTHER SPECIFICATIONS								
Thomas #	Description	Pkg	Height / Thickness	Diameter / Width	Pore size	Color	Typical water flow rate	Max Operating Temp	Extractables - Boiling Water	Min Bubble Point (Water)	Recovery	Refractive Index	Cleaning and Sterilization
21A00B010	0.45 µm 25 mm GN-6 white ungridded membrane, bulk pack	100/pkg	152 µm (6 mils)	25 mm	0.45 µm	white	> 65 mL/min/cm2at 0.7 bar (70 kPa, 10 psi)	74 °C (165 °F)	<2%	1.8 bar (180 kPa, 26 psi)	>90% E.coli (measured vs control)	1.512	Autoclave if desired at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min
21A00B012	0.45 µm 25 mm GN-6 white gridded membrane, bulk pack	100/pkg	152 µm (6 mils)	25 mm	0.45 µm	white with black grid	> 65 mL/min/cm2at 0.7 bar (70 kPa, 10 psi)	74 °C (165 °F)	<2%	1.8 bar (180 kPa, 26 psi)	>90% E.coli (measured vs control)	1.512	Autoclave if desired at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min
21A00B013	0.45 µm 37 mm GN-6 white ungridded membrane, bulk pack, with support pad	100/pkg	152 µm (6 mils)	37 mm	0.45 µm	white	> 65 mL/min/cm2at 0.7 bar (70 kPa, 10 psi)	74 °C (165 °F)	<2%	1.8 bar (180 kPa, 26 psi)	>90% E.coli (measured vs control)	1.512	Autoclave if desired at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min
21A00B056	0.45 µm 47 mm GN-6 white ungridded membrane, individually sealed, gamma irradiated	200/pkg	152 µm (6 mils)	47 mm	0.45 um	white	> 65 mL/min/cm2at 0.7 bar (70 kPa, 10 psi)	74 °C (165 °F)	<2%	1.8 bar (180 kPa, 26 psi)	>90% E.coli (measured vs control)	1.512	Gamma irradiated at validated dose of 15 - 30 kGy
21A00B057	0.45 µm 47 mm GN-6 white gridded membrane, individually sealed, gamma irradiated	200/pkg	152 µm (6 mils)	47 mm	0.45 um	white with black grid	> 65 mL/min/cm2at 0.7 bar (70 kPa, 10 psi)	74 °C (165 °F)	<2%	1.8 bar (180 kPa, 26 psi)	>90% E.coli (measured vs control)	1.512	Gamma irradiated at validated dose of 15 - 30 kGy
21A00B022	0.45 µm 47mm GN-6 white gridded membrane, individually sealed, gamma irradiated	1000/pkg (5 boxes of 200)	152 µm (6 mils)	47 mm	0.45 um	white with black grid	> 65 mL/min/cm2at 0.7 bar (70 kPa, 10 psi)	74 °C (165 °F)	<2%	1.8 bar (180 kPa, 26 psi)	>90% E.coli (measured vs control)	1.512	Gamma irradiated at validated dose of 15 - 30 kGy
21A00B039	0.45 µm 47 mm GN-6 white gridded membrane, individually sealed, gamma irradiated	2000/pkg (10 boxes of 200)	152 µm (6 mils)	47 mm	0.45 um	white with black grid	> 65 mL/min/cm2at 0.7 bar (70 kPa, 10 psi)	74 °C (165 °F)	<2%	1.8 bar (180 kPa, 26 psi)	>90% E.coli (measured vs control)	1.512	Gamma irradiated at validated dose of 15 - 30 kGy
21A00B009	0.45 µm 47 mm GN-6 white gridded membrane, bulk pack	100/pkg	152 µm (6 mils)	47 mm	0.45 µm	white with black grid	> 65 mL/min/cm2at 0.7 bar (70 kPa, 10 psi)	74 °C (165 °F)	<2%	1.8 bar (180 kPa, 26 psi)	>90% E.coli (measured vs control)	1.512	Autoclave if desired at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min
21A00B011	0.45 µm 47 mm GN-6 white ungridded membrane, bulk pack	100/pkg	152 µm (6 mils)	47 mm	0.45 µm	white	> 65 mL/min/cm2at 0.7 bar (70 kPa, 10 psi)	74 °C (165 °F)	<2%	1.8 bar (180 kPa, 26 psi)	>90% E.coli (measured vs control)	1.512	Autoclave if desired at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min
21A00B078	0.45 µm 50 mm GN-6 white gridded membrane, individually sealed, gamma irradiated	200/pkg	152 µm (6 mils)	50 mm	0.45 um	white with black grid	> 65 mL/min/cm2at 0.7 bar (70 kPa, 10 psi)	74 °C (165 °F)	<2%	1.8 bar (180 kPa, 26 psi)	>90% E.coli (measured vs control)	1.512	Gamma irradiated at validated dose of 15 - 30 kGy
21A00A951	0.45 µm 85 mm GN-6 white gridded membrane, bulk pack, gamma irradiated	50/pkg	152 µm (6 mils)	85 mm	0.45 um	white with black grid	> 65 mL/min/cm2at 0.7 bar (70 kPa, 10 psi)	74 °C (165 °F)	<2%	1.8 bar (180 kPa, 26 psi)	>90% E.coli (measured vs control)	1.512	Gamma irradiated at validated dose of 15 - 30 kGy



# FILTER FUNNEL MEMBRANES

Ordering information and specifications



CLOSE

- 1
- 2
- 3

## METRICEL BLACK

ORDERING INFORMATION			DIMENSIONS AND WEIGHT		OTHER SPECIFICATIONS								
Thomas #	Description	Pkg	Height / Thickness	Diameter / Width	Pore size	Color	Typical water flow rate	Max Operating Temp	Extractables - Boiling Water	Min Bubble Point (Water)	Recovery	Refractive Index	Cleaning and Sterilization
21A00B088	0.45 µm 47 mm MetriceI black gridded membrane, individually sealed, gamma irradiated	200/pkg	0.45 µm: 130 µm (5.1 mils)	47 mm	0.45 µm	black with white grid	mL/min/cm2 at 0.7 bar (70 kPa, 10 psi) 0.45 µm: > 34	N/A	N/A	0.45 µm: 1.6 bar (160 kPa, 23 psi)	N/A	N/A	Gamma irradiated at validated dose of 15 - 30 kGy
21A00B089	0.45 µm 47 mm MetriceI black gridded membrane, bulk pack	100/pkg	0.45 µm: 130 µm (5.1 mils)	47 mm	0.45 µm	black with white grid	mL/min/cm2 at 0.7 bar (70 kPa, 10 psi) 0.45 µm: > 34	N/A	N/A	0.45 µm: 1.6 bar (160 kPa, 23 psi)	N/A	N/A	Autoclave if desired at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min
21A00B090	0.8 µm 47 mm MetriceI black gridded membrane, individually sealed, gamma irradiated	200/pkg	0.8 µm: 147 µm (5.8 mils)	47 mm	0.8 µm	black with white grid	mL/min/cm2 at 0.7 bar (70 kPa, 10 psi) 0.8 µm: > 102	N/A	N/A	0.8 µm: 1.0 bar (100 kPa, 15 psi)	N/A	N/A	Gamma irradiated at validated dose of 15 - 30 kGy
21A00B091	0.8 µm 47 mm MetriceI black gridded membrane, bulk pack	100/pkg	0.8 µm: 147 µm (5.8 mils)	47 mm	0.8 µm	black with white grid	mL/min/cm2 at 0.7 bar (70 kPa, 10 psi) 0.8 µm: > 102	N/A	N/A	0.8 µm: 1.0 bar (100 kPa, 15 psi)	N/A	N/A	Autoclave if desired at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min

# FILTER FUNNEL MEMBRANES

Ordering information and specifications



CLOSE

- 1
- 2
- 3

## SUPOR®

ORDERING INFORMATION			DIMENSIONS AND WEIGHT		OTHER SPECIFICATIONS								
Thomas #	Description	Pkg	Height / Thickness	Diameter / Width	Pore size	Color	Typical water flow rate	Max Operating Temp	Extractables - Boiling Water	Min Bubble Point (Water)	Recovery	Refractive Index	Cleaning and Sterilization
21A00B050	0.2 µm 47 mm Supor black gridded membrane, individually sealed, gamma irradiated	200/pkg	145 um (5.7mils)	47 mm	0.2 um	white with black grid	26 mL/min/cm2 at 0.7 bar (70 kPa, 10 psi)	100 °C (212 °F)	<4%	3.5 bar (350 kPa, 51 psi)	>90% (measured vs control)	1.64	Gamma irradiated at validated dose of 15 - 30 kGy
21A00A952	0.45 µm 47 mm Supor black gridded membrane, individually sealed, gamma irradiated	200/pkg	140 um (5.5 mils)	47 mm	0.45 µm	white with black grid	58 mL/min/cm2 at 0.7 bar (70 kPa, 10 psi)	100 °C (212 °F)	<4%	2.5 bar (250 kPa, 36 psi)	N/A	N/A	Gamma irradiated at validated dose of 15 - 30 kGy
21A00B020	0.8 µm 47 mm Supor black gridded membrane, individually sealed, gamma irradiated	200/pkg	140 um (5.5 mils)	47 mm	0.8 um	white with black grid	165 mL/min/cm2 at 0.7 bar (70 kPa, 10 psi)	100 °C (212 °F)	<4%	110 bar (250 kPa, 15 psi)	N/A	N/A	Gamma irradiated at validated dose of 15 - 30 kGy

## CERTIFICATIONS

Certified for the microbiological analysis of potable, waste, process, and natural waters in accordance with the MF Technique referenced in *Standard Methods for the Examination of Water and Wastewater* and the U.S. EPA's *Microbiological Methods for Monitoring the Environment*, 600/8-78-017.

# AMPOULE BROTHS, PETRI DISHES & ACCESSORIES

Everything you need to  
grow and manage your  
microbial colonies



Full Product List  
and Specifications

## PRODUCT CATALOG

- Single-Use Filter Funnels
- Sentino® Dispensers/Pumps
- Laboratory Manifold
- Reusable Filter Funnels
- Filter Funnel Membranes
- ▶ Ampoule Broths/Petri Dishes/Accessories
- Environmental Filters/Shakers

### Everything You Need

From petri dishes to fit a standard 47 mm membrane to autoclavable forceps, we have everything you need to process microbial samples.



### Broth Media

Wide variety of sterile ampoule media premixed, premeasured, and sterilized for maximum efficiency and time savings. Meets Membrane Filter (MF) Technique requirements with 2 mL ampoules. Wide-mouth ampoules available for easier pouring. Choose from plastic or glass options.

### Ready-to-Use

Absorbant pads and petri dishes provided gamma-irradiated and sterile, plus pre-packaged, single-use media, mean no potential for contamination found with traditional in-house media formulation.



### Petri Dishes and Absorbent Pads

Size-compatible dishes come with or without absorbent pads. Bulk packaging offers exceptional value. Absorbent pads, available both non-sterile and gamma irradiated in dispenser packs of 100, are also available separately with a patented-design dispenser for one-handed removal.

### All Backed by Pall

Whether you need scientific expertise, tips, and tricks or help finding solutions to your laboratory problems, our team of technical and commercial experts are here to help.



### Forceps

Make filter handling safe and easy. Flat, smooth tip surface avoids membrane damage. Polypropylene finger grips provide comfortable and secure hold. Ideal for membrane handling to and from filter holders and petri dishes.

## APPLICATIONS

### Water

MF-Endo and M-FC (with and without rosolic acid) media are used when analyzing water samples for total coliforms, fecal coliforms and *E. coli*, *Pseudomonas* and KF-Streptococcal broths are highly selective media for detecting contamination in water samples.

### Food & Beverage

M-TGE, HPC, M-Green YM, and Orange Serum broths are used in the food and beverage industry to detect potential spoilage organisms in final products (and fluids used in manufacture of these products).

### Pharmaceutical & Microelectronics

Trypticase Soy broth, M-TGE, and HPC may be used to test final products and process waters for total bacteria in the pharmaceutical and microelectronics industries.



# AMPOULE BROTHS, PETRI DISHES & ACCESSORIES

Ordering information and specifications



CLOSE

- 1
- 2
- 3
- 4

## 2 ML PLASTIC AMPOULES

ORDERING INFORMATION			OTHER SPECIFICATIONS					
Thomas #	Description	Pkg	Test organisms	pH at 25 C	Shelf life (2-8C)	Media Color	Target Golony Color	Application
CHM01P686	MF-Endo broth, total coliforms	50/pkg	<i>E. coli</i>	7.2 +/- 0.2	1 year	pinkish red	dark red with metallic sheen	
CHM01P678	M-FC broth with rosolic acid, fecal coliforms	50/pkg	<i>E. coli</i>	7.4 +/- 0.2	1 year	violet	blue	Municipal wastewater, drinking water
CHM01P687	M-TGE broth, total bacteria	50/pkg	<i>E. coli</i> , <i>S. epidermidis</i>	7.0 +/- 0.2	1 year	pale yellow	organism dependent	Municipal wastewater, drinking water
CHM01P691	M-TGE with TTC indicator, total bacteria	50/pkg	<i>E. coli</i>	7.0 +/- 0.2	1 year	pale yellow	red	Food and beverage; pharmaceutical; electronics
CHM01P680	Trypticase soy broth - USP, total bacteria	50/pkg	<i>E. coli</i> , <i>S. epidermidis</i>	7.3 +/- 0.2	1 year	pale yellow	organism dependent	Pharmaceutical; electronics
CHM01P689	KF-Streptococcal broth, fecal Streptococcus	50/pkg	<i>S. faecalis</i>	7.2 +/- 0.2	1 year	light purple	bright red	General to monitor these organisms
CHM01P679	Pseudomonas broth, Pseudomonas sp.	50/pkg	<i>P. aeruginosa</i>	7.1 +/- 0.2	1 year	light amber	green-blue	General to monitor these organisms
CHM01P688	M-Green YM broth, yeast and mold	50/pkg	<i>S. cerevisiae</i>	4.6 +/- 0.2	1 year	green	pale green	Food and beverage
CHM01P690	Orange serum broth, Lactobacillus sp.	50/pkg	<i>L. plantarum</i> , <i>S. cerevisiae</i>	5.6 +/- 0.2	1 year	dark amber	organism dependent	Food and beverage
CHM01P682	HPC Media with TTC indicator, total bacteria	50/pkg	<i>E. coli</i> , <i>S. epidermidis</i>	7.1 +/- 0.2	1 year	pale yellow	red	Food and beverage; pharmaceutical; electronics



# AMPOULE BROTHS, PETRI DISHES & ACCESSORIES

Ordering information and specifications



CLOSE

- 1
- 2
- 3
- 4

## PETRI DISHES AND PADS

ORDERING INFORMATION			DIMENSIONS		OTHER SPECIFICATIONS	
Thomas #	Description	Pkg	HEIGHT / THICKNESS	Diameter	FILTER SIZE	Cleaning and Sterilization
21A00A872	Petri dish for 47 mm membrane without absorbant pad, bulk packed, gamma irradiated	500/pkg	9.0 mm (0.35 in)	50.0 mm (1.97 in)	accepts 47 mm	Gamma irradiated at validated dose of 15 - 30 kGy
21A00A874	Petri dish for 47 mm membrane without absorbant pad, gamma irradiated	100/pkg	9.0 mm (0.35 in)	50.0 mm (1.97 in)	accepts 47 mm	Gamma irradiated at validated dose of 15 - 30 kGy
21A00A875	Petri dish for 47 mm membrane, with absorbant pad, gamma irradiated	100/pkg	9.0 mm (0.35 in)	50.0 mm (1.97 in)	accepts 47 mm	Gamma irradiated at validated dose of 15 - 30 kGy
21A00B021	Absorbant pads, dispenser included, gamma irradiated	1000/pkg (10 tubes of 100 pads)	0.9 mm (35 mils)	47 mm	accepts 47 mm	Gamma irradiated at validated dose of 15 - 30 kGy
21A00B038	Absorbent pads, dispenser included	1000/pkg (10 tubes of 100 pads)	0.9 mm (35 mils)	47 mm	accepts 47 mm	N/A



# AMPOULE BROTHS, PETRI DISHES & ACCESSORIES

Ordering information and specifications



CLOSE

- 1
- 2
- 3
- 4

## FORECEPS

ORDERING INFORMATION			DIMENSIONS		OTHER SPECIFICATIONS	
Thomas #	Description	Pkg	HEIGHT / THICKNESS	Diameter	FILTER SIZE	Cleaning and Sterilization
21A00A825	Stainless steel forceps with polypropylene multi-colored grips	3/pkg	N/A	N/A	N/A	Withstands multiple autoclavings* at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min
21A00A949	Stainless steel forceps with polypropylene black grips	1/pkg	N/A	N/A	N/A	Withstands multiple autoclavings* at 121 - 123 °C (250 -253 °F) at 1.0 bar (100 kPa, 15 psi) for 15 - 20 min

\*Actual number of autoclave cycles will depend upon application and use

# ENVIRONMENTAL WATER FILTERS & SHAKERS

High-performance concentration and recovery of *Cryptosporidium* oocysts and *Giardia* cysts from source or finished water



**Full Product List  
and Specifications**

## PRODUCT CATALOG

Single-Use Filter Funnels

Sentino® Dispensers/Pumps

Laboratory Manifold

Reusable Filter Funnels

Filter Funnel Membranes

Ampoule Broths/Petri Dishes/  
Accessories

▶ **Environmental Filters/Shakers**

### High Flow Rate

Patented pleated design's high filtration area produces superior throughput

### Safe Single-Use Disposable

Self-contained capsule eliminates handling of potentially contaminated filter parts. No assembly or cleaning of filter holders or elution equipment is required.

### Efficient Recovery

Typical recovery is greater than 70% of target organisms.



### Environmental Shaker

Save time by processing up to eight samples at once. Robust and designed for years of safe and efficient operation.



### Envirochek® Capsules

Along with high flow rates and excellent recoveries, Envirochek capsules are designed to also eliminate false negatives with a 1 µm pore size designed to retain *Cryptosporidium* and *Giardia*.



### Envirochek HV Capsules

The Envirochek HV capsule's high flow rate enable filtration of up to 50L of source water testing and up to 1000 L of drinking water analysis.

## APPLICATIONS

### Environmental Water Quality

Our Envirochek capsules are validated and listed in U.S. EPA Methods 1622 and 1623.1 for sampling source water for *Cryptosporidium* and *Giardia*.

### High Filtration Volumes

The Envirochek HV capsules are suited for filtration of higher volumes for regulatory testing and are approved for EPA method 1623.1 for monitoring *Cryptosporidium* and *Giardia*.









# MICROBIOLOGY QC APPLICATIONS



## Pharmaceutical, Bioprocessing & Biotech

Pall's disposable, ready-to-use filtration devices enhance pharmaceutical QC workflows. Execute testing at the time of sampling to reduce cross contamination and false test results.

[Learn More >](#)



## Food & Beverage

Effective cleaning procedures and high-quality raw materials are essential to preparing safe food and beverages. Pall filtration identifies the presence of microorganisms that shorten shelf life and render inedible products.

[Learn More >](#)



## Environmental Water Quality

Meeting and exceeding industry standards, Pall filtration has led the industry since membrane filtration was adopted as a preferable method for monitoring water quality.

[Learn More >](#)






# PHARMACEUTICAL, BIOPROCESSING & BIOTECH

Reduce cross contamination and repeat testing



From microbial limit testing of water and raw materials through bioburden and sterility testing, filtration is critical for the manufacture of safe and effective pharmaceuticals. Appropriate testing can prevent production disruptions and support out-of-specification investigations.

Pall's disposable, ready-to-use filtration systems are ideal for quality control analysis of aqueous fluids used in pharmaceutical and biologic production.



[View Workflow >](#)

## PALL QUALITY POLICY AND CERTIFICATIONS

[Learn More about Quality at Pall >](#)

[Request a Product Certificate >](#)



### MicroFunnel™ Plus Filter Funnels

Eliminates need for sample collection cup during water testing. Unique squeeze design permit easy membrane access. Compatible with temperatures up to 90° C.



### MicroFunnel ST Filter Funnels

Convenient filters for testing in isolators or clean-rooms. Overpack layer means only one wipe down to transfer several funnels into clean test areas.



### Laboratory Manifold

Optimize testing without sacrificing cleanliness. Reduces cross contamination with fewer parts to clean. Coupler enables joining two smaller units together, permitting sterilization of up to 6 places at once in standard lab-size autoclaves.




### Sentino® Pump System

Reduce the time to prepare membrane filtration. Single-sample filtration quickly and safely. Free up lab space, simplify testing, and ensure contamination control.



# PHARMACEUTICAL, BIOPROCESSING & BIOTECH WORKFLOW



[Learn More about Quality at Pall](#)

[Request a Product Certificate](#)




## FOOD & BEVERAGE

Effectively identify microorganisms that spoil food and shorten shelf life



Food and beverage industry quality control processes require options that range from completely disposable, ready-to-use filter funnels, such as our MicroCheck® filter funnels, to modular and versatile platforms such as the Sentino® Microbiology System, all enabling use of the Membrane Filtration (MF) technique. This flexibility enables choice of the most efficient testing so that safe food products can get to market faster.

Pall's food and beverage filtration solutions are simple to set up and easy to use. The high-performance products speed up laboratory processing and reduce contamination risk.



View Workflow >

### PALL QUALITY POLICY AND CERTIFICATIONS

Learn More about Quality at Pall >

Request a Product Certificate >



#### MicroCheck Filter Funnels

Specifically designed for beverage microbial analysis. Easy-to-use filters are ideal for finished product and raw material microbial testing with an integrated petri dish for culture-in-place capability.



#### Sentino Microbiology Pump

Compact footprint frees valuable bench space while optimizing efficiency. Peristaltic pump action sends filtrate to waste collection.



#### Sentino Filter Dispenser

Aseptically dispenses one membrane disc at the touch of a button. Accepts a miniaturized refill pack that minimizes storage space and packaging waste.



#### Sentino Filter Funnels

Unique design enables efficient membrane removal. No-leak magnetic seals allow one-handed operation.



#### Laboratory Manifold

Optimize testing without sacrificing cleanliness. Reduces cross contamination with fewer parts to clean. Coupler enables joining two smaller units together, permitting sterilization of up to 6 places at once in standard lab-size autoclaves.





## FOOD & BEVERAGE WORKFLOW

Beverage



Sample collection




Transfer from Sample container to MicroCheck® Beverage Monitors



Manifold

Sentino



Analysis

Sample collection



Dispense membranes from Sentino® Dispenser and Dispenser packs



Place membrane on magnetic funnel



Learn More about Quality at Pall



Request a Product Certificate



duces cross contamination with fewer parts to clean. Coupler enables joining two smaller units together, permitting sterilization of up to 6 places at once in standard lab-size autoclaves.




# ENVIRONMENTAL WATER QUALITY

Reliable, easy-to-use products help your environmental testing stay error-free



Every day, health officials and quality managers make critical decisions about water quality that impact public safety. Reliable data from products designed to meet and even exceed the stringent requirements of water or product testing regulations are the key to assuring proper actions are taken.

Pall filtration has led the industry since membrane filtration was adopted as a preferable method for monitoring drinking water and environmental water quality. Our easy-to-use products help avoid testing errors.



[View Workflow >](#)

## PALL QUALITY POLICY AND CERTIFICATIONS

[Learn More about Quality at Pall >](#)

[Request a Product Certificate >](#)



### Envirochek® Capsules & Shaker

Capture 100% of *Cryptosporidium* oocysts and *Giardia* cysts from source or finished water. Disposable design eliminates false positives from cross contamination. Shaker processes up to eight samples at once.



### Reusable Magnetic Filter Funnels

Used extensively by the water quality testing community, the one-handed operation simplifies testing and improves aseptic technique.



### GN-6 Membranes

Mixed cellulose ester membranes provide uniform, consistent organism growth. A variety of media, petri dishes, and accessories support water quality labs.




### Sentino® Pump and Dispenser

Filter funnels, pumps, and media dispensers enhance the performance of your water testing workflows. Their compact design frees valuable bench space and disposable fluid path limits biofilm build up and contamination.



# ENVIRONMENTAL WATER QUALITY WORKFLOW



[Learn More about Quality at Pall](#) >

[Request a Product Certificate](#) >

## DIGITAL LIBRARY

Your one stop for all our  
Micro QC links at pall.com.


### ACCESS ALL OUR DIGITAL CONTENT

- > Application Notes and Science Briefs
- > Data/Info Sheets
- > Instructions For Use
- ▶ Videos
- ▶ Webinar Hub
- > All Micro QC Content

### READ MORE AT PALL.COM

- > **Micro QC**
- > Bioburden And Microbial Limit Testing In Pharma
- > Food And Beverage Spoilage Organism Testing
- > Track Contamination In Environmental Water

### SEE OUR LATEST U.S. AND CANADIAN PROMOTIONS



Redeem Limited  
Time Offers  
**Today!**

Learn More >

**Request a Micro QC  
Sample or Demo**

Click here and tell us about your application and we'll  
schedule a demo and/or send you a free sample!





## WHY PALL FOR MICROBIOLOGY QC?

Ensuring reliable test results essential for effective product quality monitoring.

The accurate, reliable detection of microorganisms is critical to public safety and industrial economics. Pall excels in the development and manufacture of products to detect and control these microorganisms. With over 70 years of development expertise, Pall is a recognized leader in membrane chemistry. Our filtration and membrane products set the standard for quality and compliance with stringent microbial regulations.



### BROAD SELECTION

A wide range of disposable filter funnels and accessories that simplify microbiological analysis.



### THROUGHPUT FLEXIBILITY

Filtration solutions that speed microbiological sample collection, analysis, and test results whether testing a single sample or hundreds per day.



### EASY TO USE

Products designed for superior ergonomic use, reduced contamination risk, flexible membrane/funnel configurations and sample filtration.



### YOUR TECHNICAL PARTNER

Solutions that comply with international testing methods are supported by technical expertise, literature, and quality certifications.

At Pall, we know quality is paramount for successful pharmaceutical development and production. We will always ask customers what can be done better. Our personal commitment is to continually advance our Quality Management System and processes by establishing quality objectives that deliver sustained measurable improvements.

# CONTACT US

For customer service or technical support,  
contact us at the email or phone numbers below:



ThomasSci.com  
833.544.SHIP (7447)  
CustomerService@thomassci.com

Connect With Us:

