



# Digital Thermo Microplate Shaker DTS-2



## Product Description

### 2 or 4 Immune Plates

With the ability to accommodate 4 microplates simultaneously, the DTS-4 enables a considerable increase in processed volume. These high-precision space-savers free up valuable lab space while still ensuring a superior level of performance.

### 1.5 mm Rotational Orbit

The DTS series features an ideal rotational orbit of 1.5 mm for maximum performance, and works conveniently with any standard microplate.

### Bi-Directional Heating System

The hermetic thermostatic container of each unit is equipped with a bi-directional heating system housed within both the base and the lid. Impervious to room temperature, this component allows the entire volume to be heated uniformly while eliminating condensation at the same time. The result – pinpoint accuracy and reliability with even micro-volume samples.

### Simultaneous Display Of All Adjustable Parameters

With a user-friendly display panel showing temperature, RPM, and timer settings separately, technicians can adjust these criteria with ease.

### Autonomous Memory For Storing User Settings

Operate the DTS-4 with confidence, knowing that in the event of power outage or disconnection from power supply, these units will independently store all user settings.

### Guaranteed For Robust, Durable Operation

Equipped with an anti-vibration system, and durably designed for daily hard duty and long life, these incubated digital thermostatic shakers will be a valuable asset and dependable partner in your lab.

## Specifications

Microplate Capacity	2
Supported Microplate Dimensions	86 x 128 x 20 mm
Temperature Range	Ambient +3 up to 60 °C
Temperature Control Accuracy	0.1 °C
Platform Rotation Type	Orbital
Platform Rotation Orbit	1.5 mm
Platform Rotation Speed	100 - 1300 RPM
Timer	1 - 999 min
Ambient Temperature Range	from +10 to +45 °C
Relative Atmospheric Moisture at 20 °C	max 80 %
Power Supply	100-240V; 50/60 Hz
Power Consumption	140 W
External Dimensions (L x W x H)	305 x 280 x 120 mm
Weight	6.4 kg

