Product Name:	ABT-HC-LP-72-TS
Description:	Templog Premier Glass Door Laboratory Refrigerator
·	72 Cu. Ft. capacity
	Three swing glass doors, self-closing, right hinged, not reversible Microprocessor temperature controller
	Adjustable operating temperature range: 1°C - 10°C
	Touch Screen Digital Temperature Display and Alarm Module
	Password-protected control panel
	Sample simulated digital temperature display; .1° Resolution, adjustable
	temperature display in Celsius or Fahrenheit
	Active temperature scale bar display
	Resettable 1-point min/max history
	Digital 24-hour temperature chart
	Temperature data logging
	USB port for data transfer and software updates
	Real-time operational display clock
	4-20mA output
	Electronic troubleshooting guide Electronic QR Code to access Owner's Manual & technical support
	contact information
	Adjustable alarm volume
	Audible and visual high/low temperature alarms
	2 probes; 1 in air and 1 in sample bottle
	Sensor error alarm
	Power failure alarm
	Door ajar alarm
	Low battery alarm
	Operation indicator
	Alarm validation (audible, visual, and remote alarm) and alarm mute with ring back
	Remote alarm contacts
	Twelve adjustable shelves (adjustable in ½" increments)
	Forced draft air circulation Keyed door locks
	Magnetic door gasket for positive seal
	Heavy duty door handles
	LED interior lights are safety shielded and switch controlled
	Swivel casters (3 ½")
	probe access port (3/8")
	White powder-coated steel exterior and interior
	High density urethane foam cabinet insulation
	Hydrocarbon, natural refrigerant (R290)
	Three year parts and labor warranty, plus an additional two year compressor parts
	warranty
	Exterior dimensions: 81" W x 34" D x 78 1/4" H without casters; 81 3/4" H with
	casters
	Cycle defrost
	115V, 60 Hz, 7.5 Amps, 1/2 HP   ETL   listed
	Shipping weight: 743 lbs.
	ompping worgin. 740 lbs.