

Oxidation Solution

SR664-20

Version 2.0

Revision Date 08/07/2018

Print Date 07/31/2019

SECTION 1. IDENTIFICATION

Product name	:	Oxidation Solution
Number	:	00000011429
Product Use Description	:	Laboratory chemicals, Oxidation Reagent for DNA/RNA Synthesis
Manufacturer or supplier's details	:	Honeywell International Inc. 1953 South Harvey Street Muskegon, MI 49442
For more information call	:	1-800-368-0050 +1-231-726-3171
		(Monday-Friday, 9:00am-5:00pm)
In case of emergency call	:	Medical: 1-800-498-5701 or +1-303-389-1414 Transportation (CHEMTREC): 1-800-424-9300 or +1-703-527-3887
	:	(24 hours/day, 7 days/week)
SECTION 2. HAZARDS IDENTIF	ICA	TION
Emergency Overview		
Form		: liquid, clear
Color		: colourless to yellowish
Odor		: strong pungent
		Page 1 / 17



Oxidation Solution

SR664-20

Symbol(s)

Version 2.0

Revision Date 08/07/2018

Print Date 07/31/2019

Classification of the substance or mixture

Classification of the substance or mixture	:	Flammable liquids, Category 3 Acute toxicity, Category 4, Oral Acute toxicity, Category 4, Inhalation Acute toxicity, Category 4, Dermal
		Eye irritation, Category 2A Carcinogenicity, Category 2

GHS Label elements, including precautionary statements

:		

Signal word	: Warning
Hazard statements	 Flammable liquid and vapour. Harmful if swallowed, in contact with skin or if inhaled. Causes serious eye irritation. Suspected of causing cancer.
Precautionary statements	 Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area.
	Page 2 / 17
	Page 2 / 17



Oxidation Solution

SR664-20

Version 2.0 Revision Date 08/07/2018 Print Date 07/31/2019 Wear protective gloves/protective clothing/eye protection/face protection. Response: IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell. Rinse mouth. IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Wash contaminated clothing before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction. Storage: Store in a well-ventilated place. Keep cool. Store locked up. Disposal: Dispose of contents/ container to an approved waste disposal plant. Carcinogenicity ACGIH: Pyridine 110-86-1 A3: Confirmed animal carcinogen SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS : Mixture Chemical nature

Page 3 / 17



Oxidation Solution

rsion 2.0		Revision Date 08/07/2018	Print Date 07/31/2
		0.0 M	
Chemical	nam	e CAS-No.	Concentration
Pyridine		110-86-1	88.70 %
Water		7732-18-5	10.00 %
lodine		7553-56-2	1.30 %
TION 4. FIRST AID MEASU	IRES :	Remove to fresh air. If not breathing breathing is difficult, give oxygen. U	
Skin contact	:	provided a qualified operator is pres Wash off immediately with plenty of minutes. Take off contaminated cloth	ent. Call a physician. water for at least 15
		Wash contaminated clothing before	re-use. Call a physician.
Eye contact	:	Rinse immediately with plenty of wa for at least 15 minutes. Call a physic	
Ingestion	:	Do not induce vomiting without med anything by mouth to an unconsciou	
Notes to physician			
Indication of immediate medical attention and special treatment needed, in necessary	:	Treat symptomatically.	
TION 5. FIREFIGHTING MI	EASL	IRES	
Suitable extinguishing medi	a	: Carbon dioxide (CO2) Dry chemical Alcohol-resistant foam	
		Page 4 / 17	



		Devision Data 08/07/2019	Drint Data 07/24/20
ersion 2.0		Revision Date 08/07/2018	Print Date 07/31/20
		Cool closed containers exposed to	fire with water sprav
		Cool closed containers exposed to	ine with water spray.
Unsuitable extinguishing media	:	Do not use a solid water stream as fire.	it may scatter and spread
Specific hazards during	:	Flammable.	
firefighting		Vapours may form explosive mixtue Vapours are heavier than air and m	
		Vapors may travel to areas away from	
		igniting/flashing back to vapor source	ce.
		In case of fire hazardous decompose produced such as:	sition products may be
		Hydrogen cyanide (hydrocyanic ac	id)
		Ammonia	
		Carbon dioxide (CO2), carbon mon nitrogen (NOx), dense black smoke	
Special protective equipment for firefighters	:	Wear self-contained breathing appa	aratus and protective suit.
3			
ECTION 6. ACCIDENTAL RELE	EAS	E MEASURES	
Demonstrations			
Personal precautions, protective equipment and	:	Wear personal protective equipment Immediately evacuate personnel to	
emergency procedures		Keep people away from and upwind	
		Ensure adequate ventilation.	
		Remove all sources of ignition. Do not swallow.	
		Avoid breathing vapours, mist or gas	S.
		Avoid contact with skin, eyes and clo	
Environmental precautions	:	Prevent further leakage or spillage if	safe to do so.
		Prevent product from entering drains	8.
		Discharge into the environment mus	
		Do not flush into surface water or sa Do not allow run-off from fire fighting	
		courses.	
Methods and materials for	:	Ventilate the area.	
		Page 5 / 17	
		u de la companya de	



Ś	SF	R66	64-	·20

R664-20 rsion 2.0	Povision Data 09/07/2019	Print Date 07/31/2
	Revision Date 08/07/2018	
containment and cleaning up	No sparking tools should be used. Use explosion-proof equipment. Contain and collect spillage with non- materials, e.g. sand, earth, vermiculit place in container for disposal accord (see section 13).	e, diatomaceous earth and
CTION 7. HANDLING AND ST Handling	ORAGE	
Precautions for safe handling	 Wear personal protective equipment. Use only in well-ventilated areas. Keep container tightly closed. Do not smoke. Do not swallow. Avoid breathing vapours, mist or gas. Avoid contact with skin, eyes and clo 	
Advice on protection against fire and explosion	 Keep away from fire, sparks and heat Take precautionary measures agains Ensure all equipment is electrically gr transfer operations. Keep product and empty container as of ignition. No sparking tools should be used. Use explosion-proof equipment. No smoking. 	t static discharges. rounded before beginning
Storage		
Conditions for safe storage, including any incompatibilities	 Store in area designed for storage of from physical damage. Keep containers tightly closed in a dr place. Containers which are opened must b kept upright to prevent leakage. Keep away from heat and sources of Keep away from direct sunlight. 	y, cool and well-ventilated e carefully resealed and ignition.
	Store away from incompatible substa	nces.



SR664-20		
/ersion 2.0	Revision Date 08/07/2018	Print Date 07/31/2019
	Container hazardous when emp Do not pressurize, cut, weld, bra containers to heat or sources of	aze, solder, drill, grind or expose
ECTION 8. EXPOSURE CONT	ROLS/PERSONAL PROTECTION	
Protective measures	: Ensure that eyewash stations a the workstation location.	nd safety showers are close to
Engineering measures	: Use with local exhaust ventilatio Prevent vapour buildup by provi and after use.	n. ding adequate ventilation during
Eye protection	: Do not wear contact lenses. Wear as appropriate: Safety glasses with side-shields If splashes are likely to occur, w Goggles or face shield, giving c	/ear:
Hand protection	: Solvent-resistant gloves Gloves must be inspected prior Replace when worn.	to use.
Skin and body protection	: Wear as appropriate: Solvent-resistant apron Flame retardant antistatic protec If splashes are likely to occur, w Protective suit	-
Respiratory protection	 In case of insufficient ventilation equipment. For rescue and maintenance we self-contained breathing appara Use NIOSH approved respirator 	ork in storage tanks use tus.
Hygiene measures	 When using, do not eat, drink of Wash hands before breaks and product. Keep working clothes separately Remove and wash contaminate 	immediately after handling the y.
	Page 7 / 17	



Oxidation Solution

SR664-20

Version 2.0

Revision Date 08/07/2018

Print Date 07/31/2019

Do not swallow. Avoid breathing vapours, mist or gas. Avoid contact with skin, eyes and clothing.

Exposure Guidelines

Components	CAS-No.	Value	Control parameters	Upda te	Basis
Pyridine	110-86-1	TWA : Time weighted average	(1 ppm)	2008	ACGIH:US. ACGIH Threshold Limit Values
Pyridine	110-86-1	REL : Recomm ended exposure limit (REL):	15 mg/m3 (5 ppm)	2005	NIOSH/GUIDE:US. NIOSH: Pocket Guide to Chemical Hazards
Pyridine	110-86-1	PEL : Permissi ble exposure limit	15 mg/m3 (5 ppm)	02 2006	OSHA_TRANS:US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)
Pyridine	110-86-1	TWA : Time weighted average	15 mg/m3 (5 ppm)	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000)
lodine	7553-56-2	STEL :	(0.1 ppm)	03	ACGIH:US. ACGIH

Iounic		1000 00 2	UILL .		00		1
			Short		2014	Threshold Limit	
			term			Values	
			exposure				
			limit				
Further :	:	Form of exposure :	Vapor and	aerosol.			
information							

Page 8 / 17



Oxidation Solution

SR664-20

Version 2.0

Revision Date 08/07/2018

Print Date 07/31/2019

Further : F information : I	Form of exposure 7553-56-2		raction and vap	or	1
lodine	7553-56-2	•		01.	
		Ceil_Tim e : Ceiling Limit Value and Time Period (if specified) :	1 mg/m3 (0.1 ppm)	2005	NIOSH/GUIDE:US. NIOSH: Pocket Guide to Chemical Hazards
lodine	7553-56-2	Ceiling : Ceiling Limit Value:	1 mg/m3 (0.1 ppm)	02 2006	OSHA_TRANS:US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)
lodine	7553-56-2	Ceiling : Ceiling Limit Value:	1 mg/m3 (0.1 ppm)	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000)
TION 9. PHYSICAL			ES		
Physical state		id, clear	allowiah		
Color Ddor		ourless to ye	EIIOWISTI		
		e: Not appli	cable		
Melting point/range		2.2 °C			
		Page 9	/ 17		
		l age 9	, .,		



Note: The physical data is that of the n Boiling point/boiling range : 115.25 °C at 1,013 hPa Note: The physical data is that of the n Flash point : 81 °F (27 °C) Method: closed cup Lower explosion limit : 1.8 %(V) Note: The physical data is that of the n Upper explosion limit : 1.8 %(V) Note: The physical data is that of the n Vapor pressure : 21.3 hPa at 20 °C(68 °F)Note: The physical data component. Vapor density : 2.7 Note: (Air = 1.0), The physical data component. Density : 0.983 g/cm3 at 20 °C Note: The physical data is that of the n Water solubility : Note: completely soluble	Print Date 07/31/
Boiling point/boiling range : 115.25 °C at 1,013 hPa Note: The physical data is that of the n Flash point : 81 °F (27 °C) Method: closed cup Lower explosion limit : 1.8 %(V) Note: The physical data is that of the n Upper explosion limit : 12.4 %(V) Note: The physical data is that of the n Vapor pressure : 21.3 hPa at 20 °C(68 °F)Note: The physical data component. Vapor density : 2.7 Note: (Air = 1.0), The physical data component. Density : 0.983 g/cm3 at 20 °C Note: The physical data is that of the n	
Boiling point/boiling range : 115.25 °C at 1,013 hPa Note: The physical data is that of the n Flash point : 81 °F (27 °C) Method: closed cup Lower explosion limit : 1.8 %(V) Note: The physical data is that of the n Upper explosion limit : 12.4 %(V) Note: The physical data is that of the n Vapor pressure : 21.3 hPa at 20 °C(68 °F)Note: The physical data component. Vapor density : 2.7 Note: (Air = 1.0), The physical data component. Density : 0.983 g/cm3 at 20 °C Note: The physical data is that of the n	
Note: The physical data is that of the n Flash point : 81 °F (27 °C) Method: closed cup Lower explosion limit : 1.8 %(V) Note: The physical data is that of the n Upper explosion limit : 12.4 %(V) Note: The physical data is that of the n Vapor pressure : 21.3 hPa at 20 °C(68 °F)Note: The physical data component. Vapor density : 2.7 Note: (Air = 1.0), The physical data component. Density : 0.983 g/cm3 at 20 °C Note: The physical data is that of the n	iain component.
Lower explosion limit : 1.8 %(V) Note: The physical data is that of the n Upper explosion limit : 12.4 %(V) Note: The physical data is that of the n Vapor pressure : 21.3 hPa at 20 °C(68 °F)Note: The physical data component. Vapor density : 2.7 Note: (Air = 1.0), The physical data component. Density : 0.983 g/cm3 at 20 °C Note: The physical data is that of the n	ain component.
Note: The physical data is that of the nUpper explosion limit: 12.4 %(V) Note: The physical data is that of the nVapor pressure: 21.3 hPa at 20 °C(68 °F)Note: The physical data component.Vapor density: 2.7 Note: (Air = 1.0), The physical data component.Density: 0.983 g/cm3 at 20 °C Note: The physical data is that of the n	
Note: The physical data is that of the nUpper explosion limit: 12.4 %(V) Note: The physical data is that of the nVapor pressure: 21.3 hPa at 20 °C(68 °F)Note: The physical data component.Vapor density: 2.7 Note: (Air = 1.0), The physical data component.Density: 0.983 g/cm3 at 20 °C Note: The physical data is that of the n	
Note: The physical data is that of the n Vapor pressure : 21.3 hPa at 20 °C(68 °F)Note: The physical data component. Vapor density : 2.7 Note: (Air = 1.0), The physical data component. Density : 0.983 g/cm3 at 20 °C Note: The physical data is that of the n	ain component.
at 20 °C(68 °F)Note: The physical data component. Vapor density : 2.7 Note: (Air = 1.0), The physical data component. Density : 0.983 g/cm3 at 20 °C Note: The physical data is that of the n	nain component.
component. Density : 0.983 g/cm3 at 20 °C Note: The physical data is that of the n	is that of the main
Note: The physical data is that of the n	a is that of the main
Water solubility : Note: completely soluble	nain component.
Ignition temperature : 482 °C Method: The physical data is that of th	e main component.
Page 10 / 17	



Oxidation Solution

SR664-20

Version 2.0

Revision Date 08/07/2018

Print Date 07/31/2019

SECTION 10. STABILITY AND REACTIVITY

Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Hazardous polymerisation does not occur. Forms highly explosive by-product with Trifluoromethyl hypofluorite in reactions where used as an acid receptor.
Conditions to avoid	: Heat, flames and sparks. Keep away from direct sunlight.
Incompatible materials	 Strong oxidizing agents Strong acids Acid chlorides Chloroformates Fluorine May attack many plastics, rubbers and coatings.
Hazardous decomposition products	 In case of fire hazardous decomposition products may be produced such as: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke. Hydrogen cyanide (hydrocyanic acid) Ammonia

SECTION 11. TOXICOLOGICAL INFORMATION

Acute oral toxicity Pyridine

: LD50: 800 - 1,600 mg/kg Species: Rat

Acute inhalation toxicity

Page 11 / 17



R664-20		
rsion 2.0	Revision Date 08/07/2018	Print Date 07/31/20
Pyridine	: LC50: 5400 ppm, vapour Exposure time: 4 h	
lodine	Species: Rat, male : LC50: > 4.588 mg/l , dust/mist Exposure time: 4 h Species: Bet	
Acute dermal toxicity Pyridine	Species: Rat : LD50: > 1,000 - < 2,000 mg/kg Species: Rabbit	
lodine	Method: OECD Test Guideline 402 : LD50: 1,425 mg/kg Species: Rabbit, male	
Skin irritation lodine	: Species: reconstructed human epiderr Result: Irritating to skin.	nis (RhE)
Eye irritation Pyridine	: Species: Rabbit Result: Irritating to eyes.	
Pyridine	: Test Method: Ames test Result: negative	
	: Test Method: Chromosome aberration Cell type: Chinese Hamster Ovary Cel Result: negative	
	: Test Method: Cell Transformation Tes Result: negative	t
Further information Pyridine	: Note:	
	Page 12 / 17	



Oxidation Solution SR664-20 Version 2.0 Revision Date 08/07/2018 Print Date 07/31/2019 Confirmed animal carcinogen with unknown relevance to humans. SECTION 12. ECOLOGICAL INFORMATION Toxicity to fish Pyridine : flow-through test LC50: 99 mg/l Exposure time: 96 h Species: Pimephales promelas (fathead minnow) lodine : LC50: 1.67 mg/l Exposure time: 96 h Species: Oncorhynchus mykiss (rainbow trout) Toxicity to daphnia and other aquatic invertebrates : EC50: 320 mg/l Pyridine Exposure time: 48 h Species: Daphnia magna (Water flea) Method: OECD Test Guideline 202 : LC50: 0.55 mg/l lodine Exposure time: 48 h Species: Daphnia magna (Water flea) Toxicity to algae lodine : Growth inhibition EC50: 0.13 mg/l Exposure time: 72 h Species: Desmodesmus subspicatus (green algae) Method: OECD Test Guideline 201

Further information on ecology

Additional ecological information

Pyridine	: Harmful to aquatic organisms.
	Page 13 / 17



Oxidatio	n Solution		
SR664-20 Version 2.0		evision Date 08/07/2018	Print Date 07/31/2019
lodine		armful to aquatic organisms, may ects in the aquatic environment.	cause long-term adverse
SECTION 13.	DISPOSAL CONSIDERATI	ONS	
Disposal		oserve all Federal, State, and Loc gulations.	al Environmental
Disposal	methods : Di	spose according to legal requirem	ients.
Packagir	ng : Le dis	gal requirements are to be consider sposal of used packaging materia	dered in regard of reuse or ls
SECTION 14.	TRANSPORT INFORMATI	ON	
DOT	UN/ID No. Proper shipping name Class Packing group Hazard Labels	: UN 1993 : Flammable liquids, n.o.s (Pyridine) 3 III 3	5.
ΙΑΤΑ	UN/ID No. Description of the goods Class Packaging group Hazard Labels Packing instruction (carge aircraft) Packing instruction (passenger aircraft) Packing instruction (passenger aircraft)	: UN 1993 : Flammable liquids, n.o.s (Pyridine) : 3 : III : 3 o : 366 : 355 : Y344	;.
	/	: UN 1993	
IMDG	UN/ID No.		



Oxidation Solution

SR664-20

Version 2.0

Revision Date 08/07/2018

Print Date 07/31/2019

Description of the goods	: Flammable liquids, n.o.s. (PYRIDINE)
Class	: 3
Packaging group	: 111
Hazard Labels	: 3
EmS Number	: F-E, S-E
Marine pollutant	: no

SECTION 15. REGULATORY INFORMATION

Inventories

US. Toxic Substances Control Act	: On TSCA Inventory
Australia. Industrial Chemical (Notification and Assessment) Act	: On the inventory, or in compliance with the inventory
Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL)	: All components of this product are on the Canadian DSL
Japan. Kashin-Hou Law List	: On the inventory, or in compliance with the inventory
Korea. Existing Chemicals Inventory (KECI)	: On the inventory, or in compliance with the inventory
Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act	: On the inventory, or in compliance with the inventory
China. Inventory of Existing Chemical Substances	: On the inventory, or in compliance with the inventory
New Zealand. Inventory of Chemicals (NZloC), as published by ERMA New Zealand	: On the inventory, or in compliance with the inventory
	Page 15 / 17



Oxidation Solution

SR664-20

Version 2.0

Revision Date 08/07/2018

Print Date 07/31/2019

National regulatory inform	ation	
JS. Drug Enforcement Administration (DEA) Listed Precursor and Essential Chemicals (21 CFR 1310)		States Drug Enforcement Authority (DEA) List of Essential Chemicals
JS. EPA CERCLA Hazardous Substances (40 CFR 302)		7553-56-2 omponent(s) of this product is/are subject to g under 40 CFR 302 when release exceeds the antity (RQ):
	Reportable qua : Pyridine	ntity: 1000 lbs 110-86-1
SARA 302 Components		n this material are subject to the reporting f SARA Title III, Section 302.
SARA 313 Components		omponents are subject to reporting levels SARA Title III, Section 313: 110-86-1
SARA 311/312 Hazards	: Fire Hazard Acute Health Ha Chronic Health	
CERCLA Reportable Quantity	: 1127 lbs	
California Prop. 65	listed below, kn	IG: This product can expose you to chemicals, nown to the State of California to cause cancer. nation go to www.P65Warnings.ca.gov.
	Pyridine	110-86-1
Massachusetts RTK	: Pyridine	110-86-1



Oxidation Solution

SR664-20

Version 2.0	Revision Date 08/07/2018	Print Date 07/31/2019
	. In all a	7550 50 0
	: lodine	7553-56-2
New Jersey RTK	: Pyridine	110-86-1
	: lodine	7553-56-2
Pennsylvania RTK	: Pyridine	110-86-1
	: lodine	7553-56-2
	. Iouine	7555-56-2
1		

SECTION 16. OTHER INFORMATION

	HMIS III	NFPA
Health hazard	: 2*	2
Flammability	: 3	3
Physical Hazard	: 0	
Instability	:	0

* - Chronic health hazard

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Previous Issue Date: 05/13/2014

Prepared by Honeywell Performance Materials and Technologies Product Stewardship Group