



Airstream® Reliant Class II Type A2 Biosafety Cabinet, Model AR2-459



Airstream® Class II Type A2 Biosafety Cabinet, Model AC2-459-NS

Airstream® Airstream® RELIANT

Class II Type A2 Biological Safety Cabinets
The World's Leading Energy-Efficient, Quiet, and Ergonomic Biosafety Cabinet



ESCO

WORLD CLASS. WORLDWIDE.



RS 232 Serial Interface Port and Voltage Free Relay Contact (Not Applicable for AR2)

- Send operational information to Building Management System (BMS)
- Zero Volt Relay Contact to turn ON/OFF exhaust blower and signal the building alarm



Sentinel™ Gold Microprocessor Controller (for AC2)

- Displays all safety information on one screen
- Centered and angled down for easy reach & viewing
- Selectable Quickstart mode for fast operation



Rocker Switches and Pressure Gauge (for AR2)

- Easy to use switches
- Displays filter loading status
- Manually adjustable UV timer



Single-Piece Wall

- Easy to reach service fixture and outlets
- Large radius for easy cleaning



Single-Piece Work Tray

- Recessed to contain spillage
- Sloped perimeter that's easy to wipe



Raised Arm Rest

- Helps prevent grille blocking
- Comfortable working posture



Available in 0.9, 1.2, 1.5 and 1.8 meter width (3', 4' 5" and 6')



NSF 49



UL 61010

Airstream® / Airstream® • RELIANT

Class II Type A2 • Biological Safety Cabinets





Airflow Sensor (Not Applicable for AR2)

- Monitors real-time airflow for safety
- Alert the user if airflow is insufficient



Energy-Efficient DC ECM Motor

- The leading energy efficient Class II Type A2 Biosafety Cabinet in the world with 70% Energy savings compared to AC motor
- Stable airflow, despite building voltage fluctuations & filter loading
- Stand by mode to further reduce power consumption by 60%




ULPA Filter

- 10x Filtration efficiency of HEPA filter
- Creates ISO Class 3 work zone instead of industry-standard ISO Class 5

Dynamic Chamber

- Blower plenum and side walls are surrounded by negative pressure
- Prevent contaminants from escaping outside




■ Positive pressure
■ Negative pressure

Angled Sash

- 5° angled front to optimize user comfort, reduce glare and maximize reach into the work area

ISOCIDE™ Powder Coat

- Silver-ion impregnated powder coat
- Inhibit microbial growth to improve safety




Removable Paper Catch

- Easy to clean
- Optional pre-filter can be fitted



Certification

	Biosafety Cabinets	Air Quality	Filtration	Electrical Safety
Standards Compliance	NSF / ANSI 49 NSF*	ISO 14644.1, Class 3, Worldwide JIS B9920, Class 3, Japan JIS B55295, Class 3, Japan US Fed Std 209E, Class 1 USA	EN-1822 (H14), Europe IEST-RP-CC001.3, USA IEST-RP-CC007, USA IEST-RP-CC034.1, USA	UL-61010A-1, USA CSA22.2, No.1010-192, Canada EN-61010-1, Europe IEC61010-1, Worldwide




- ULPA-filtered air
- Unfiltered / potentially contaminated air
- Room air / Inflow air

Cabinet Filtration System

- Ambient air is pulled through front grille to create inflow, without going into the work surface. Inflow is joined by half of the downflow, to create front air curtain that is fine-tuned to create a large performance envelope. The combined air stream travels through the back air column towards the blower.
- Approximately 1/3 of the air in the common plenum is exhausted through the ULPA filter to the room. The remaining 2/3 of the air is passed through the downflow ULPA filter and into the work area as a vertical laminar flow air to create ISO Class 3 work surface and prevents cross contamination.
- Near the work surface, the downflow splits. About half goes to the front grille, and half goes to the rear grille. A small portion enters the side capture zones to prevent dead air corners (small blue arrows)
- The design was optimized to give large performance envelope, that provides operator and product protection at wide Inflow and Downflow variation from the Nominal point.


Performance Envelope Test of AC2-NS





- Nominal Airflow
- Personnel / Product Protection
- Area of Personnel and Product Protection
- ▲ NO Personnel / Product Protection
- Area of NO Personnel and Product Protection

AC2-NS Engineering Drawing

4



1. Airflow Sensor
2. Voltage Free Relay Contact
3. RS232 Port
4. Power Inlet
5. Esco Sentinel™ Gold Microprocessor Control System
6. Tempered Glass Sliding Sash Window
7. Ergonomic Sash Handle
8. Single Piece Stainless Steel Work Tray
9. Electrical Panel
10. Curved Front Panel
11. Control Panel
12. Energy-efficient T5 Fluorescent Lamps
13. IV Bar Retrofit Kit Provision
14. Steris VHP / Bioquell HPV Provision (Optional)
15. Provision for Service Fixtures (2 on each side)
16. Duplex GFCI Electrical Outlets (1 on each side)
17. Stainless Steel Arm Rest
18. Drain Hole
19. Exhaust ULPA / H14 Filter
20. DC ECM Blower (Energy-Efficient & Self-Compensating)
21. Downflow ULPA / H14 Filter
22. Paper Catch



Airstream® / Airstream® • RELIANT

Class II Type A2 • Biological Safety Cabinets

TECHNICAL SPECIFICATIONS

Model	110-130 VAC 50/60 Hz	AC2-3S9-NS 2010945	AC2-4S9-NS 2010752	AC2-5S9-NS 2010977	AC2-6S9-NS 2010925
		AR2-3S9 2010982	AR2-4S9 2010753	AR2-5S9 2010984	AR2-6S9 2010986
External Dimensions (W x D x H) mm		1035 x 753 x 1400 mm (40.7" x 29.6" x 55.1")	1340 x 753 x 1400 mm (52.8" x 29.6" x 55.1")	1645 x 753 x 1400 mm (64.8" x 29.6" x 55.1")	1950 x 753 x 1400 mm (76.8" x 29.6" x 55.1")
Gross Internal Dimensions (W x D x H) mm		915 x 580 x 660 mm (36" x 22.8" x 26")	1220 x 580 x 660 mm (48" x 22.8" x 26")	1525 x 580 x 660 mm (60" x 22.8" x 26")	1830 x 580 x 660 mm (72" x 22.8" x 26")
Usable Work Area		0.42 m ² (4.5 ft ²)	0.56 m ² (6.0 ft ²)	0.70 m ² (7.5 ft ²)	0.86 m ² (9.3 ft ²)
Tested Opening		203 mm (8")			
Average Inflow Velocity		0.53 m/s (105 fpm)			
Average Downflow Velocity		0.30 m/s (60 fpm)			
Airflow Volume	Inflow	354 cmh (208 cfm)	473 cmh (278 cfm)	591 cmh (348 cfm)	709 cmh (417 cfm)
	Downflow	553 cmh (325 cfm)	738 cmh (434 cfm)	922 cmh (543 cfm)	1107 cmh (652 cfm)
	Exhaust	354 cmh (208 cfm)	473 cmh (278 cfm)	591 cmh (348 cfm)	709 cmh (417 cfm)
	Required Exhaust With Optional Thimble Exhaust Collar	531 cmh (313 cfm)	710 cmh (418 cfm)	887 cmh (522 cfm)	1064 cmh (626 cfm)
	Static Pressure For Optional Thimble Exhaust Collar	32 Pa / 0.12 in H ₂ O	45 Pa / 0.18 in H ₂ O	57 Pa / 0.23 in H ₂ O	68 Pa / 0.27 in H ₂ O
ULPA Filter Typical Efficiency		>99.999% at 0.1 to 0.3 micron, ULPA as per IEST-RP-CC001.3 USA >99.999% at MPPS, H14 as per EN 1822 EU			
Sound Emission per NSF / ANSI 49*		57.5 dBA		58.5 dBA	60.5 dBA
Fluorescent Lamp Intensity (lux)		1983 lux (184 foot candles)	1700 lux (158 foot candles)	1200 lux (95 foot candles)	1647 lux (153 foot candles)
Cabinet Construction	Main body	1.2 mm (0.05") / 18 gauge EG Steel With Isocide™ Oven-Baked Epoxy-Polyester Powder Coating			
	Work Zone	1.5 mm (0.06") / 16 gauge, SS 304, 4B finish			
	Side Walls	1.5 mm (0.06") / 16 gauge, SS 304, 4B finish			
Electrical 110-130VAC 50/60Hz	Cabinet Full Load Amps (FLA)	11	11.5	12.5	15
	Heat Load (BTU / Hr)	503	628	698	999
	Nominal Power Consumption (W)	160	200	222	318
Net Weight**		188 Kg (414 lbs)	230 Kg (507 lbs)	288 Kg (634 lbs)	346 Kg (763 lbs)
Shipping Weight**		216 Kg (476 lbs)	285 Kg (628 lbs)	356 Kg (785 lbs)	428 Kg (944 lbs)
Shipping Dimensions, Maximum (W x D x H)**		1120 x 820 x 1760 mm (44" x 32" x 69")	1450 x 820 x 1760 mm (57" x 32" x 69")	1720 x 820 x 1760 mm (68" x 32" x 69")	2050 x 820 x 1760 mm (80" x 32" x 69")
Shipping Volume, Maximum**		1.62 m ³ (57 ft ³)	2.09 m ³ (74 ft ³)	2.48 m ³ (88 ft ³)	2.96 m ³ (105 ft ³)

Specifications are subject to change without notice.

*Noise reading in open field condition / anechoic chamber. Noise reading in normal room varies by room size, layout, and background noise, but may reach roughly 3-4 dBA above these values.

**Cabinet only, excludes optional stand.

AC2 and AR2 Cabinets Save Money and Environment



Description	AC2-4S -NS /AR2 with DC ECM blower	Typical BSC with AC Blower	Savings	Units
Instantaneous Power	200	800	600	Watt
Hours of Operation in a year	2000			Hours
Energy	400	1600	1200	kWh
Energy cost in USA at \$ 0.10 / kWh	40	160	120	USD
Energy cost in EU at € 0.20 / kWh	80	320	240	Euro
CO ₂ released in USA at 1 lbs / kWh	400	1600	1200	lbs
CO ₂ emission in EU at 0.35 Kg / kWh	140	560	420	Kg

Accessories for AC2-NS and AR2 Biological Safety Cabinets

Cabinet	Standard Unit	AC2-3S9-NS	AC2-4S9-NS	AC2-5S9-NS	AC2-6S9-NS
		2010945	2010752	2010978	2010963
Cabinet	Unit with Cable Port	AR2-3S9	AR2-4S9	AR2-5S9	AR2-6S9
		2010982	2010753	2010984	2010986
Exhaust Ducting	Anti-blowback Valve 10 inches	ABBV-10P 5170352			
	Tri-safe Exhaust Collar with Alarm (not applicable for AR2)	TEM-4 2010606			
	Thimble Exhaust Collar with Alarm (not applicable for AR2)	ECO-A-AC23 5170618	ECO-A-AC24 5170619	ECO-A-AC25 5170620	ECO-A-AC26 5170621
	Exhaust Damper	B2-DAMPER 5170352			



ABBV-10P



TEM-4



Thimble Exhaust Collar with Alarm



B2-DAMPER

Airstream® / Airstream® •RELIANT

Class II Type A2 • Biological Safety Cabinets

Hydrogen Peroxide Decontamination Kit	VHP In Port (Ø 1")	VHP-IN PORT 5170552			
	VHP Out Top Box for Cabinet WITH Exhaust Collar Installed (Ø 1")	VHP-ECO/OUT 5170554	VHP-ECO/OUT 5170615	VHP-ECO/OUT 5170616	VHP-ECO/OUT 5170617
	VHP Out Top Box for Cabinet WITHOUT Exhaust Collar Installed (Ø 1")	VHP OUT TOP BOX 3ft 5170553	VHP OUT TOP BOX 4ft 5170612	VHP OUT TOP BOX 5ft 5170613	VHP OUT TOP BOX 6ft 5170614
Work Zone	UV Lamp	UV-15A 5170251	UV-30A-L 5170255		
	IV Bar	IV-910 5170499	IV-1215 5170231	IV-1520 5170500	IV-1825 5170501
Electrical Outlet	GFCI	EO-GFCI 5170071			
Service Fixtures	US SF-Universal-22 mm	SF-2U22 5170504			
Support Stands, Ships Flat	Fixed Stand with Leveling Feet, 28" height	SAL-3A0 Gen 2 5130170	SAL-4A0 Gen 2 5130134	SAL-5A0 Gen 2 5130171	SAL-6A0 Gen 2 5130172
	Fixed Stand with Leveling Feet, 34" height	SAL-3B0 Gen 2 5130174	SAL-4B0 Gen 2 5130175	SAL-5B0 Gen 2 5130176	SAL-6B0 Gen 2 5130177
	Fixed Stand with Caster Wheels, 28" height	SPC-3A0 Gen 2 5130155	SPC-4A0 Gen 2 5130152	SPC-5A0 Gen 2 5130162	SPC-6A0 Gen 2 5130154
	Fixed Stand with Caster Wheels, 34" height	SPC-3B0 Gen 2 5130165	SPC-4B0 Gen 2 5130166	SPC-5B0 Gen 2 5130167	SPC-6B0 Gen 2 5130168
	Telescopic Stand with Leveling Feet, 1" adjustment	STL-3A0 5130050	STL-4A0 5130051	STL-5A0 5130052	STL-6A0 5130053
	Telescopic Stand with Caster Wheels, 1" adjustment	STC-3A0 5130055	STC-4A0 5130056	STC-5A0 5130057	STC-6A0 5130058
	Motorized height Stand with Caster Wheels	SPM-3A2 5130093	SPM-4A2 5130047	SPM-5A2 5130100	SPM-6A2 5131141
Misc	IQ OQ Protocol	9010179			



VHP-IN PORT



VHP-ECO/OUT



VHP OUT TOP BOX



UV_A-L



IV_-



Electrical Outlet GFCI



SF-2U



SPC-3A0 Gen2



SAL-3A0 Gen2




STC-3A0



SPM-3A2

ESCO GLOBAL NETWORK



- ART Equipment
- Biological Safety Cabinets
- CO₂ Incubators
- Compounding Pharmacy Equipment
- Containment / Pharma Products
- Ductless Fume Hoods
- Freeze Dryers
- Lab Animal Research Products
- Laboratory Centrifuges
- Laboratory Fume Hoods
- Laboratory Ovens and Incubators
- Laboratory Shakers
- Laminar Flow Clean Benches
- PCR Cabinets
- PCR Thermal Cyclers
- Powder Weighing Balance Enclosures
- Ultra-low Temperature Freezers

The Esco Group of Companies is a global life sciences tools provider with sales in over 100 countries. The group is active in lab equipment, pharma equipment and medical devices. Manufacturing facilities are located in Asia and Europe. R&D is conducted worldwide spanning the US, Europe and Asia. Sales, service and marketing subsidiaries are located in 12 major markets including the US, UK, Singapore, Japan, China and India. Regional distribution centers are located in the US, UK, and Singapore.

Life Science • Chemical Research • Assisted Reproductive Technology (ART) • Pharmaceutical Equipment • General Equipment

ESCO

WORLD CLASS. WORLDWIDE.

Esco Micro Pte. Ltd. • 21 Changi South Street 1 • Singapore 486 777
 Tel +65 6542 0833 • Fax +65 6542 6920 • mail@escoglobal.com
 www.escoglobal.com

Esco Technologies, Inc. • 903 Sheehy Drive, Suite F, Horsham, PA 19044, USA
 Toll-Free USA and Canada 1-877-479-3726 • Tel 215-441-9661 • Fax 484-698-7757
 eti.sales@escoglobal.com • www.escolifesciences.us

Esco Global Offices: Bahrain | Bangladesh | China | India | Indonesia | Italy | Japan | Malaysia
 Philippines | Russia | Singapore | South Africa | South Korea | Thailand | United Kingdom | USA | Vietnam



910258_Artstream_Brochure_US_v1_062316
 All trademarks, trade names and other intellectual property are the property of their respective owners. All trademarks and logos used in this material are the property of Esco and the respective companies.