

Refrigerated Heating Circulator Bath with air-cooled cooling machine. Powerful, variable speed, pressure and suction pump, evaporator (cooler) and housing of stainless steel, CFC and H-CFC free. With adjustable overtemperature protection according to DIN 12876.

Pilot ONE:

The new Pilot ONE controller with pioneering technology and advanced control functions brings numerous advantages to routine work. The extensive features list includes a brilliant 5,7" TFT touchscreen display, USB and network connections, an integrated technical glossary and language support in 11 languages (EN, DE, FR, IT, ES, RU, CN, PT, JP, CZ, PL). The Pilot ONE has a convenient navigation system with easily remembered icons and menu categories which are colour sorted to make routine work simpler. Thanks to a favourites menu and One-Click operator guidance all important information is always just a few keystrokes away. Software wizards also help you to set up, ensuring correct settings. The USB port allows connection of the system to a PC or notebook. Together with the Spy software, requirements such as remote control or data transmission are easily achieved in a cost-effective manner. Network integration is easy with the internet port.

The range of functions can be expanded very easily via E-grade at any time by entering a unit specific upgrade code:

E-grade "Exclusive": TAC (True Adaptive Control) - self optimising internal and cascade control, selectable temperature control mode (Internal/Process), programmer with 3 programs (max. 15 steps), ramp function (linear), 5 point calibration, scalable graphic display, favourites menu, display resolution 0,01 K.

E-grade "Professional": Programmer with 10 programs (max. 100 steps), ramp function for temperature gradients (linear and non-linear), 2nd set point, user menus (Administrator level), calendar start.

3-2-1 warranty - registration required.

Technical data according to DIN 12876

| | | |
|--------------------------------------|---------------------------------------|--------------------------------|
| Operating temperature range | -45...200 °C | |
| Temperature stability at -10°C | 0,02 K | |
| temperature set point / display | 5,7" colour Touchscreen | Order-No.: 2019.0006.01 |
| Internal temperature sensor | Pt100 | |
| Sensor external connection | Pt100 | |
| Interface digital | Ethernet, USB (Host u. Device), RS232 | |
| Safety classification | Class III / FL | |
| Heating power | 2,45 kW | |
| Cooling power | | |
| at 100°C | 0,8 kW | |
| at 20°C | 0,8 kW | |
| at 0°C | 0,8 kW | |
| at -20°C | 0,5 kW | |
| at -30°C | 0,15 kW | |
| at -40°C | 0,1 kW | |
| Refrigeration machine | air- and water-cooled, CFC-free | |
| Refrigerant | R507 | |
| Refrigerant quantity | 0,36 kg | |
| Pressure pump | | |
| max. delivery | 33 l/min | |
| max. delivery pressure | 0.7 bar | |
| Suction pump | yes | |
| max. delivery (suction) | 22 l/min | |
| max. delivery pressure (suction) | 0.4 bar | |
| Pump connection | M16x1 male | |
| max. permissible kin. viscosity | 50 mm ² /s | |
| Bath volume | 22 l | |
| Bath capacity with displacement rack | 8,5 l | |
| Width bath opening WxD / bath depth | 280 x 280 / 200 mm | |
| Height of bath opening | 520 mm | |
| Overall dimensions WxDxH ** | 420x565x719 mm | |
| Net weight | 72 kg | |
| Power supply requirement | 208V 2~ 60Hz | |
| max. current | 14,5 A | |

Technical data according to DIN 12876

| | |
|--------------------------|-------|
| Fuse (1 phase) | 16 A |
| Protection class | IP20 |
| max. ambient temperature | 40 °C |
| min. ambient temperature | 5 °C |

from Serial-No.: **207200** **1.0/14**

Technical details and dimensions are subject to change. No liability is accepted for errors or omissions.

Accessories and periphery: mini-USB cable #54949*, bath cover*, Adapter nom. dia. 12*, dummy plugs*, sleeve nuts thread M16x1*, connection tubes, drain valve

* standard equipment

Output data valid for: Room temperature 20° C

in accordance with EN60034-1 the following voltage and frequency tolerances are valid:

Voltage + / - 5% with a simultaneous frequency tolerance of + / - 2%

Example -5% voltage and + 2% frequency -> not allowed!

-5% voltage and - 2% frequency -> allowed

** Please respect space requirements. See operating conditions at www.huber-online.com